

C# - Console Applications



Study Notes

Owner: Satish Talim
File: C# - Console Applications
Last saved: 13th Sept. 2001
Email Id. medunet@vsnl.com
Version β4

Notice:

This documentation is an early release of the final Study Notes, which may change substantially prior to final release.

This document is provided for informational purposes only and Satish Talim makes no warranties, either express or implied, in this document. Information in this document is subject to change without notice.

The entire risk of the use or the results of the use of this document remains with the user. Complying with all applicable international copyright laws is the responsibility of the user.

Microsoft, Windows, Visual Basic, and Visual C++ are either registered trademarks or trademarks of Microsoft Corporation in the U.S.A. and/or other countries.

Other product and company names mentioned herein may be the trademarks of their respective owners.

Table of Contents

1. Introduction	7
1.1 A New Platform?	7
1.2 System Requirements	7
1.3 Purpose of these Study Notes.....	7
1.4 Who can use these Study Notes?	7
1.5 Updates to this document	7
1.6 Recommended Sites on C#	7
1.7 My Workshops on C#	8
1.8 Satish Talim?	8
1.9 Acknowledgements	8
2. C# Program Elements	10
2.1 Overview of the .NET	10
2.2 C# and Java	11
2.3 Our first C# Program – Hello, world.....	11
2.4 Compiler Options	15
2.5 Response files	16
2.6 Compiler Errors	16
2.7 Managed Module.....	16
2.8 ILDASM.....	17
2.9 Naming Guidelines	18
2.9.1 Namespaces	18
2.9.2 Classes	18
2.9.3 Methods.....	18
2.9.4 Method Arguments	18
2.9.5 Interfaces	18
2.9.6 Class members	18
2.10 Automatic memory management.....	18
2.11 Comments	19
2.12 Blocks	22
2.13 Separation	22
2.14 Whitespace	22
2.15 Keywords (76).....	22
2.16 Constants – const / readonly	23
2.17 Variables	23
2.18 Naming constants and variables	24
2.19 Escape sequences	24
2.20 Statements and Expressions.....	25
2.20.1 Empty statement.....	25
2.21 Types.....	25
2.22 Predefined types	28
2.23 Operators	34
2.23.1 checked and unchecked operators.....	35
2.24 Operator overloading.....	36
2.25 Program Control	38
2.25.1 The if statement.....	38
2.25.2 The switch statement.....	38
2.25.3 The while statement	39
2.25.4 The do statement	40
2.25.5 The for statement.....	40
2.25.6 The foreach statement.....	40

C# - CONSOLE APPLICATIONS

2.26 Console I/O.....	40
2.26.1 Console Input	40
2.26.2 Console Output	41
2.27 Array types	41
2.28 Calling methods – ref / out.....	45
2.28.1 Method Overloading	47
2.28.2 Variable Method Parameters - params	47
2.29 Handling Exceptions	48
2.30 Namespaces.....	50
2.31 Namespaces and Assemblies	53
2.32 Summary of Key Concepts	55
3. Object Oriented Concepts.....	59
3.1 What is an Object?.....	59
3.2 The Benefit of Encapsulation	60
3.3 What are Messages?	60
3.4 What are Classes?	61
3.5 What is Inheritance?	62
4. Class and Object.....	64
4.1 Class Declaration	64
4.1.1 Class modifiers	65
4.1.1.1 Abstract classes	66
4.1.1.2 Sealed classes	66
4.1.1.3 Inner Classes	67
4.1.1.4 Base classes	68
4.1.1.5 Internal class	69
4.1.1.6 Interface implementations	69
4.1.2 Class body	69
4.1.2.1 Class members.....	69
4.1.2.2 Signature	71
4.1.2.3 Constructors	71
4.1.2.4 Calling Base Class Constructors	74
4.1.2.5 Static Constructors	74
4.1.2.6 Destructors.....	76
4.1.2.7 Inheritance - Single	77
4.1.2.8 Accessing Base Class Members	77
4.1.2.9 The this Reference	77
4.1.2.10 The new modifier	77
4.1.2.11 Casting between Types	79
4.1.2.12 Access modifiers	80
4.1.2.13 Restrictions on Using Accessibility Levels	81
4.1.2.14 Accessibility Domain.....	81
4.1.2.15 Virtual methods	82
4.1.2.16 Override methods	83
4.2 Interfaces.....	84
4.3 Structs	85
4.4 Enums	86
4.5 Properties.....	87
4.6 Delegates	88
4.6.1 Delegate	88
4.6.2 Multicast Delegates:	89
4.7 Events	90

4.8 Reflection	93
4.9 Assertions.....	94
4.10 MultiThreading – An Introduction	95
4.11 Assignment.....	97
4.12 Summary of Key Concepts	99
5. Using .NET Base Classes.....	102
5.1 The WinCV Tool.....	102
5.2 StringBuilder class	102
5.3 File and Folder operations	103
5.3.1 Finding out information about a File.....	103
5.3.2 Listing Files in a Folder.....	103
5.3.3 Copying and Deleting Files.....	104
5.3.4 Reading Text Files	104
5.3.5 Writing Text Files	105
5.3.6 Reading Binary Files	105
5.3.7 Writing Binary Files	105
5.3.8 Reading/Writing to log files.....	106
5.4 Networking	108
5.4.1 HTTP	108
5.4.2 Generic Request/Response Architecture.....	109
6. Miscellaneous.....	112
6.1 Comparison of C# and Java.....	112
6.1.1 Common features are:	112
6.1.2 Differences.....	113
6.1.3 C# improvements over Java	113
6.2 Web Service.....	113
6.2.1 What is a Web Service?.....	113
6.2.2 Programming Web Services using ASP.NET and C#	113
6.2.2.1 Declare the Web Service:	114
6.2.2.2 Define the Web Service methods:	116
6.2.3 Building ASP.NET Web Services:.....	116
6.2.4 Deploying a Web Service:	117

1. Introduction

1.1 A New Platform?

The crash of the dotcoms and the downturn in the prospects of Java notwithstanding, Microsoft's .NET and C# opens a whole New World of possibilities. There are many people in the industry, which see a great future to the .NET. We now have .NET, a new and exciting technology that finally addresses issues we've been grappling with for years (for example, multi-language development environments, the deployment and versioning problems of large, complex systems, and so on).

1.2 System Requirements

To build and run your C# programs, you will need Windows 2000, IE 5.5, Microsoft .NET SDK (Beta 2), an optional Visual Studio .NET (available for MSDN Universal Subscribers) and a text editor.

The .NET SDK can be downloaded from:

<http://msdn.microsoft.com/downloads/default.asp?url=/downloads/sample.asp?url=/msdn-files/027/000/976/msdncompositedoc.xml&frame=true>

It's a 127 MB download. The C# compiler (csc.exe) currently ships with the .NET beta.

The use of Visual Studio.NET has been intentionally avoided, to focus on the language and runtime environment and not place any restrictions on your particular development environment. Therefore, all the sample codes in these notes will compile and run from the command line.

1.3 Purpose of these Study Notes

To learn the C# language, I had to refer to all available material – books, articles on the net, discussion groups. As I studied the C# language, I kept making notes. I felt the need of a single repository where individuals could go to and know everything about a particular topic in C# – this repository became the Study Notes. I have tried to explain every point of C#, with the help of an example. Please do appreciate that, this is **not** a book on C#.

1.4 Who can use these Study Notes?

These Study Notes supplement my C# lectures and assume a basic knowledge of Java. However, I am confident that it would prove useful to all those interested in learning the C# language.

1.5 Updates to this document

The latest version of this document in .pdf format is always available at the URL:

<http://www.pune-csharp.com/downloads/index.htm>

All feedback / suggestions about this document can be sent to medunet@vsnl.com

1.6 Recommended Sites on C#

Amit Karmakar (based in Sydney, Australia) and I have launched a site

<http://www.pune-csharp.com>

C# - CONSOLE APPLICATIONS

which will cater to all the technical needs of the C# professionals. Two activities on the site which would benefit all C# beginners are:

- C# Study Group – where the C# language can be learnt step-by-step with the help of experts, and
- C# Projects – where everyone can take part and contribute in building a project.

Here are some other sites related to C# -

<http://msdn.microsoft.com/net/>

<http://www.thecodechannel.com/>

<http://www.c-sharpcorner.com/>

<http://www.csharpindex.com/>

<http://www.csharp-station.com/>

<http://www.c-point.com>

<http://www.devx.com/dotnet/resources/>

<http://www.csharphelp.com/>

<http://www.aspwire.com>

<http://www.asptoday.com>

1.7 My Workshops on C#

Some of my workshops on the C# language, being conducted at Pune are -

- Console Applications
- Database Applications with ADO.NET
- WinForms and WebForms
- Web Services

1.8 Satish Talim?

Is a software professional with over 23 years of software consulting experience. He has been working on Java-based software-export projects and corporate training in Java since 1995. His clients include Satyam Ltd., KPIT, IBM ACE, Focus Inc., Kanbay Software Ltd., Global Electronic Commerce Services amongst many others. He is also a certified instructor at the Sun Authorized Java Training center in Pune. He was the founder Director of Infonox Software Pvt. Ltd. (ISPL) based in California, USA and Pune, India. His current area of interest is C#.

1.9 Acknowledgements

These Study Notes would not have been possible without the contribution, support and generous help of many individuals.

I would like to acknowledge the help, right from my Java days, to my student and friend [Amit Karmakar](#), who always believes in me and inspires me to go on to greater heights. Amit is based in Sydney, Australia and is a Web Developer for the Department of Education and Training, in New South Wales, Australia.

[Sunil Kelkar](#), who has always stood by me and helped me in going through these notes and suggest changes. Sunil, is an independent consultant and works in Java and C#, in Pune.

I want to thank [Rahul Waghmare](#), who made me look at and explore C# ! Rahul, is a graphics artist by profession; works in Pune and likes to experiment with various computer languages – Java, VC++, C#.

To all *my students* and *people* on the Internet who provided me with information/feedback, a big thank-you.

I acknowledge all the authors, whose works I have referred. Here is a partial list.

The *C# Programming* book from Wrox Press was the first book I read on C#. I have been highly influenced by this book and it probably reflects in these Study Notes.

[Tom Archer](#), author of *Inside C#* for his valuable tips and help in clarifying many of my doubts in C#. His book helped me understand the internal architecture of C#.

[Ben Albahari](#), author of *C# Essentials* for clarifying my doubt on byte array. The book gives a very precise and to the point description of every element in the language.

[Jesse Liberty](#), author of *Programming C#* for his excellent book.

Anders Hejlsberg and **Scott Wiltamuth** for their excellent work, *C# Language Reference*.

[Ashish Banerjee](#), [Anant Charturvedi](#), [Willy Denoyette](#), [Sunil Gudipati](#), [Shafeen Sarangi](#), [Chris Maunder](#), [Mahesh Chand](#), [Sudhakar Jalli](#), [Pramod Singh](#), [Ashok Kumar P.](#) [Joe Mayo](#), [Brad Wilson](#), [Mark Johnson](#), [Richard Grimes](#), [Mitch Denny](#), [Marc](#) and [Saurabh Nandu](#) for their excellent articles on various aspects of C# and / or their sites on C#, which I have extensively used.

Finally to **Microsoft Corporation** for giving us this C# language.

2. C# Program Elements

C# (pronounced "C sharp") is a simple, modern, object oriented, and type-safe programming language derived from C and C++. C# aims to combine the high productivity of Visual Basic, the elegance of Java and the raw power of C++. We will study the C# language and its use as a tool for programming on the .NET platform.

2.1 Overview of the .NET

.NET shifts the focus in computing from a world in which individual devices and Web sites are simply connected through the Internet to one in which devices, services, and computers work together to provide richer solutions for users.

The .NET platform consists of four separate product groups:

- A set of languages (C#, VB.NET...); a set of development tools (Microsoft Visual Studio .NET...); a comprehensive class library for building web services and web and Window applications; as well as the Common Language Runtime (CLR) to execute objects built within this framework.
- A set of .NET Enterprise Servers (SQL Server 2000, BizTalk 2000) that provide specialised functionality for relational data storage, email, B2B commerce etc.
- Commercial web services, like Project Hailstorm; for a fee.
- New .NET-enabled non-PC devices, from cell phones to PDAs etc.

The **.NET Framework** sits on top of the operating system and consists of the:

- **Common Language Runtime (CLR)**. You can think of the CLR as an agent that manages code at execution time, providing core services such as memory management, thread management, and remoting, while also enforcing strict safety and accuracy of the code. In fact, the concept of code management is a fundamental principle of the runtime. Code that targets the runtime is known as managed code; code that does not target the runtime is known as unmanaged code. **The code that runs within the CLR runs in an encapsulated and managed environment, separate from other processes on the machine.**
- .NET Framework class libraries sometimes called the **Base Class Library (BCL)**. All .NET languages have the .NET Framework class libraries at their disposal. The .NET Framework class libraries include support for everything from file I/O and database I/O to XML and SOAP. The .NET Framework class libraries are very vast. **The BCLs functionality is available to all languages that use the CLR.**
- An universal type system called the .NET **Common Type System (CTS)**. In addition to defining all types, the (CTS) also stipulates the rules that the CLR follows with regard to applications declaring and using these types. **In the world of .NET and C# everything in the CTS is an object.** In fact, not only is everything an object but, even more importantly, all objects implicitly derive from a single base class defined as part of the CTS. This base class called *System.Object*.
- **Common Language Subset (CLS)**, that ensures seamless interoperability between CLS-compliant languages and class libraries. For C# developers, this means that even though C# is a new language, it has complete access to the same rich class libraries that are used by seasoned tools such as Visual Basic and Visual C++. **C# itself does not include a class library. Because the same .NET base class library is shared between all programming languages, a**

developer can take his knowledge of this library with him as he migrates from language to language.

C# is a programming language for developing applications for the Microsoft's .NET development platform. C# is provided as a part of Microsoft .NET. In addition to C#, .NET supports Visual Basic, Visual C++, and the scripting languages VBScript and Jscript (infact 21 languages so far). A developer picks the .NET language that he/she likes most, writes components in it, and shares the compiled binary versions of his/her components with developers using other .NET languages. This makes the .NET platform **language-neutral** – i.e. modules written in C# would also be compatible with those written in VC++ and VB. When executed, the components use the .NET runtime component for security and memory management.

The basic premise is quite simple: all .NET programs are compiled to an intermediate language **Microsoft Intermediate Language (MSIL)** files, rather than to native code which can be understood by the computer's processor. This MSIL code is then compiled again using the **Just In Time (JIT)** compiler to native code either when the application is installed, or when the application is run, which is then executed by the machine's processor.

Microsoft has submitted a C# standard for ratification by ECMA (the European Computer Manufacturers' Association). Once this standard is in place, vendors worldwide will be able to use it to develop C# compilers that target their own platforms. **C# applications cannot run without the .NET runtime.** At present the .NET platform has been released for Win NT/2000/XP. Until the time a separate runtime environment is released for .NET, you will have to install the full .NET Software Development Kit (SDK) on every machine you can to run your programs.

MS plans to release the .NET runtime for other platforms soon. Now if a .NET runtime has been released for your platform then all the .NET programs will run on your platform. A .NET Platform for Linux is expected soon. As of today, Windows is the only platform for which an IL runtime has been developed so far, but this situation is expected to change. Even if Microsoft Corporation doesn't produce the Macintosh, UNIX, and IBM runtimes, someone else probably will in order to enjoy the reduced development costs associated with platform independence. A threat to Java?

2.2 C# and Java

There's no doubt that C# resembles Java. Both languages, for example, promote the grouping of classes, interfaces and implementation together in one file so that developers can edit the code more easily. Both handle objects in much the same way: via references. There are parallels between Java's JVM and C#'s CLR – both are in charge of interpreting bytecode. Both have garbage collectors. Both are in charge of authenticating code before it's executed. Additionally, some of the classes and namespaces inside the .NET class library are very similar to classes and namespaces in the Java class library.

Some differences though: C# uses operator overloading, type-safe enumeration. The C# compiler has an option to automatically produce XML-formatted code documentation using a special comment syntax.

The one edge that Java has over C# is platform independence. However, as mentioned earlier, it's speculated that Microsoft would release the CLR for platforms other than Windows.

2.3 Our first C# Program – Hello, world

Before you write your first C# application, you need to choose an editor. Notepad will also do. We'll now write the "Hello, world" example application to get to know the basic syntax and structure of writing C# applications.

Let's make a directory where we will save all our work. In order to do so, click on Start, Programs, then go to Accessories and select Command Prompt (Windows 2000). Once you are at

C# - CONSOLE APPLICATIONS

the command prompt create a directory called csharp (md csharp) and change to this directory (cd csharp). Load your favourite editor and type-in your first C# program.

Program `Hello.cs`

```
using System;
class Hello {
    public static void Main(string[] args) {
        Console.WriteLine("Hello, world");
    }
}
```

The default file extension for C# programs is `.cs`, as in `Hello.cs`. The name of the program can be `hello.cs` or any name you want. In fact, you can name your program as `Hello.txt` too! (Java programmers should note this).

An important note by Tom Archer, Author Inside C#:

"Most people would recommend that you use the `.cs` extension for three reasons:

1. The extension makes it obvious to anyone browsing a particular folder that the file is C# source code.
2. The Visual Studio File Open filter for C# files is set to look for (and therefore, display) files with a `.cs` extension. Having source code files with any other extension would require you to always change that filter (or update the Registry setting for Visual Studio).
3. When you install Visual Studio.NET, an automatic file association is created for the `.cs` files such that they appear in the Windows Explorer as "C# Source files" and when you open them, they are automatically opened with Visual Studio. Once again, using a different extension would require you to manually create the association and in the case of a `.txt` file, that might not be what you want.

With regards to the C# compiler allowing the use of files that don't have the `.cs` extension, this is simply the compiler team allowing you the freedom to use whatever extension you wish."

We would be using the C# command-line compiler (`csc.exe`) throughout these notes. This provides two benefits. First, it means that no matter what environment you're using, the steps for building the programs will always work. Second, learning the different compiler options will help you in the long run in situations where your editor doesn't provide you complete control over this step.

Such a program can be compiled with the command line directive

```
csc Hello.cs
```

which produces an executable program named `Hello.exe`.

If you haven't made any typos. Something like:

```
Microsoft (R) Visual C# Compiler Version 7.00.9254 [CLR version v1.0.2914]
```

```
Copyright (C) Microsoft Corp 2000-2001. All rights reserved.
```

will appear in your command prompt window. The C# compiler produces an executable program named `hello.exe`. **C# compiles straight from source code to executable (.exe), with no object files.** By simply typing **hello** you will see the output of the program as:

```
Hello, world
```

Close examination of this program is illuminating:

- C# **programs** (Note: program code only) are **case-sensitive and in free format.**

- Console (character only and graphics free) applications are normally used for creating driver programs for components that you are testing and a great way to start learning C#. It also means that we are not doing anything specific to Windows development.
- When you define a class in C#, you must define all methods inline—header files do not exist. Why is this a good thing? It enables the writers of classes to create highly mobile code, which is one of the key concepts of the .NET environment. This way when you write a C# class, you end up with a fully encapsulated bundle of functionality that you can easily drop into any other development environment without worrying how that language processes include files or if it has a mechanism for including files within files. Using this "one-stop programming" approach, you can, for instance, take an entire class and drop it into an Active Server Pages (ASP) page and it will function just as it would if it were being compiled into a desktop Windows application!
- The `using System;` directive references a namespace (similar to a package in Java) called `System` that is provided by the .NET runtime. `System` is the root of the .NET base class namespace. `using` is very similar in concept to Java's `import` keyword. All it does is to tell the compiler where to look if it comes across any types which are not in the current namespace. A "using" directive enables unqualified use of the members of a namespace. This namespace contains the `Console` class referred to in the `Main` method. Namespaces provide a hierarchical means of organizing the elements of a class library. Unlike Java, in C# you cannot import a single class, but the whole package. However, the components of a namespace name do not have to map onto directories (remember in Java, a package has to physically map to a directory). The "Hello, world" program uses `Console.WriteLine` as a shorthand for `System.Console.WriteLine`. What do these identifiers denote? `System` is a namespace, `Console` is a class defined in that namespace, and `WriteLine` is a static method (a static method can access any static member within the class, but it cannot access an instance member) defined in that class.
- In `Main()` the first character is a capital `M`.
- The `Main` function is a static member of the class `Hello`. Functions and variables are not supported at the global level; such elements are always contained within type declarations (e.g., class and struct declarations). The `Main` function can have any access modifier and can be written as `static void Main()` too. Every method (Main method here) must have a return type. In this case, it is "void", which means that "Main" does not return a value. Every method also has a parameter list following its name with zero or more parameters between parenthesis. The `Main` method is a static member of the class `Hello`. The static qualifier makes the `Main()` method a class method, so that it can be invoked on its own, without the creation of an instance of the class.
- Every C# application must have a method named `Main` defined in one of its classes. It doesn't matter which class contains the method—you can have as many classes as you want in a given application—as long as one class has a method named `Main`. It is the entry point of your program, where the program control starts and ends. Every C# executable (such as console applications, Windows applications and Windows services) must have an entry point. It is declared inside a class or struct. It must be static. It can either be `void` or return an `int`. The `Main` method is the place where you create objects and execute other methods. The `Main` method can be written without parameters or with parameters.
- There are three ways to declare the `Main` method: (a) It can return `void` as in `public static void Main() { ... }` (b) It can also return an `int` as in `public static int Main() { ...; return 0; }` (c) It can also take arguments as in `public static int Main(string[] args) { ...; return 0; }`

C# - CONSOLE APPLICATIONS

- The parameter of the Main method is a string array that represents the command-line arguments used to invoke the program. Notice that, unlike C, C++, this array does not include the name of the executable (exe) file.
- **If you have zero or more than one Main() in a program, you can expect compiler errors.** This is shown in the example **ManyMain.cs** below:

```
using System;
class GF {
    public GF() {
        Console.WriteLine("In GF class");
    }
    public static void Main(string[] args) {
    }
}
class F : GF {
    public F() {
        Console.WriteLine("In F class");
    }
    public static void Main(string[] args) {
    }
}
class S : F {
    public S() {
        Console.WriteLine("In S class");
    }
    public static void Main(string[] args) {
        S son = new S();
    }
}
```

This program when compiled gives the error:

Microsoft (R) Visual C# Compiler Version 7.00.9254 [CLR version v1.0.2914]

Copyright (C) Microsoft Corp 2000-2001. All rights reserved.

ManyMain.cs(13,22): warning CS0108: The keyword new is required on

'F.Main(string[])' because it hides inherited member 'GF.Main(string[])'

ManyMain.cs(6,22): (Location of symbol related to previous warning)

ManyMain.cs(6,22): error CS0017: Program 'ManyMain.exe' has more than one entry point defined: 'GF.Main(string[])'

ManyMain.cs(13,22): error CS0017: Program 'ManyMain.exe' has more than one entry point defined: 'F.Main(string[])'

ManyMain.cs(20,22): warning CS0108: The keyword new is required on

'S.Main(string[])' because it hides inherited member 'F.Main(string[])'

ManyMain.cs(13,22): (Location of symbol related to previous warning)

ManyMain.cs(20,22): error CS0017: Program 'ManyMain.exe' has more than one entry point defined: 'S.Main(string[])'

The designers of C# included a mechanism by which you can define more than one class with a **Main** method. Why would you want to do that? One reason is to place test code in your classes. You can then use the

/main: < className >

switch with the C# compiler to specify which class's *Main* method is to be used.

To compile this application such that the *S.Main* method is used as the application's entry point, you'd use this switch:

```
csc ManyMain.cs /main:S
```

Changing the switch to */main:F* would then use the *F.Main* method.

The **`/main`** compiler option specified a class in which to look for a *Main* method.

The error CS0108 indicates to us that a variable or method was declared with the same name as a variable or method in a base class. However, the `new` keyword was not used. This warning informs you that you should use **`new`**; the variable or method is declared as if **`new`** had been used in the declaration. The *Main()* methods in class *S* and *F* have to be declared as follows:

```
public static new void Main(string[] args) { }
```

- The "Hello, world" output is produced using a class library. C# does not itself provide a class library. Instead, C# uses a common class library that is also used by other languages such as Visual Basic and Visual C++.
- The program does not contain forward declarations. Forward declarations are never needed in C# programs, as declaration order is not significant.
- C# programs use "." as a separator in compound names such as *Console.WriteLine*.
- The program does not use `#include` to import program text. Dependencies between programs are handled symbolically rather than with program text. This system eliminates barriers between programs written in different languages. For example, the *Console* class could be written in C# or in some other language.

Note: Observe the following -

- Save the above Hello, world program as *Hello.cs* and compile as `csc Hello.cs` and run the program as *Hello*
- Compile the above program as `csc hello.cs` and run the program as *hello* or *Hello*
- Save the above file as *hello.cs* and compile as `csc Hello.cs` or `csc hello.cs` and run the program as *Hello* or *hello*
- Save the above file as *rubbish.cs* and compile as `csc rubbish.cs` and run the program as *rubbish*
- Make the class as `public` and try a, b and c as above

For a to e above we get the same output i.e. Hello, world

- We can have more than one public class in a source file.**

2.4 Compiler Options

You can compile your program as follows:

```
csc SourceFile.cs /out:TargetFile.exe
```

Some of the other options are:

```
/t:exe - produces a console application
```

```
/t:winexe - produces a Windows Form application
```

```
/t:library - produces a stand-alone assembly containing a manifest
```

```
/t:module - produces a stand-alone assembly without a manifest
```

C# - CONSOLE APPLICATIONS

2.5 Response files

To make automating builds easier, the C# compiler supports response files. A response file contains a listing of command line options and can be linked in by a reference to the file when the compiler is invoked.

```
csc SourceFile.cs /out:TargetFile.exe @<responsefilename>
```

The `/noconfig` option tells the compiler not to compile with the global or local versions of `csc.rsp`.

By default, the C# compiler looks in the `C:\WINDOWS\Microsoft.NET\Framework\v1.0.2914` directory and in the directory from which the compiler was invoked for files called `csc.rsp`.

The `csc.rsp` file that is supplied in `C:\WINDOWS\Microsoft.NET\Framework\v1.0.2914` references the .NET Framework assemblies that would be included in a C# project. You can modify this global `csc.rsp` file to contain any other compiler options that you want to include in a compilation from the command line with `csc.exe`.

The compiler will then look for a `csc.rsp` file in the directory from which the compiler was invoked. The commands in the local `csc.rsp` file will be combined with the global `csc.rsp` file for the compilation. Since the global `csc.rsp` is processed first, any command that is also in the local `csc.rsp` file will override the setting of the same command in the global `csc.rsp` file.

Finally, the compiler will read the options passed to the `csc` command. Since these are processed last, any option on the command line will override a setting of the same option in either of the `csc.rsp` files.

2.6 Compiler Errors

Here is what to expect when the compiler encounters syntax errors in your code. First, you'll see the name of the current file being compiled, followed by the **line number and column position** of the error. Next, you'll see the error code as defined by the compiler—for example, `CS0234`. Finally, after the error code, you'll see a short description of the error. Many times, this description will give you enough to make the error clear. You can also search for the error code in the .NET Framework SDK Documentation (which is installed with the .NET Framework SDK) for a more detailed description.

2.7 Managed Module

The C# compiler creates a Managed Module (MM). A MM is a standard Windows's portable executable (PE) file, that requires the CLR to execute and is therefore being managed by the CLR.

A MM is composed of the following things:

- Windows PE file header
- .NET Framework file header - some of the many information it carries is: version of the CLR required, the MM entry point method (Main), location/size of the MM meta data, resources etc.
- Metadata - simply it's a set of data tables that describe what is defined in the module, such as types and members. The Metadata is always embedded in the same EXE/DLL as the code.
- Microsoft Intermediate Language (MSIL) also known as Managed Code - MSIL is a complete language (it's a CPU-independent machine language) that you can write applications in. The MSIL is further compiled into native CPU instructions when the application is executed for the first time by the CLR.

End-users must have the CLR installed on their machine in order to execute any MMs. The CLR does not actually work with MMs; it works with assemblies. An assembly is a logical grouping of zero or more MMs and resource or data files. By default, compilers actually do the work of turning

the emitted MM into an assembly. Deployment can be as simple as copying the necessary assemblies to a target location. There is no need to register components in the Windows registry.

The System.Reflection namespace contains types that allow the inspection of metadata. Hence all components in the .NET are self-describing. This enables any application - not just the CLR - to query another application's metadata. Tools such as Visual Studio.NET use these reflection methods to implement features such as IntelliSense. With IntelliSense, as you type in a method name, that method's arguments pop up in a list box on the screen. The .NET tool called Microsoft .NET Framework IL Disassembler (ILDASM) also makes use of reflection. This tool parses the target application's metadata and then displays information about the application in a tree-like hierarchy.

2.8 ILDASM

Type the following program - **Hello.cs**

```
using System;
class Hello {
    static void Main() {
        Console.WriteLine("Hello");
    }
}
```

Compiling it gives us a file Hello.exe

In the Start menu's Run dialog box, type ildasm and click Ok. You will see an application with a few menu options. At this point, from the File menu, click Open. When the File Open dialog box appears, browse to the folder containing the Hello.exe application and select it. The ILDASM gives us a tree view of the contents of a managed binary. The Hello.exe consists of a manifest, one class (Hello), two methods (a class constructor and a static method Main), and a bit of class information.

Double-click the Main method in the tree view, and ILDASM will present a window displaying the MSIL for the Main method, as shown below.

```
.method private hidebysig static void Main() cil managed
{
    .entrypoint
    // Code size          11 (0xb)
    .maxstack 8
    IL_0000: ldstr          "Hello"
    IL_0005: call          void [mscorlib]System.Console::WriteLine(class
System.String)
    IL_000a: ret
} // end of method Hello::Main
```

The first line defines the Main method by using the .method MSIL keyword. Note that the method is defined as being public and static, which are the default modifiers for the Main method. Also note that this method is defined as managed.

The next line of code uses the MSIL .entrypoint keyword to designate this particular method as the entry point to the application. When the .NET runtime executes this application, this is where control will be passed to the program.

Next, look at the MSIL opcodes on lines IL_0000 and IL_0005. The first uses the ldstr (Load String) opcode to load a hard-coded literal ("Hello") onto the stack. The next line of code calls the System.Console.WriteLine method. Notice that the MSIL prefixes the method name with the name of the assembly that defines the method. This line also tells us the number of arguments (and

C# - CONSOLE APPLICATIONS

their types) that are expected by the method. Here, the method will expect a System.String object to be on the stack when it's called. Finally, line IL_000a is a simple ret MSIL opcode to return from the method.

2.9 Naming Guidelines

Choosing a stable and easily understood naming convention will enable you to write code that's easier to read and, therefore, to maintain. A standard is still evolving. It might end up slightly different from what is presented here, but this will at least give you a place to start.

For all i.e. 2.6.1 to 2.6.6 below, the start of the second word is always a capital letter.

2.9.1 Namespaces

Use your company or product name, and employ **mixed casing with an initial capital letter** - for example, *JavaTech*. If your company is called Javatech, and you have two products - training and software development - name your namespaces *JavaTech.Training* and *JavaTech.SoftwareDevelopment*.

2.9.2 Classes

Name your classes by using nouns that describe the class's problem domain. Employ **mixed casing with an initial capital letter** - for example, *MyButtonClass*

2.9.3 Methods

Employ **mixed casing with an initial capital letter** - on all methods. Methods are meant to act—they carry out work. Therefore, let the names of your methods depict *what* they do. Examples of this are *PrintBill* and *OpenFile*.

2.9.4 Method Arguments

Employ **mixed casing with an initial capital letter** on all arguments. Give meaningful names to arguments.

2.9.5 Interfaces

Employ **mixed casing with an initial capital letter** on all interfaces. It's common to prefix interface names with a capital "I"—for example, *IMyInterface*. A common technique is naming interfaces with adjectives.

2.9.6 Class members

Use camel casing, **in which the first letter is not capitalized**. That way if you have a method that takes as an argument something called *Foo*, you can differentiate it from the internal representation of that variable by creating the internal member named *foo*.

2.10 Automatic memory management

Manual memory management requires developers to manage the allocation and de-allocation of blocks of memory. Manual memory management is both time consuming and difficult. **C# provides automatic memory management** so that developers are freed from this burdensome task. In the vast majority of cases, this automatic memory management increases code quality and enhances developer productivity without negatively impacting either expressiveness or performance.

Once a variable is assigned null, it become eligible for garbage collection. The .NET Garbage Collector (GC) is permitted to clean up immediately, but is not required to do so.

Hence, once you finish with an object, that object no longer has any live references to it (i.e. it won't be assigned to any variables or stored in any arrays). C# has a garbage collector that looks for unused objects and reclaims the memory that those objects are using. You don't have to do any explicit freeing of memory; you just have to make sure that you are not holding onto an object you want to get rid of.

Note:

The **Finalize** (inherited from Object) method allows an Object to attempt to free resources and perform other cleanup operations before the **Object** is reclaimed by the Garbage Collector (GC). This method may be ignored by the Common Language Runtime; therefore, necessary cleanup operations should be done elsewhere.

2.11 Comments

The first line contains a comment:

```
// A "Hello World!" program in C#
```

Text following a comment // up to the end of the line is ignored by the compiler.

```
// Comments can appear on an independent line or as part of a statement too.
```

You can also comment a block of text by placing it between the characters /* and */, for example:

```
/* A "Hello World!" program in C#.
```

```
This program displays the string "Hello World!" on the screen. */
```

The C-style comment can occur within a line and can span more than one line.

```
// This line is commented out // is extra.
```

The extra // above, have no effect.

Block comments can't be nested.

Comments are not considered when your program is compiled. They are there to document what your program does in plain English.

In C# you can document the code you write using XML. C# is the only programming language in .NET framework with this feature. In source code files, lines that begin with **///** and that precede a user-defined type such as a class, delegate, or interface; member such as a field, event, property, or method; or a namespace declaration can be processed as comments and placed in a file. **These will be treated as normal comments by the compiler, unless you use the /doc: filename compiler option to tell it to generate the XML.** The compiler also supports a set of documentation tags that you can use within XML comments. The source code file that contains Main is output first into the XML.

The following sample XMLsample.cs program provides a basic overview of a type that has been documented.

```
// XMLsample.cs
// compile with: /doc:XMLsample.xml
using System;
/// <summary>
/// Class level summary documentation goes here.</summary>
/// <remarks>
/// Longer comments can be associated with a type or member
/// through the remarks tag</remarks>
public class SomeClass
```

C# - CONSOLE APPLICATIONS

```
{
    /// <summary>
    /// Store for the name property</summary>
    private string myName = null;

    /// <summary>
    /// The class constructor. </summary>
    public SomeClass()
    {
        // TODO: Add Constructor Logic here
    }

    /// <summary>
    /// Name property </summary>
    /// <value>
    /// A value tag is used to describe the property value</value>
    public string Name
    {
        get
        {
            if ( myName == null )
            {
                throw new Exception("Name is null");
            }

            return myName;
        }
    }

    /// <summary>
    /// Description for SomeMethod.</summary>
    /// <param name="s"> Parameter description for s goes here</param>
    /// <seealso cref="String">
    /// You can use the cref attribute on any tag to reference a type or member
    /// and the compiler will check that the reference exists. </seealso>
    public void SomeMethod(string s)
    {
    }

    /// <summary>
    /// Some other method. </summary>
    /// <returns>
    /// Return results are described through the returns tag.</returns>
    /// <seealso cref="SomeMethod(string)">
    /// Notice the use of the cref attribute to reference a specific method
</seealso>
    public int SomeOtherMethod()
    {
        return 0;
    }

    /// <summary>
    /// The entry point for the application.
    /// </summary>
    /// <param name="args"> A list of command line arguments</param>
    public static int Main(String[] args)
    {

```

```

    // TODO: Add code to start application here

    return 0;
}
}

```

To compile the sample code, type the following command line:

```
csc XMLsample.cs /doc:XMLsample.xml
```

The /doc option allows you to place documentation comments in an XML file.

This will create the XML file XMLsample.xml. as shown below:

```

<?xml version="1.0"?>
<doc>
  <assembly>
    <name>xmlsample</name>
  </assembly>
  <members>
    <member name="T:SomeClass">
      <summary>
        Class level summary documentation goes here.</summary>
      <remarks>
        Longer comments can be associated with a type or member
        through the remarks tag</remarks>
      </member>
      <member name="F:SomeClass.myName">
        <summary>
          Store for the name property</summary>
        </member>
        <member name="M:SomeClass.#ctor">
          <summary>The class constructor.</summary>
        </member>
        <member name="M:SomeClass.SomeMethod(System.String)">
          <summary>
            Description for SomeMethod.</summary>
          <param name="s"> Parameter description for s goes here</param>
          <seealso cref="T:System.String">
            You can use the cref attribute on any tag to reference a type or
member
            and the compiler will check that the reference exists. </seealso>
          </member>
          <member name="M:SomeClass.SomeOtherMethod">
            <summary>
              Some other method. </summary>
            <returns>
              Return results are described through the returns tag.</returns>
            <seealso cref="M:SomeClass.SomeMethod(System.String)">
              Notice the use of the cref attribute to reference a specific method
</seealso>
          </member>
          <member name="M:SomeClass.Main(System.String[])">
            <summary>
              The entry point for the application.
            </summary>
            <param name="args"> A list of command line arguments</param>
          </member>

```

C# - CONSOLE APPLICATIONS

```
<member name="P:SomeClass.Name">
  <summary>
    Name property </summary>
  <value>
    A value tag is used to describe the property value</value>
  </member>
</members>
</doc>
```

All the members of the assembly are denoted by `<member>` tags, and you can see how the compiler has added the full name of the member as a name attribute. The T, F and M prefixes denote types, fields and members respectively.

2.12 Blocks

C# code is organised into blocks (or sections). You specify the beginning and end of a block using curly braces.

```
{ // C# block of code }
```

Every executable statement in C# will be within one or more blocks. It is a standard C# programming style to identify different blocks with indentation. Every time you enter a new block, you should indent your source code by preferably two spaces. When you leave a block, you should de-indent by two spaces. Blocks define scope (or lifetime and visibility) of program elements.

2.13 Separation

As in C, C# uses the **semicolon** to indicate the end of a statement.

2.14 Whitespace

C# is a freeform language. You don't have to indent anything to get it to work properly. Whitespace characters are **space, tab or newline**. Appropriate use of white space makes your programs easier to read and understand.

2.15 Keywords (76)

Because keywords have specific meaning in C#, you can't use them as identifiers for something else, such as variables, constants, class names, and so on. However, they can be used as part of a longer token, for example: `public int abstract_int;`

Also, because C# is case sensitive, if a programmer is bent on using one of these words as an identifier of some sort, you can use an initial uppercase letter. While this is possible, it is a very bad idea in terms of human readability.

There are numerous Classes defined in the standard packages. While their names are not keywords, the overuse of these names may make your meaning unclear to future people working on your programs.

The keywords are:

<i>abstract</i>	<i>base</i>	<i>bool</i>	<i>break</i>	<i>byte</i>
<i>case</i>	<i>catch</i>	<i>char</i>	<i>checked</i>	<i>class</i>
<i>const</i>	<i>continue</i>	<i>decimal</i>	<i>default</i>	<i>delegate</i>
<i>do</i>	<i>double</i>	<i>else</i>	<i>enum</i>	<i>event</i>
<i>explicit</i>	<i>extern</i>	<i>false</i>	<i>finally</i>	<i>fixed</i>
<i>float</i>	<i>for</i>	<i>foreach</i>	<i>goto</i>	<i>if</i>
<i>implicit</i>	<i>in</i>	<i>int</i>	<i>interface</i>	<i>internal</i>

<i>is</i>	<i>lock</i>	<i>long</i>	<i>namespace</i>	<i>new</i>
<i>null</i>	<i>object</i>	<i>operator</i>	<i>out</i>	<i>override</i>
<i>params</i>	<i>private</i>	<i>protected</i>	<i>public</i>	<i>readonly</i>
<i>ref</i>	<i>return</i>	<i>sbyte</i>	<i>sealed</i>	<i>short</i>
<i>sizeof</i>	<i>static</i>	<i>string</i>	<i>struct</i>	<i>switch</i>
<i>this</i>	<i>throw</i>	<i>true</i>	<i>try</i>	<i>typeof</i>
<i>uint</i>	<i>ulong</i>	<i>unchecked</i>	<i>unsafe</i>	<i>ushort</i>
<i>using</i>	<i>virtual</i>	<i>void</i>	<i>while</i>	<i>as</i>

stackalloc

The break and continue keywords:

These can be used to control iteration. The break statement will exit from the immediately enclosing for, do, while, foreach or switch statement. The continue statement will terminate the current iteration, causing a jump to the end of the block forming the body of the loop. C# does not support labeled break as in Java.

2.16 Constants – const / readonly

A constant is nothing more than a value, in a program, that stays the same throughout the program's execution. Such values as the numeral 2 and the string constant "C#" are sometimes called hard-coded values or literals. Symbolic constants are simply words that represent values in a program, for example:

```
const float SALESTAX = 0.06;
```

const tells C# that this data object is going to be a constant.

```
const int x = 100;
```

```
const int y = x*5; // OK – compiler knows value of x
```

By default, *const* members are static. A *const* variable cannot take as its value a variable that is not *const*. Therefore, this is not allowed:

```
int x = 100;
const int y = x*5; // Error, x is not const
```

One problem you may encounter is that values of *const* members are calculated at compile-time, so you can't use const to define a member whose value can't be set in this way. What does a programmer do when the need arises for a field with a value that won't be known until run time and should not be changed once it's been initialized? To get around this, C# has provided a *readonly* modifier, which specifies that the member can have its value set once only, and afterwards is read-only. The readonly fields that we define are instance fields, meaning that the user would have to instantiate the class to use the fields. Hence, when you define a field with the *readonly* keyword, you have the ability to set that field's value in one place: the constructor. After that point, the field cannot be changed by either the class itself or the class's clients.

In the example below, we are setting the sortcode to the string value passed into the constructor.

```
public class Account {
    public readonly string sortcode;
    public Account(string code) {
        sortcode = code;
    }
}
```

2.17 Variables

Variables are values that can change as much as needed during the execution of a program. One reason you need variables in a program is to hold the results of a calculation. Hence, variables

C# - CONSOLE APPLICATIONS

are locations in memory in which values can be stored. They have a name, a type, and a value. C# allows simple and compound variable declarations.

2.18 Naming constants and variables

The rules for choosing constant and variable names (identifiers) are that every C# identifier must begin with one of the characters: A-Z, a-z. Following the first character, the rest of the identifier can use any of these characters: A-Z, a-z, 0-9. An identifier must not clash with a keyword. As a special case, the @ prefix can be used to avoid such a conflict, but the character is not considered part of the identifier that it precedes. For instance, the following two identifiers are equivalent:

```
int
@int
```

The example [SI.cs](#) below clarifies this point:

```
using System;
class SI {
    static void Main(){
        int @int = 20;
        Console.WriteLine("Value is: {0} ", @int);
    }
}
```

A class name or other identifier can be no longer than 512 characters.

C# language uses the **Unicode** character set. Unicode is a character set definition that not only offers characters in the standard ASCII character set, but also a wide range of other characters for representing most international characters.

Variable definitions can go anywhere in a method definition, although typically variable declarations for a given block are placed immediately after the opening curly brace ({}). C# actually has three kinds of variables: instance, class and local variables. C# does not have global variables, as in 'C'.

Instance variables are defined outside the confines of any method declaration. In general, instance variables are available to all methods within the class and are automatically initialised when an object is created. Their initial value depends on the type of variable: null for objects of classes, 0 for numeric variables, '\0' for characters, and false for bool.

Local variables are local to some method, are not automatically initialised and are lost once a method terminates. Your C# program will not compile if you try to use an unassigned local variable. The scope extends to the end of the current block. You can't declare another variable with the same name in the current or any nested blocks.

A static variable belongs to the class itself (not any individual object). No object really owns this variable but any can read or write it. This is useful to provide a means of communication between objects or for storing data that all objects need to reference. No matter how many times a class gets instantiated, only one copy of this variable will exist. In C#, static members must be accessed through a class name. You can't access them via an object, as you can in Java. Also, static variables cannot be declared inside a method.

2.19 Escape sequences

The \" in a string literal is an example of an escape sequence. The \ character indicates the beginning of an escape sequence and the character or characters that follow are interpreted in a special way. In this example, the escape sequence means that the " mark should be printed and it does not indicate the end of the string literal. Another example is \n indicating newline character.

2.20 Statements and Expressions

A C# program is structured into classes, which contain methods, and these in turn are made up of statements. Statements are free format; can run over more than one line without any need for continuation characters; and are terminated with a semicolon. A statement forms a single C# operation. Statements sometimes return values - for example, when you add two numbers together or test to see whether one value is equal to another. Expressions are built by combining variables and operators together into statements. C# statements end with a semicolon. A statement may have a label associated with it. Normally labeled statements are used in switch statements, but in C# they can also be used as the destination for a goto operation.

An **expression statement** evaluates a given expression. The value computed by the expression, if any, is discarded. Not all expressions are permitted as statements. In particular, expressions such as $x + y$ and $x == 1$ that have no side effects, but merely compute a value (which will be discarded), are not permitted as statements.

The example

```
using System;
class SMT {
    static int F() {
        Console.WriteLine("Test.F");
        return 0;
    }
    static void Main() {
        F();
    }
}
```

shows an expression statement. The call to the function F made from Main, constitutes an expression statement. The value that F returns is simply discarded.

2.20.1 Empty statement

An *empty-statement* does nothing.

empty-statement:

```
;
```

An empty statement is used when there are no operations to perform in a context where a statement is required. Execution of an empty statement simply transfers control to the end point of the statement. Thus, the end point of an empty statement is reachable if the empty statement is reachable. An empty statement can be used when writing a while statement with a null body:

```
bool ProcessMessage() {...}
void ProcessMessages() {
    while (ProcessMessage());
}
```

Also, an empty statement can be used to declare a label just before the closing "}" of a block:

```
void F() {
    ...
    if (done) goto exit;
    ...
    exit: ;
}
```

2.21 Types

A C# program is written by building new **types (typically classes)** and leveraging existing types, either those defined in the C# language itself or imported from other libraries. **Each type**

C# - CONSOLE APPLICATIONS

contains a set of data (typically fields) and function members (typically methods), which combine to form the modular units that are the key building blocks of a C# program.

Generally, you must create instances of a type to use that type. Those data members and function members that require a type to be instantiated are called instance members. Data members and function members that can be used on the type itself are called static members.

C# supports two major kinds of types (including both predefined types and user-defined types): **value types** and **reference types**. Value types include simple types such as `char`, `int`, `float` etc. **are structs** (simple type actually alias structs found in the `System` namespace). You can expand the set of simple types by defining your own structs and enums. Reference types include class types, interface types, delegate types, and array types.

Value types are allocated on the stack and Reference types are allocated on the heap.

Value types differ from reference types in that variables of the value types directly contain their data, whereas variables of the reference types store references to objects. With reference types, it is possible for two variables to reference the same object, and thus possible for operations on one variable to affect the object referenced by the other variable. With value types, the variables each have their own copy of the data, and it is not possible for operations on one to affect the other. An example `SRMEM.cs` clarifies this point:

```
// SRMEM.cs
// Reference-type declaration
using System;
class PointR {
    public int x, y;
}
// Value-type declaration
struct PointV {
    public int x, y;
}
class SMT {
    static void Main() {
        PointR a; // Local reference-type variable, uses 4 bytes of
                // memory on the stack to hold address
        PointV b; // Local value-type variable, uses 8 bytes of
                // memory on the stack for x and y
        a = new PointR(); // Assigns the reference to address of new
                        // instance of PointR allocated on the
                        // heap. The object on the heap uses 8
                        // bytes of memory for x and y, and an
                        // additional 8 bytes for core object
                        // requirements, such as storing the
                        // object's type & synchronization state
        b = new PointV(); // Calls the value-type's default
                        // constructor. The default constructor
                        // for both PointR and PointV will set
                        // each field to its default value, which
                        // will be 0 for both x and y.

        a.x = 7;
        b.x = 7;
    }
}
```

At the end of the method the local variables `a` and `b` go out of scope, but the new instance of a `PointR` remains in memory until the garbage collector determines it is no longer referenced

```

*/

// Assignment to a reference type copies an object reference;
// assignment to a value type copies an object value...
PointR c = a;
PointV d = b;
c.x = 9;
d.x = 9;
Console.WriteLine(a.x); // Prints 9
Console.WriteLine(b.x); // Prints 7
}
}

```

The process of turning a value type into a reference type is known as *boxing*. Each value type has a corresponding hidden reference type, which is automatically created when it's cast to a reference type.

The process of turning a reference type back into a value type is called *unboxing*.

C# provides a “unified type system”, whereby the **object** class is the ultimate base type for both reference and value types. All types – including value types – can be treated like objects. It is possible to call Object methods on any value, even values of “primitive” types such as `int`. The example

```

using System;
class SMT {
    static void Main() {
        Console.WriteLine(3.ToString());
    }
}

```

calls the Object-defined `ToString` method on a constant value of type `int`.

The example **BUB.cs**

```

class BUB {
    static void Main() {
        int i = 123;
        object o = i; // boxing
        int j = (int) o; // unboxing
    }
}

```

is more interesting. An `int` value can be converted to object and back again to `int`. This example shows both *boxing* and *unboxing*. When a variable of a value type needs to be converted to a reference type, an object *box* is allocated to hold the value, and the value is copied into the box. *Unboxing* is just the opposite. When an object box is cast back to its original value type, the value is copied out of the box and into the appropriate storage location. When unboxing—converting from a reference type to a value type—the cast is needed. This is because in the case of unboxing, an object could be cast to any type. Therefore, the cast is necessary so that the compiler can verify that the cast is valid per the specified variable type.

This type system unification provides value types with the benefits of object-ness, and does so without introducing unnecessary overhead. For programs that don't need `int` values to act like object, `int` values are simply 32 bit values. For programs that need `int`'s to behave like objects, this functionality is available on-demand. This ability to treat value types as objects bridges the gap between value types and reference types that exists in most languages.

All types in C# - value and reference – inherit from the Object superclass. The `object` type is based on **System.Object** in the .NET Framework. You can assign values of any type to variables

C# - CONSOLE APPLICATIONS

of type object. All data types, predefined and user-defined, inherit from the **System.Object** class. **The object data type is the type to and from which objects are boxed.**

Developers can define new value types through enum and struct declarations, and can define new reference types via class, interface, and delegate declarations.

2.22 Predefined types

C# provides a set of predefined types, most of which will be familiar to C and C++ developers.

The table below lists each of the predefined types, and provides examples of each.

Type	Description	Examples
Object	The ultimate base type of all other types	Object o = new Stack();
String	String type; a string is a sequence of Unicode characters	String s = "Hello";
Sbyte	8-bit signed integral type	Sbyte val = 12;
Short	16-bit signed integral type	Short val = 12;
Int	32-bit signed integral type	int val = 12;
Long	64-bit signed integral type	long val 1 = 12; long val 2 = 34L;
Byte	8-bit unsigned integral type	byte val 1 = 12; byte val 2 = 34U;
Ushort	16-bit unsigned integral type	ushort val 1 = 12; ushort val 2 = 34U;
UInt	32-bit unsigned integral type	uint val 1 = 12; uint val 2 = 34U;
ULong	64-bit unsigned integral type	ulong val 1 = 12; ulong val 2 = 34U; ulong val 3 = 56L; ulong val 4 = 78UL;
Float	Single-precision floating point type	float value = 1.23F;
Double	Double-precision floating point type	double val 1 = 1.23 double val 2 = 4.56D;
Bool	Boolean type; a bool value is either true or false	bool value = true;
Char	Character type; a char value is a Unicode character	char value = 'h';
Decimal	Precise decimal type with 28 significant digits	Decimal value = 1.23M;

C# is 'type-safe' - a reference (when not *null*) is always guaranteed to point to an object that is of the type specified and that has already been allocated on the heap. Also take note of the fact that a reference can be *null*.

C# is a **strongly "Typed" language**. Thus, all operations on variables are performed with consideration of what the variable's "Type" is. There are rules that define what operations are legal in order to maintain the integrity of the data you put in a variable. This is enforced at compile time. Therefore, you cannot initialize a variable of type int to a variable of type bool.

The conversions between types may be implicit or explicit. **Implicit numeric conversions** can be performed automatically and are guaranteed to succeed and not lose information. The implicit numeric conversions are:

- From sbyte to short, int, long, float, double, or decimal.
- From byte to short, ushort, int, uint, long, ulong, float, double, or decimal.
- From short to int, long, float, double, or decimal.
- From ushort to int, uint, long, ulong, float, double, or decimal.
- From int to long, float, double, or decimal.
- From uint to long, ulong, float, double, or decimal.
- From long to float, double, or decimal.
- From ulong to float, double, or decimal.
- From char to ushort, int, uint, long, ulong, float, double, or decimal.
- From float to double.

Conversions from int, uint, or long to float and from long to double may cause a loss of precision, but will never cause a loss of magnitude. The other implicit numeric conversions never lose any information.

There are no implicit conversions to the char type. This in particular means that values of the other integral types do not automatically convert to the char type.

Explicit numeric conversions require a cast and runtime circumstances determine whether the conversion succeeds or information is lost during the conversion. An example of this:

```
int x = 123456; // 4bytes
short s = (short)x; //convert to 2 bytes
```

All the types have fixed sizes, and will be the same size on any system. All data types, predefined and user-defined, inherit from the System.Object class.

While the CTS is responsible for defining the types that can be used across .NET languages, most languages choose to implement aliases to those types. There is no advantage to using one technique over the other.

In C#, each of the predefined types is a shorthand (alias) for a system-provided type. For example, the keyword `int` is shorthand for a struct named `System.Int32` by the CTS. The two names can be used interchangeably, though it is considered good style to use the keyword rather than the complete system type name.

The C# type keywords and their aliases are interchangeable. For example, you can declare an integer variable by using either of the following declarations:

```
int x = 123;
System.Int32 x = 123;
```

All the types in the table, except `object` and `string`, are referred to as simple types. The predefined value types include signed and unsigned integral types, floating point types, and the types `bool`, `char`, and `decimal`. The signed integral types are `sbyte`, `short`, `int`, and `long`; the unsigned integral types are `byte`, `ushort`, `uint`, and `ulong`; and the floating point types are `float` and `double`.

C# - CONSOLE APPLICATIONS

The predefined reference types are `object` and `string`. The `object` type is based on `System.Object` in the .NET Framework. You can assign values of any type to variables of type `object`. This is in contrast to Java, where the basic types have no object-like behaviour at all, and need to be explicitly converted to and from object wrapper types. In the .NET runtime, a reference-type instance has an eight-byte overhead, which stores the object's type and temporary information such as synchronisation lock state or whether it has been fixed from movement by the garbage collector. Each reference to a reference type instance uses four bytes of storage.

The following sample shows how variables of type `object` can accept values of any data type and how variables of type `object` can use methods on `System.Object` from the .NET Framework.

Example `ObjClass.cs`

```
using System;
public class MyClass1 {
    public int i = 10;
}
public class MyClass2 {
    public static void Main() {
        object a;
        a = 1; // an example of boxing
        Console.WriteLine(a);
        Console.WriteLine(a.GetType());
        Console.WriteLine(a.ToString());
        Console.WriteLine();
        a = new MyClass1 ();
        MyClass1 ref_MyClass1;
        ref_MyClass1 = (MyClass1)a;
        Console.WriteLine(ref_MyClass1.i);
    }
}
```

`Equals()` is a very important method in `Object` class. The default implementation of `Equals` supports reference equality only, but subclasses can override this method to support value equality instead. In the case of value types, this method returns true if the two types are identical and have the same value. The example `ObjEquals.cs` clarifies this point.

```
using System;
public class ObjEquals {
    static void Main() {
        Object o = new Object();
        Object o1 = new Object();
        String s1 = "Hello";
        String s2 = "Hello";
        String s3 = "World";
        String s4 = s3;
        int i1 = 1;
        int i2 = 1;
        int i3 = 2;
        if (o == o1) // false
            Console.WriteLine("Same Object Reference (o and o1)");
        if (o.Equals(o1)) // false
            Console.WriteLine("Same Object Content (o and o1)");
        if (s1 == s2) // true
            Console.WriteLine("Same Object Reference (s1 and s2)");
        if (s1.Equals(s2)) // true
            Console.WriteLine("Same Object Content (s1 and s2)");
        if (s1 == s3) // false
```

```

    Console.WriteLine("Same Object Reference (s1 and s3)");
    if (s1.Equals(s3)) // false
        Console.WriteLine("Same Object Content (s1 and s3)");
    if (s3 == s4) // true
        Console.WriteLine("Same Object Reference (s3 and s4)");
    if (s3.Equals(s4)) // true
        Console.WriteLine("Same Object Content (s3 and s4)");
    if (i1.Equals(i2)) // true
        Console.WriteLine("Same Object Content (i1 and i2)");
    if (i1.Equals(i3)) // false
        Console.WriteLine("Same Object Content (i1 and i3)");
}
}

```

The **string** type represents a string of Unicode characters. `string` is an alias for **System.String** in the NGWS Framework. The string reference type requires a minimum of 20 bytes of memory. Although `string` is a reference type, the equality operators (`==` and `!=`) are overloaded to compare the values of string objects, not references. This makes testing for string equality more intuitive.

```

string a = "hello";
string b = "hello";
Console.WriteLine( a == b ); // output: True -- same value
Console.WriteLine( (object)a == b ); // False -- different objects

```

The **+** operator concatenates strings:

```
string a = "good " + "morn ing";
```

The **[]** operator accesses individual characters of a string:

```
char x = "test"[2]; // x = 's';
```

String literals are of type `string` and can be written in two forms, quoted and `@`-quoted. Quoted string literals are enclosed in double quotation marks ("):

```
"good morn ing" // a string literal
```

and can contain any character literal, including escape sequences:

```
string a = "\\u0066\n"; // backslash, letter f, new line
```

`@`-quoted string literals start with `@` and are enclosed in double quotation marks. For example:

```
@"good morn ing" // a string literal
```

The advantage of `@`-quoting is that escape sequences are not processed, which makes it easy to write, for example, a fully qualified file name:

```
@"c:\Docs\Source\a.txt" // rather than "c:\\Docs\\Source\\a.txt"
```

To include a double quotation mark in an `@`-quoted string, double it:

```
@""Ahoy!" cried the captain." // "Ahoy!" cried the captain.
```

The C# object class is very similar to Java's `Object`.

```
int n = 5;
string s = n.ToString(); // call object.ToString()
```

One can declare a string as follows:

```
string str = "Hello";
```

If you declare as follows:

C# - CONSOLE APPLICATIONS

```
string str = new string("Hello");
```

you will get a compiler warning.

The **bool** type is used to represent boolean values: values that are either true or false. The **bool** keyword is an alias of **System.Boolean**. Although Boolean values require only 1 bit (0 or 1), they occupy **1 byte of storage** since this is the minimum chunk addressing on most processor architectures can work with. The inclusion of **bool** makes it easier for developers to write self-documenting code, and helps eliminate the all-too-common C++ coding error in which a developer mistakenly uses "=" when "==" should have been used. In C#, the example

```
int i = ...;
F(i);
if (i = 0) // Bug: the test should be (i == 0)
    G();
```

is invalid because the expression `i = 0` is of type `int`, and `if` statements require an expression of type `bool`. **No standard conversions exist between bool and other types.** In particular, the `bool` type is distinct and separate from the integral types, and a `bool` value cannot be used in place of an integral value, or vice versa.

The **byte** type is an Unsigned 8-bit integer. The **byte** keyword is an alias of **System.Byte**.

The **sbyte** type is a Signed 8-bit integer. The **sbyte** keyword is an alias of **System.SByte**.

The **char** type is used to represent **Unicode characters**. A variable of type `char` represents a single 16-bit Unicode character. The **char** keyword is an alias of **System.Char**. Constants of the `char` type can be written as character literals, hexadecimal escape sequence, or Unicode representation. You can also cast the integral character codes. All of the following statements declare a `char` variable and initialize it with the character X:

```
char MyChar = 'X'; // Character literal
char MyChar = '\x0058'; // Hexadecimal
char MyChar = (char)88; // Cast from integral type
char MyChar = '\u0058'; // Unicode
```

The **decimal** type is appropriate for calculations in which rounding errors are unacceptable. Common examples include financial calculations such as tax computations and currency conversions. The `decimal` type provides **28 significant digits**. The `decimal` keyword is an alias of **System.Decimal**. It occupies 16 bytes of memory. **If you want a numeric real literal to be treated as decimal, use the suffix m or M**, for example:

```
decimal myMoney = 300.5m;
```

Without the suffix `m`, the number is treated as a `double`, thus generating a compiler error.

The **double** keyword denotes a simple type that stores 64-bit floating-point values. **Precision is 15-16 digits**. The `double` keyword is an alias of **System.Double**. By default, a real numeric literal on the right-hand side of the assignment operator is treated as `double`. However, **if you want an integer number to be treated as double, use the suffix d or D**, for example:

```
double x = 3D;
```

You can use `F` to denote single precision (i.e. 12.7F). `U` can be used to denote unsigned literals, and `L` longs. The precise decimal type is denoted by an `M` suffix, as in 12.77M.

The **float** keyword denotes a simple type that stores 32-bit floating-point values. **Precision is 7 digits**. The `float` keyword is an alias of **System.Single**. By default, a real numeric literal on the right-hand side of the assignment operator is treated as `double`. Therefore, to initialize a `float` variable use the suffix `f` or `F`, for example:

```
float x = 3.5F;
```


If you don't use the suffix in the previous declaration, you will get a compilation error because you are attempting to store a double value into a float variable.

The **int** keyword denotes an integral type. It's a Signed 32-bit integer. The int keyword is an alias of **System.Int32**.

The **uint** keyword denotes an integral type. It's an unsigned 32-bit integer. The int keyword is an alias of **System.UInt32**. You can declare and initialize a variable of the type uint like this example:

```
uint myUint = 4294967290;
```

When an integer literal has no suffix, its type is the first of these types in which its value can be represented: int, uint, long, ulong. In this example, it is uint. You can also use the suffix u or U, like this:

```
uint myUint = 123U;
```

When you use the suffix U or u, the literal type is determined to be either uint or ulong according to its size. In this example, it is uint.

The **long** keyword denotes an integral type. It's a signed 64-bit integer. The long keyword is an alias of **System.Int64**. You can declare and initialize a long variable like this example:

```
long myLong = 4294967296;
```

When an integer literal has no suffix, its type is the first of these types in which its value can be represented: int, uint, long, ulong. In the preceding example, it is of the type long because it exceeds the range of uint (see Integral Types Table for the storage sizes of integral types). You can also use the suffix L or l with the long type like this:

```
long myLong = 4294967296L;
```

When you use the suffix L or l, the type of the literal integer is determined to be either long or ulong according to its size. In the case it is long because it less than the range of ulong.

A common use of the suffix is with calling overloaded methods. Consider, for example, the following overloaded methods that use long and int parameters:

```
public static void MyMethod(int i) {}
public static void MyMethod(long l) {}
```

Using the suffix L or l guarantees that the correct type is called, for example:

```
MyMethod(5); // Calling the method with the int parameter
MyMethod(5L); // Calling the method with the long parameter
```

You can use the long type with other numeric integral types in the same expression, in which case the expression is evaluated as long (or bool in the case of relational or Boolean expressions). For example, the following expression evaluates as long:

```
898L + 88
```

The **ulong** keyword denotes an integral type. It's an unsigned 64-bit integer. The ulong keyword is an alias of **System.UInt64**.

The **short** keyword denotes an integral type. It's a signed 16-bit integer. The short keyword is an alias of **System.Int16**.

The **ushort** keyword denotes an integral type. It's an unsigned 16-bit integer. The ushort keyword is an alias of **System.UInt16**.

C# - CONSOLE APPLICATIONS

2.23 Operators

Operators are special symbols that are commonly used in expressions. C# has 50 built-in operators. There are four basic kinds of operators: arithmetic, bitwise, relational and logical. In addition, many operators can be overloaded by the user, thus changing their meaning when applied to a user-defined type.

Anyone familiar with the operators of C will have no problem using C#'s. C# does add a few operators of its own. The order of evaluation of operators in an expression is determined by the *precedence* and *associativity* of the operators. In general, operators with the same precedence level will be evaluated from left to right in the given expression. A student has suggested a mnemonic: "Ulcer Addicts Really Like C A lot" where U is Unary, A is Arithmetic, R is Relational, L is logical, C is Conditional, A lot is Assignment. The Associativity for Assignment, ==, != and ?: is from Right to Left, for all others it's Left to Right.

Expressions are constructed from *operands* and *operators*. The operators of an expression indicate which operations to apply to the operands. Examples of operators include +, -, *, /, and new. Examples of operands include literals, fields, local variables, and expressions.

These can be categorised into three types:

- Unary operators. The unary operators take one operand and use either prefix notation (such as -x) or postfix notation (such as x++).
- Binary operators. The binary operators take two operands and all use infix notation (such as x + y).
- Ternary operator. Only one ternary operator, ?:, exists. The ternary operator takes three operands and uses infix notation (c? x: y).

The following table summarizes all operators in order of precedence from highest to lowest:

Category	Operators
Primary	(x) x.y f(x) a[x] x++ x-- new typeof sizeof checked unchecked
Unary	+ - ! ~ ++x --x (T)x
Multiplicative	* / %
Additive	+ -
Shift	<< >>
Relational	< > <= >= is
Equality	== !=
Logical AND	&
Logical XOR	^
Logical OR	
Conditional AND	&&
Conditional OR	
Conditional	?:
Assignment	= *= /= %= += -= <<= >>= &= ^= =

When an operand occurs between two operators with the same precedence, the *associativity* of the operators controls the order in which the operations are performed:

- Except for the assignment operators, all binary operators are *left associative*, meaning that operations are performed from left to right. For example, $x + y + z$ is evaluated as $(x + y) + z$.
- The assignment operators and the conditional operator (`?:`) are *right associative*, meaning that operations are performed from right to left. For example, $x = y = z$ is evaluated as $x = (y = z)$.

Precedence and associativity can be controlled using parentheses. For example, $x + y * z$ first multiplies y by z and then adds the result to x , but $(x + y) * z$ first adds x and y and then multiplies the result by z .

An example using `%` operator – **P3.cs**

```
// P3.cs
using System;
class P3 {
    public static void Main(String[] args) {
        int number = 548;
        int sum = 0;
        while (true) {
            sum = sum + number % 10;
            number = number / 10;
            if (number == 0) break;
        }
        Console.WriteLine("Sum = " + sum);
    }
}
```

2.23.1 checked and unchecked operators

The arithmetic operators (`+`, `-`, `*`, `/`) can produce results that are outside the range of possible values for the numeric type involved. In general:

Integer arithmetic overflow either throws an `OverflowException` or discards the most significant bits of the result (see below). Integer division by zero always throws a `DivideByZeroException`.

Floating-point arithmetic overflow or division by zero never throws an exception, because floating-point types are based on IEEE 754 and so have provisions for representing infinity and NaN (Not a Number).

Decimal arithmetic overflow always throws an `OverflowException`. Decimal division by zero always throws a `DivideByZeroException`.

When integer overflow occurs, what happens depends on the execution context, which can be checked or unchecked. The checked operator tells the runtime to generate an `OverflowException` if an integral expression exceeds the arithmetic limits of that type. The unchecked operator disables arithmetic checking at compile time, the most significant bits of the result are discarded and execution continues. It is seldom useful. Thus, C# gives you the choice of handling or ignoring overflow.

```
// OverflowTest.cs - Using checked expressions
// The overflow of non-constant expressions is checked at run time
using System;
class OverflowTest {
    static short x = 32767; // Max short value
    static short y = 32767;
    // Using a checked expression
```

C# - CONSOLE APPLICATIONS

```
public static int MyMethodCh() {
    int z = checked((short)(x + y));
    return z; // Throws the exception OverflowException
}
public static void Main() {
    Console.WriteLine("Checked output value is: {0}", MyMethodCh());
}
}
```

Output:

When you run the program, it throws the exception `OverflowException`. You can debug the program or abort execution.

```
// UCS.cs - Using the unchecked statement with constant expressions
// Overflow is checked at compile time
using System;
class UCS {
    const int x = 2147483647; // Max int
    const int y = 2;
    public int MethodUnCh() {
        // Unchecked statement:
        unchecked {
            int z = x * y;
            return z;
        } // Returns -2
    }
    public static void Main() {
        UCS myObject = new UCS();
        Console.WriteLine("Unchecked output value: {0}",
            myObject.MethodUnCh());
    }
}
```

Output:

Unchecked output value: -2

In addition to the arithmetic operators, integral-type to integral-type casts can cause overflow (for example, casting a long to an int) and are subject to checked or unchecked execution.

2.24 Operator overloading

All unary and binary operators have predefined implementations that are automatically available in any expression. In addition to the predefined implementations, user-defined implementations can be introduced by including operator declarations in classes and structs. User-defined operator implementations always take precedence over predefined operator implementations: Only when no applicable user-defined operator implementations exist will the predefined operator implementations be considered.

The *overloadable unary operators* are:

+ - ! ~ ++ -- true false

The *overloadable binary operators* are:

+ - * / % & | ^ << >> == != > < >= <=

Only the operators listed above can be overloaded. In particular, it is not possible to overload member access, method invocation, or the `=`, `&&`, `||`, `?:`, `new`, `typeof`, `sizeof`, and `is` operators.

When a binary operator is overloaded, the corresponding assignment operator is also implicitly overloaded. For example, an overload of operator `*` is also an overload of operator `*=`. Note that the assignment operator itself (`=`) cannot be overloaded. An assignment always performs a simple bit-wise copy of a value into a variable.

Cast operations, such as `(T)x`, are overloaded by providing user-defined conversions.

Element access, such as `a[x]`, is not considered an overloadable operator. Instead, user-defined indexing is supported through indexers.

User-defined operator declarations always require at least one of the parameters to be of the class or struct type that contains the operator declaration. Thus, it is not possible for a user-defined operator to have the same signature as a predefined operator.

User-defined operator declarations cannot modify the syntax, precedence, or associativity of an operator. For example, the `*` operator is always a binary operator, always has the predefined precedence level and is always left associative.

While it is possible for a user-defined operator to perform any computation it pleases, implementations that produce results other than those that are intuitively expected are strongly discouraged. For example, an implementation of operator `==` should compare the two operands for equality and return an appropriate result.

This example shows how you can use operator overloading to create a complex number class `Complex` that defines complex addition. The program displays the imaginary and the real parts of the addition result.

Example: `Complex.cs` – [Refer Anant's email here](#)

```
// Complex.cs
using System;
public class Complex {
    public int real = 0;
    public int imaginary = 0;
    public Complex(int real, int imaginary) {
        this.real = real;
        this.imaginary = imaginary;
    }
    public static Complex operator +(Complex c1, Complex c2) { //Line 10
        return new Complex(c1.real + c2.real, c1.imaginary + c2.imaginary);
    }
    public static void Main() {
        Complex num1 = new Complex(2,3);
        Complex num2 = new Complex(3,4);
        Complex sum = num1 + num2; // Line 16
        Console.WriteLine("Real: {0}", sum.real); // Line 17
        Console.WriteLine("Imaginary: {0}", sum.imaginary); // Line 18
    }
}
```

Code Discussion:

- Line 010 declares which operator to overload (`+`), the types that can be added (two `Complex` objects), and the return type (`Complex`).
- Line 016 adds two `Complex` objects (`num1` and `num2`) through the overloaded plus operator declared on line 010.
- Lines 017 and 018 show on execution that the real and imaginary parts of objects `num1` and `num2` have been added to produce the sum values.

C# - CONSOLE APPLICATIONS

2.25 Program Control

C# borrows most of its statements directly from C and C++, though there are some noteworthy additions and modifications.

2.25.1 The if statement

An `if` statement selects a statement for execution based on the value of a boolean expression. An `if` statement may optionally include an `else` clause that executes if the boolean expression is false.

The example

```
using System;
class SMT {
    static void Main(string[] args) {
        if (args.Length == 0)
            Console.WriteLine("No arguments were provided");
        else
            Console.WriteLine("Arguments were provided");
    }
}
```

shows a program that uses an `if` statement to write out two different messages depending on whether command-line arguments were provided or not.

2.25.2 The switch statement

A `switch` statement executes the statements that are associated with the value of a given expression, or default of statements if no match exists.

The example

```
using System;
class SMT {
    static void Main(string[] args) {
        switch (args.Length) {
            case 0:
                Console.WriteLine("No arguments were provided");
                break;
            case 1:
                Console.WriteLine("One arguments was provided");
                break;
            default:
                Console.WriteLine("{0} arguments were provided");
                break;
        }
    }
}
```

switches on the number of arguments provided.

The `switch` expression must be an integer type (including `char`) or a string. The case labels have to be constants. Unlike Java, you no longer fall through from case to case if you omit the `break` and there's code in the case. You will get a compiler error instead, and have to use a `goto` to jump to the next (or previous) case. The end of a case statement must explicitly state where to go next. If you have adjacent case labels, (i.e. No code in the case) then you can fall through.

Example: [SwitchSelection.cs](#)

```
using System;
class SwitchSelect {
```

```

public static void Main() {
    string myInput;
    int myInt;
    begin:
        Console.WriteLine("Please enter a number between 1 and 3: ");
        myInput = Console.ReadLine();
        myInt = Int32.Parse(myInput);
        // switch with integer type
        switch (myInt) {
            case 1:
                Console.WriteLine("Your number is {0}.", myInt);
                break;
            case 2:
                Console.WriteLine("Your number is {0}.", myInt);
                break;
            case 3:
                Console.WriteLine("Your number is {0}.", myInt);
                break;
            default:
                Console.WriteLine("Your number {0} is not between 1 and 3.", myInt);
        }
    decide:
        Console.WriteLine("Type \"continue\" to go on or \"quit\" to stop: ");
        myInput = Console.ReadLine();
        // switch with string type
        switch (myInput) {
            case "continue":
                goto begin;
            case "quit":
                Console.WriteLine("Bye.");
                break;
            default:
                Console.WriteLine("Your input {0} is incorrect.", myInput);
                goto decide;
        }
    }
}

```

2.25.3 The while statement

A `while` statement conditionally executes a statement zero or more times – as long as a boolean test is true.

```

using System;
class SMT {
    static int Find(int value, int[] arr) {
        int i = 0;
        while (arr[i] != value) {
            if (++i > arr.Length)
                throw new ArgumentException();
        }
        return i;
    }
    static void Main() {
        Console.WriteLine(Find(3, new int[] {5, 4, 3, 2, 1}));
    }
}

```

uses a `while` statement to find the first occurrence of a value in an array.

C# - CONSOLE APPLICATIONS

2.25.4 The do statement

A do statement conditionally executes a statement one or more times.

The example

```
using System;
class SMT {
    static void Main() {
        string s;
        do {
            s = Console.ReadLine();
        } while (s != "Exit");
    }
}
```

reads from the console until the user types "Exit" and presses the enter key.

2.25.5 The for statement

A for statement evaluates a sequence of initialization expressions and then, while a condition is true, repeatedly executes a statement and evaluates a sequence of iteration expressions.

The example

```
using System;
class SMT {
    static void Main() {
        for (int i = 0; i < 10; i++)
            Console.WriteLine(i);
    }
}
```

uses a for statement to write out the integer values 1 through 10.

2.25.6 The foreach statement

A foreach statement lets you iterate over the elements in arrays and collections.

The example **FE.cs**:

```
using System;
class FE {
    static void Main() {
        int[] arr1 = new int[] {1,2,3,4,5};
        foreach (int i in arr1)
            Console.WriteLine("Value is {0}", i);
    }
}
```

uses a foreach statement to iterate over the elements of an array.

2.26 Console I/O

Console I/O is provided by the `System.Console` class, which gives you access to the standard input (`Console.In`), standard output (`Console.Out`) and standard error (`Console.Error`) streams.

2.26.1 Console Input

`Console.In` has two methods for obtaining input. `Read()` returns a single character as an `int`, or `-1` if no more characters are available. `ReadLine()` returns a string containing the next line of input, or `null` if no more lines are available.

Note that `Console.In.ReadLine()` and `Console.ReadLine()` are equivalent.

2.26.2 Console Output

`Console.Out` has two methods for writing output. `Write()` outputs one or more values without a newline character. `WriteLine()` does the same but appends a newline.

`Write()` and `WriteLine()` have numerous overloads, so that you can easily output many different types of data.

If you want to produce **formatted output**, you use a version of `WriteLine()` which takes a string containing a format and a variable number of objects. Formats contain both static text, plus markers that show where items from the argument list are to be substituted, and how they are to be formatted. In its simplest form, a marker is a number in curly brackets, the number showing which argument is to be substituted:

```
"The value is {0}"           // use the first argument
"{0} plus {1} = {2}"       // use the first three arguments
```

Note that `Console.Out.WriteLine()` and `Console.WriteLine()` are equivalent.

2.27 Array types

Arrays in C# are objects, accessed through a reference variable. Arrays in C# may be single-dimensional or multi-dimensional.

Single-dimensional arrays are the most common type, so this is a good starting point. The example [MyArray.cs](#)

```
using System;
class MyArray {
    static void Main() {
        int[] arr = new int[5]; // size fixed to 5, can't be changed
        for (int i = 0; i < arr.Length; i++) // index 0 for arrays
            arr[i] = i * i;
        // we can also do something like this
        // int[] arr = new int[] {1,2,3,4,5};
        // or
        // int[] arr = {1,2,3,4,5};
        // any attempt to access an array outside the bounds
        // will result in a runtime error
        for (int i = 0; i < arr.Length; i++)
            Console.WriteLine("arr[{0}] = {1}", i, arr[i]);
    }
}
```

creates a single-dimensional array of `int` values, initializes the array elements, and then prints each of them out. The program output is:

```
arr[0] = 0
arr[1] = 1
arr[2] = 4
arr[3] = 9
arr[4] = 16
```

The type `int[]` used in the previous example is an array type. Array types are written using a non-array-type followed by one or more rank specifiers.

C# supports two types of multidimensional arrays – **rectangular** and **jagged**. In rectangular arrays, every row is the same length. A jagged array is simply an array of one-dimensional arrays, each of which can be of different length if desired.

C# - CONSOLE APPLICATIONS

The example:

```
class SMT {
    static void Main() {
        int[] a1; // single-dimensional array of int
        int[,] a2; // 2-dimensional array of int
        int[,,] a3; // 3-dimensional array of int
        int[][] j2; // "jagged" array: array of (array of int)
        int[][][] j3; // array of (array of (array of int))
    }
}
```

shows a variety of local variable declarations that use array types with `int` as the element type.

Arrays are reference types, and so the declaration of an array variable merely sets aside space for the reference to the array. Array instances are actually created via array initializers and array creation expressions. The example

```
class SMT {
    static void Main() {
        int[] a1 = new int[] {1, 2, 3};
        int[,] a2 = new int[,] {{1, 2, 3}, {4, 5, 6}};
        int[,,] a3 = new int[10, 20, 30];
        int[][] j2 = new int[3][];
        j2[0] = new int[] {1, 2, 3};
        j2[1] = new int[] {1, 2, 3, 4, 5, 6};
        j2[2] = new int[] {1, 2, 3, 4, 5, 6, 7, 8, 9};
    }
}
```

shows a variety of array creation expressions. The variables `a1`, `a2` and `a3` denote *rectangular arrays*, and the variable `j2` denotes a *jagged array*. It should be no surprise that these terms are based on the shapes of the arrays. Rectangular arrays always have a rectangular shape. Given the length of each dimension of the array, its rectangular shape is clear. For example, the length of `a3`'s three dimensions are 10, 20, and 30 respectively, and it is easy to see that this array contains $10 \times 20 \times 30$ elements.

In contrast, the variable `j2` denotes a "jagged" array, or an "array of arrays". Specifically, `j2` denotes an array of an array of `int`, or a single-dimensional array of type `int[]`. Each of these `int[]` variables can be initialized individually, and this allows the array to take on a jagged shape. The example gives each of the `int[]` arrays a different length. Specifically, the length of `j2[0]` is 3, the length of `j2[1]` is 6, and the length of `j2[2]` is 9.

It is important to note that the element type and number of dimensions are part of an array's type, but that the length of each dimension is not part of the array's type. This split is made clear in the language syntax, as the length of each dimension is specified in the array creation expression rather than in the array type. For instance the declaration

```
int[, ,] a3 = new int[10, 20, 30];
```

has an array type of `int[, ,]` and an array creation expression of `new int[10, 20, 30]`.

For local variable and field declarations, a shorthand form is permitted so that it is not necessary to re-state the array type. For instance, the example

```
int[] a1 = new int[] {1, 2, 3};
```

can be shortened to

```
int[] a1 = {1, 2, 3};
```

without any change in program semantics.

It is important to note that the context in which an array initializer such as {1, 2, 3} is used determines the type of the array being initialized. The example

```
class SMT {
    static void Main() {
        short[] a = {1, 2, 3};
        int[] b = {1, 2, 3};
        long[] c = {1, 2, 3};
    }
}
```

shows that the same array initializer can be used for several different array types. Because context is required to determine the type of an array initializer, it is not possible to use an array initializer in an expression context. The example

```
class SMT {
    static void F(int[] arr) {}
    static void Main() {
        F({1, 2, 3});
    }
}
```

is not valid because the array initializer {1, 2, 3} is not a valid expression. The example can be rewritten to explicitly specify the type of array being created, as in

```
class SMT {
    static void F(int[] arr) {}
    static void Main() {
        F(new int[] {1, 2, 3});
    }
}
```

Example RA.cs

```
// RA.cs
using System;
class RA {
    public static int Main() {
        int[,] arr2; // 2D rectangular array of ints
        arr2 = new int[5,5]; // create 5 by 5 array
        for (int i=0; i<5; i++)
            for (int j=0; j<5; j++)
                arr2[i,j] = i*j;
        // create a 2D array with implied size of 3 by 2
        int[,] arr3 = new int[,] {
            {1,2}, // first row
            {4,5}, // second row
            {7,8} // third row
        };
        // write out some elements
        Console.WriteLine("{0}", arr2[2,2]);
        Console.WriteLine("{0}", arr3[1,1]);
        return 0;
    }
}
```

Example JA.cs

```
//JA.cs
using System;
class JA {
```

C# - CONSOLE APPLICATIONS

```
public static void Main() {
    int[][] arr4;           // 2D jagged array of ints
    arr4 = new int[4][];   // four rows in this array
    arr4[0] = new int[5];  // first row has 5 elements
    arr4[1] = new int[3];  // second row has 3 elements
    arr4[2] = new int[4];  // third row has 4 elements
    arr4[3] = new int[10]; // last row has 10 elements
    arr4[1][1] = 3;       // assign an element
}
}
```

In C#, arrays are actually objects. **System.Array** is the base type of all array types. You can use the properties, and other class members that **System.Array** has. An example of this would be using **the Length property to get the length of an array**. The following code assigns the length of the numbers array, which is 5, to a variable called LengthOfNumbers:

```
int[] numbers = {1, 2, 3, 4, 5};
int LengthOfNumbers = numbers.Length;
```

The **System.Array** class provides many other useful methods/properties, such as methods for sorting, searching, and copying arrays.

Getting Command-Line Input:

Example: **NamedWelcome.cs**

```
// Namespace Declaration
using System;
// Program start class
class NamedWelcome {
    // Main begins program execution.
    public static void Main(string[] args) {
        // Write to console
        Console.WriteLine("Hello, {0}!", args[0]);
        Console.WriteLine("Welcome to the CSharp Seminar!");
    }
}
```

Remember to add your name to the command-line, i.e. "NamedWelcome Satish". If you don't, your program will crash. You'll notice an entry in the "Main" method's parameter list. The parameter name is "args". It's what you use to refer to the parameter later in your program. The "string[]" expression defines the Type of parameter that "args" is. The "string" Type holds characters. These characters could form a single word, or multiple words. The "[]", square brackets denote an Array, which is like a list. Therefore, the Type of the "args" parameter, is a list of words from the command-line.

You'll also notice an additional "Console.WriteLine(...)" statement within the "Main" method. The argument list within this statement is different from before. It has a formatted string with a "{0}" parameter embedded in it. The first parameter in a formatted string begins at number 0, the second is 1, and so on. The "{0}" parameter means that the next argument following the end quote will determine what goes in that position.

The next argument following the end quote is the "args[0]" argument, which refers to the first string in the "args" array. The first element of an Array is number 0, the second is number 1, and so on. For example, if we write "NamedWelcome Satish" on the command-line, the value of "args[0]" would be "Satish".

Now we'll get back to the embedded "{0}" parameter in the formatted string. Since "args[0]" is the first argument, after the formatted string, of the "Console.WriteLine()" statement, its value will be placed into the first embedded parameter of the formatted string. When this command is

executed, the value of "args[0]", which is "Satish" will replace "{0}" in the formatted string. Upon execution of the command-line with "NamedWelcome Satish", the output will be as follows:

Hello, Satish!

Welcome to the CSharp Seminar!

Another way to provide input to a program (`InteractiveWelcome.cs`) is via the console. The next program shows how to obtain interactive input from the user.

```
// InteractiveWelcome.cs
// Namespace Declaration
using System;
// Program start class
class InteractiveWelcome {
    // Main begins program execution.
    public static void Main() {
        // Write to console/get input
        Console.Write("What is your name?: ");
        Console.Write("Hello, {0}! ", Console.ReadLine());
        Console.WriteLine("Welcome to the CSharp Seminar!");
    }
}
```

This time, the "Main" method doesn't have any parameters. However, there are now three statements and the first two are different from the third. They are "Console.Write(...)" instead of "Console.WriteLine(...)". The difference is that the "Console.Write(...)" statement writes to the console and stops on the same line, but the "Console.WriteLine(...)" goes to the next line after writing to the console.

The first statement simply writes "What is your name?: " to the console.

The second statement doesn't write anything until its arguments are properly evaluated. The first argument after the formatted string is "Console.ReadLine()". This causes the program to wait for user input at the console, followed by a Return or Enter. The return value from this method replaces the "{0}" parameter of the formatted string and is written to the console.

The last statement writes to the console as described earlier. Upon execution of the command-line with "InteractiveWelcome", the output will be as follows:

What is your Name? <type your name here>

Hello, <your name here>! Welcome to the CSharp Seminar!

2.28 Calling methods – ref / out

Methods are extremely useful because they allow you to separate your logic into different units. Defining and calling methods in C# closely follows the Java model.

The structure of a method is as follows:

```
attributes modifiers return-type method-name ( parameters ) { statements }
```

We defer discussion of attributes and modifiers. The return-type can be any C# type, if the method does not return a value, its return type is void. It can be assigned to a variable for use later in the program or the return value can be ignored. The method name is a unique identifier for what you wish to call a method. To promote understanding of your code, a method name should be meaningful and associated with the task the method performs. Parameters allow you to pass information to and from a method. If there are no parameters, the method name is followed by empty parentheses. They are surrounded by parenthesis. Statements within the curly braces carry out the functionality of the method. **As in Java, you are free to ignore the return value of a method call.**

C# - CONSOLE APPLICATIONS

What if you want to pass a value type into a method and modify it? C# provides two ways of doing this using the **ref** and **out** keywords.

The **ref** keyword tells the C# compiler that the arguments being passed point to the same memory as the variables in the calling code. That way, if the called method modifies these values and then returns, the calling code's variables will have been modified. When you use the **ref** keyword, you must initialize the passed arguments before calling the method. See the example [RefTest.cs](#) below.

```
using System;
public class RefTest {
    int p = 3;
    public RefTest() {
        refMethod(ref p);
    }
    public static void Main(string[] args) {
        RefTest t = new RefTest();
        Console.WriteLine(t.p);
    }
    void refMethod(ref int n) {
        n += 3;
    }
}
```

The only difference between the **ref** keyword and the **out** keyword is that the **out** keyword doesn't require the calling code to initialize the passed arguments first. See the example [OutTest.cs](#) below.

```
using System;
public class OutTest {
    int p;
    public OutTest() {
        outMethod(out p);
    }
    public static void Main(string[] args) {
        OutTest t = new OutTest();
        Console.WriteLine(t.p);
    }
    void outMethod(out int n) {
        n = 3;
    }
}
```

We will now use the **ref** keyword on a string variable and modify the previous [RefTest.cs](#) program and call it [RefTest2.cs](#)

```
using System;
public class RefTest2 {
    string s = "Satish";
    public RefTest2() {
        refMethod(ref s);
    }
    public static void Main(String[] args) {
        RefTest2 t = new RefTest2();
        Console.WriteLine(t.s);
    }
    void refMethod(ref string s) {
        s = "Talim";
    }
}
```

The output is Talim, as expected. If we now remove the `ref` keyword in the above program and call the new program `RefTest3.cs`

```
using System;
public class RefTest3 {
    string s = "Satish";
    public RefTest3() {
        refMethod(s);
    }
    public static void Main(String[] args) {
        RefTest3 t = new RefTest3();
        Console.WriteLine(t.s);
    }
    void refMethod(string s) {
        s = "Talim";
    }
}
```

The output is Satish. Therefore, if a parameter is declared for a method without **ref** or **out**, the parameter can have a value associated with it. That value can be changed in the method, but the changed value will not be retained when control passes back to the calling procedure. By using a method parameter keyword (`ref`, `out`), you can change this behavior.

2.28.1 Method Overloading

C# allows you to declare more than one method with the same name. This is called overloading. **Overloaded methods must differ in the number and/or type of arguments they take.** The return type does not play any part in the overload resolution, since it's always possible to call a method without using the return value.

```
using System;
class Log {
    public Log(string fileName) {
        // Open fileName and seek to end.
    }
    public void WriteEntry(string entry) {
        Console.WriteLine(entry);
    }
    public void WriteEntry(int resourceId) {
        Console.WriteLine
            ("Retrieve string using resource id and write to log");
    }
}
```

2.28.2 Variable Method Parameters - params

You can specify a variable number of method parameters by using the **params** keyword and by specifying an array in the method's argument list.

```
// VarArgsApp.cs
using System;
class MyPoint {
    public int x;
    public int y;
    public MyPoint(int x, int y) {
        this.x = x;
        this.y = y;
    }
}
class Chart {
```

C# - CONSOLE APPLICATIONS

```
public void DrawLine(params MyPoint[] p) {
    Console.WriteLine("\nThis method would print a line " +
        "along the following points:");
    for (int i = 0; i < p.GetLength(0); i++) {
        Console.WriteLine("{0}, {1}", p[i].x, p[i].y);
    }
}
}
class VarArgsApp {
    public static void Main() {
        MyPoint p1 = new MyPoint(5,10);
        MyPoint p2 = new MyPoint(5, 15);
        MyPoint p3 = new MyPoint(5, 20);
        Chart chart = new Chart();
        chart.DrawLine(p1, p2, p3);
    }
}
```

`GetLength(0)` returns the number of elements in the first dimension of the **Array**. The `DrawLine` method tells the C# compiler that it can take a variable number of *Point* objects. At run time, the method then uses a simple *for* loop to iterate through the *Point* objects that are passed, printing each one.

2.29 Handling Exceptions

C# supports exceptions in very much the same way as Java. In C#, what you throw has to be a **System.Exception** object, or something derived from **System.Exception**. Code that may give rise to exceptions is enclosed in a try block, which is followed by one or more catch blocks.

Beta 2 of the .NET framework includes built-in exception handlers for common exception types such as divide-by-zero exception. Try this code, in the source file [DBZ.cs](#)

```
using System;
public class DBZ {
    public static void Main(string[] args) {
        double a = 15.0;
        double b = 0.0;
        double result = a/b;
        Console.WriteLine("Result is {0}", result);
    }
}
```

You will get the output:

Result is Infinity

Modifying the program to [DBZ2.cs](#) as shown below, makes no difference to the output:

```
using System;
public class DBZ2 {
    public static void Main(string[] args) {
        double a = 15.0;
        double b = 0.0;
        try {
            double result = a/b;
            Console.WriteLine("Result is {0}", result);
        } catch (Exception e) {
            Console.WriteLine("Exception occurred: " + e);
        }
    }
}
```


A catch block which will catch any exception is called a general catch clause. These blocks don't specify an exception variable, and can be written like this:

```
try {
    // code which may fail
} catch {
    // handle error
}
```

A try block can also have a finally block associated with it. If a finally block exists, it will be executed before the try block is completed, and after any possible exceptions are caught in the catch clause. This will happen no matter how control leaves the try, whether it is due to normal termination, to an exception occurring, a break or continue (or goto) statement, or a return. A finally block can occur with or without catch blocks. It is an error to transfer control out of a finally block using break, continue, return or goto.

The point to note for Java programmers is: Not only is the argument to catch optional, but the entire catch clause itself is optional. Also, C# has no throws keyword. By not requiring explicit exception declarations in method signatures, C# values short-term programmer convenience over program safety and correctness.

```
public void ReadFile() {
    try {
        // code which may fail
    } finally {
        // close the file
    }
}
```

CoreException is C#'s equivalent of Error in Java and you are not expected to handle it. You can make up your own exception classes by deriving from one of the various exception classes existing. See [MyException.cs](#) below:

```
using System;
class VowelException : Exception {}
class BlankException : Exception {}
class ExitException : Exception {}

class MyException {
    public static void Main(String[] args) {
        bool finished = false;

        do {
            try {
                processUserInput();
            } catch (VowelException x) {
                Console.WriteLine("VowelException occurred: " + x);
            } catch (BlankException y) {
                Console.WriteLine("BlankException occurred: " + y);
            } catch (ExitException z) {
                Console.WriteLine("ExitException occurred: " + z);
                // Using StackTrace property of Exception class
                Console.WriteLine("Trace: " + z.StackTrace);
                finished = true;
            } finally {
                Console.WriteLine("This is the finally clause.");
            }
        } while (!finished);
    }
}
```

C# - CONSOLE APPLICATIONS

```
// Note unlike Java, we do not declare that the method
// processUserInput() throws ... exceptions
static void processUserInput() {
    Console.Write("Enter a character: ");
    String s;
    s = Console.ReadLine();
    char c = s[0];
    switch (c) {
        case 'A':
        case 'a':
        case 'E':
        case 'e':
        case 'I':
        case 'i':
        case 'O':
        case 'o':
        case 'U':
        case 'u':
            throw (new VowelException());
        case ' ':
            throw (new BlankException());
        case 'X':
            throw (new ExitException());
    }
}
```

2.30 Namespaces

Namespaces are a great way of categorizing your types and classes to avoid name collisions.

When a language develops, many third party components are available. All these parties try to give meaningful names to their classes like the Math class, or InterestCalculator etc. We as developers end up in misery due to this. Just consider an example, I am developer who is writing up a shopping cart class. I am using third party components. I purchase two such components, one calculates discount rates for retail customers and other calculates discount rates for wholesale customers. The problem arises when both these components have a class called **Discount**. Now in my shopping cart class how do I use both these classes unambiguously? eg.

```
Discount d1 = new Discount();
```

```
//Which component does the compiler here refer to? Reseller discount or Wholesaler Discount?
```

```
int discount = d1.Cal(45.78) ;
```

Some compilers will complain others might compile and use any of the components as they wish!

This problem has been identified and solved by Microsoft on the .NET Platform with the use of Namespaces. The relationship between Namespaces and classes can directly be compared to the relationship between Files and Folders. Files actually contain data, while Folders are used to just manage and logically arrange Files. Folders can also contain many files and sub folders within them.

In the same way, Classes actually contain data and Namespaces are used to logically arrange classes. Namespaces can also contain many other Namespaces and classes. This concept may seem similar to the Package - Class relationship used in Java. However, one point of caution, you DO NOT need to create folders to store classes into a Namespace. Just defining the Namespace keyword above the class definition is enough.

Again you might say that there are two companies whose abbreviated names might be XYZ and if both companies develop the Discount class then, even if they used namespaces their full names would be XYZ.Discount class? Which will lead to the problem that we faced earlier! This is very true since Namespaces only help to extend the name of a class to make it unique. Hence, Microsoft is encouraging companies to use their full names to develop components and not abbreviations, also if possible, the department names as well as the team names should be used. Therefore, a company like American Business Company should use its full name. **AmericanBusinessCompany.It.DotNet.Discount** instead of using ABC.Discount. This will help to solve the naming conflict.

C# programs are organized using namespaces. Namespaces provide a way to group classes, by providing an extra level of naming beyond the class name. To use namespaces all you have to do is place the namespace definition above your class definition. The Dot '.' is used to denote and access classes within the namespace.

Earlier, we presented a "Hello, world" program. We'll now rewrite this program (as **HelloMsg.cs**) in two pieces: a HelloMessage component that provides messages and a console application that displays messages.

First, we'll provide a HelloMessage class in a namespace. What should we call this namespace? By convention, developers put all of their classes in a namespace that represents their company or organization. We'll put our class in a namespace named JavaTech.CSharp.Introduction.

```
namespace JavaTech.CSharp.Introduction {
    public class HelloMessage {
        public string GetMessage() {
            return "Hello, world";
        }
    }
}
```

Namespaces are hierarchical, and the name JavaTech.CSharp.Introduction is actually shorthand for defining a namespace named JavaTech that contains a namespace named CSharp that itself contains a namespace named Introduction, as in:

```
namespace JavaTech {
    namespace Csharp {
        namespace Introduction
        {....}
    }
}
```

Next, we'll write a console application that uses the HelloMessage class. We could just use the fully qualified name for the class – JavaTech.CSharp.Introduction.HelloMessage – but this name is quite long and unwieldy. An easier way is to use a "using" directive, which makes it possible to use all of the types in a namespace without qualification.

```
using JavaTech.CSharp.Introduction;
class Hello {
    static void Main() {
        HelloMessage m = new HelloMessage();
        System.Console.WriteLine(m.GetMessage());
    }
}
```

Note that the two occurrences of HelloMessage are shorthand for JavaTech.CSharp.Introduction.HelloMessage.

C# also enables the definition and use of aliases. Such aliases can be useful in situation in which name collisions occur between two libraries, or when a small number of types from a much larger namespace are being used. Our example can be rewritten using aliases as:

C# - CONSOLE APPLICATIONS

```
using MessageSource = JavaTech.CSharp.Introduction.HelloMessage;
class Hello {
    static void Main() {
        MessageSource m = new MessageSource();
        System.Console.WriteLine(m.GetMessage());
    }
}
```

Namespaces are often related to assemblies (which we will cover later).

Namespace elements cannot be explicitly declared as private or protected. Only public members are allowed in a namespace. Internal is the default. The public keyword must be explicitly specified.

The following sample generates error CS1527:

```
namespace bad {
    private class fool {} // CS1527
    protected class foo2 {} // CS1527
    class foo3 { // allowed. This is internal
        static void Main() {}
    }
}
```

Inside a [namespace](#), the compiler only accepts classes, structs, unions, enums, interfaces, and delegates.

The following sample generates error CS0116:

```
namespace x {
    int xx; // CS0116
}
```

Even if you do not explicitly declare a namespace, a default namespace is created. This unnamed namespace, sometimes called the global namespace ' ', is present in every file. Any identifier in the global namespace is available for use in a named namespace. Namespaces implicitly have public access and this is not modifiable. An example of this will make it clear. Create a program, `NSP.cs`, compile and run:

```
// NSP.cs
using System;
namespace Test {
    public class Tst {
        public static void Main(string[] args) {
            GTst t = new GTst();
        }
    }
}
class GTst { // this is in the global namespace
    public GTst() {
        Console.WriteLine("GTst called...");
    }
}
```

The **using** keyword has two uses:

- Create an alias for a namespace (a **using alias**).
- Permit the use of types in a namespace, such that, you do not have to qualify the use of a type in that namespace (a **using directive**).

Java programmers should note that, we could use namespace first, followed by using or vice-versa.

The only purpose of the `using` command in this context is to save you typing and make your code simpler. It does not, for example, cause any other code or libraries to be added to your project. If your code uses base classes, you need to ensure separately that the compiler knows which assemblies to look in for the classes (`/r` switch in the compiler).

Although you can't specify a class in a `using` directive, the following variant of the `using` directive does enable you to create aliases for classes:

```
using alias = class
```

Using this form of the `using` directive, you can write code like the following:

```
using output = System.Console;
class HelloWorld {
    public static void Main() {
        output.WriteLine("Hello, World");
    }
}
```

This gives you the flexibility to apply meaningful aliases to classes that are nested several layers deep in the .NET hierarchy, thus making your code a little easier to both write and maintain.

The `using` keyword cannot be declared inside a class.

2.31 Namespaces and Assemblies

The basic element of packaging in .NET is the *assembly*. An assembly consists of Intermediate Language code, metadata that describes what is in the assembly, and any other files that the application needs to run, such as graphics and sound files (assemblies are similar to jar files in Java). On Windows systems, assemblies can be an executable (.exe) file, a DLL, or some combination of these. It may also contain resource files. One assembly can be split across more than one physical file.

There is often a correspondence between namespaces and assemblies, so that the classes in the `Finance.Bank` namespace would be built into an assembly called `Finance.Bank.dll`. This is not mandatory.

In order to create an assembly with a particular name, compile as follows:

```
csc Bankstuff.cs /t:library /out:Finance.Bank.dll
```

During compilation how can the compiler come to know which assemblies you have used and how can the compiler map the functions and class names?

To enable the compiler to know where it can find the assembly which contains all the Namespaces and classes you have used, you have to reference those assemblies during compilation with the `/Reference` or `/r` compiler switch. If you fail to reference all the assemblies you have used, the compiler cannot map the classes and Namespaces and a CS0234 Error "The type or Namespace "XXX" does not exist in the class or Namespace "XXX" is raised.

So how do you know which assemblies should you reference? A simple way would be to look at the `using` keyword, check all the Namespaces you have aliased and in which assembly (library dll) does it exist. To find this out start the Reference documentation from "Start -> Program Files -> Microsoft.NET -> Reference Documentation". Go to the ".NET Framework Reference" section, then check out which Namespaces you have used. The reference documentation contains information about the assemblies/ libraries that contain the Namespace. Once you have figured out the list of assemblies that you have to reference, use the CSC C# compiler and while compiling add the reference to all the assemblies.

Example: For a simple Win Form application the compilation string is :

C# - CONSOLE APPLICATIONS

csc

*/r: System.dll; System.Windows.Forms.dll; Microsoft.Win32.Interop.dll; System.Drawing.dll
yourcodefile.cs*

The library file mscorlib.dll is automatically referenced by the C# compiler. Mitch Denny adds that "the namespace that you reference in your source files may not actually match an assembly that you reference. The contents of a namespace can be physically split over multiple assemblies, or multiple namespaces can be present in one assembly. In the case of the root of the System.* namespace, the implementation is split across multiple files. This was done to make a useable subset of the .NET Framework for other embedded Windows and non-Windows platforms. Therefore, some of the stuff in the System.* namespace is housed in the mscorlib.dll assembly file. The other stuff is in System.DLL and other files."

If you're packaging several classes in a given namespace, you can define each of these classes in its own source code file. A programmer employing your classes can get access to all the classes within a namespace through the using keyword. Let's see this in more detail:

```
// NA.cs
using System;
namespace A {
    public class NA {
        static void Main(String[] args) {
        }
        public NA() {
            Console.WriteLine("Using A.NA");
        }
    }
}

// NB.cs
using System;
namespace A {
    public class NB {
        public NB() {
            Console.WriteLine("Using A.NB class");
        }
        static void Main() {
        }
    }
}

// Test.cs
using System;
using A;
public class Test {
    public static void Main(string[] args) {
        NA o1 = new NA();
        NB o2 = new NB();
    }
}
```

Both NA.cs and NB.cs compile. However, when Test.cs is compiled, an error occurs:

Test.cs(3, 7): error CS0234: The type or namespace name 'A' does not exist in the class or namespace ''

To overcome this error use the .NET BETA 1 instructions for DLLs -

*csc /t:library na.cs
csc /t:library nb.cs*

```
csc test.cs /r:na.dll /r:nb.dll
```

The program Test.exe will now run.

2.32 Summary of Key Concepts

- To build and run your C# programs, you will need Windows 2000, IE 5.5, Microsoft .NET SDK (Beta 1), an optional Visual Studio .NET and an optional free C# IDE – Sharp Develop.
- The .NET Framework consists of the:
 1. Common Language Runtime (CLR): The code that runs within the CLR runs in an encapsulated and managed environment, separate from other processes on the machine.
 2. Base Class Library (BCL): C# itself does not include a class library. The BCL is shared between all programming languages on the .NET.
 3. Common Type System (CTS): In the world of .NET and C# everything in the CTS is an object.
 4. All .NET programs are compiled to an intermediate language (IL), rather than to native code which can be understood by the computer's processor. This IL code is then compiled to native code either when the application is installed, or when the application is run.
- The name of the Csharp program can be anything you want.
- C# compiles straight from source code to executable (.exe), with no object files.
- C# program code is case sensitive and in free format.
- A **namespace** in C# is somewhat similar to a package statement in Java. However, the namespace name does not have to map onto physical directories, as is the case with the package statement in Java.
- **using** is very similar in concept to Java's import keyword. Unlike Java, in C# you cannot import a single class, but the whole package.
- In Main() the first character is a capital M.
- Main() is declared inside a class or struct.
- Every C# application must have a method named *Main* defined in one of its classes. It doesn't matter which class contains the method—you can have as many classes as you want in a given application—as long as one class has a method named *Main*. If you have zero or more than one Main() in a program, you can expect compiler errors.
- You can compile a program containing multiple Main() by using the `/main:< className >` switch with the C# compiler to specify which class's *Main* method is to be used. The **/main** compiler option specifies a class in which to look for a Main method. However, the **Main** method has to be defined as follows: `public static void Main(){ }`
- The **Main()** method can be written as follows:
 1. `static void Main()`
 2. `public static void Main()`
 3. `static int Main()` – it can return an int only.
 4. `static void Main(string[] args)` – can take command line arguments.
- For **Compiler Errors** - You can search for the error code in the .NET Framework SDK Documentation (which is installed with the .NET Framework SDK) for a more detailed description.

C# - CONSOLE APPLICATIONS

- **Naming Guidelines:** First alphabet of each word (eg. MyCounter) for namespaces, classes, methods, method arguments and interfaces (interfaces should start with I). Class members (variables), the first alphabet is lower-case and the start of each word is upper-case.
- C# supports three types of **comments**: `//`, `/*` and `///`. The later will be treated as normal comments by the compiler, unless you use the `/doc: filename` compiler option to tell it to generate the XML. Observe the generated .xml file - All the members of the assembly are denoted by `<member>` tags, the compiler adds the full name of the member as a name attribute. The T, F and M prefixes denote types, fields and members respectively.
- **const** members are calculated at compile-time. By default, *const* members are static.
- A **readonly** modifier, specifies that the member can have its value set once only, and afterwards is read-only. The readonly fields that we define are instance fields, meaning that the user would have to instantiate the class to use the fields.
- In C#, static members must be accessed through a class name. You can't access them via an object, as you can in Java.
- C# supports two kinds of types: *value types* and *reference types*. Value types are allocated on the stack and Reference types are allocated on the heap.
- The process of turning a value type into a reference type is known as **boxing**. The process of turning a reference type back into a value type is called **unboxing**. In the case of unboxing, an object could be cast to any type. Therefore, the cast is necessary so that the compiler can verify that the cast is valid per the specified variable type.
- All types – including value types – can be treated like objects and derive from Object. It's possible to call Object methods on any value, even values of "primitive" types such as `int`.
- All the types have fixed sizes, and will be the same size on any system.
- In C#, each of the predefined types is a shorthand (alias) for a system-provided type.
- The **decimal** type is appropriate for calculations in which rounding errors are unacceptable. Common examples include financial calculations such as tax computations and currency conversions. The `decimal` type provides 28 significant digits.
- `Equals()` is a very important method in `Object` class. The default implementation of **Equals** supports reference equality only, but subclasses can override this method to support value equality instead. In the case of value types, this method returns true if the two types are identical and have the same value.
- **string** is a reference type; the equality operators (`==` and `!=`) are overloaded to compare the values of string objects, not references.
- The `+` operator concatenates strings. The `[]` operator accesses individual characters of a string
- String literals are of type `string` and can be written in two forms, quoted and `@`-quoted.
- If you declare a string as `string str = new string("Hello");` you will get a compiler warning.
- In C#, many operators can be overloaded by the user.
- Integer arithmetic overflow either throws an `OverflowException` or discards the most significant bits of the result. Integer division by zero always throws a `DivideByZeroException`.
- Floating-point arithmetic overflow or division by zero never throws an exception, because floating-point types are based on IEEE 754 and so have provisions for representing infinity and NaN (Not a Number).

- Decimal arithmetic overflow always throws an `OverflowException`. Decimal division by zero always throws a `DivideByZeroException`.
- When integer overflow occurs, what happens depends on the execution context, which can be checked or unchecked. In a **checked** context, an `OverflowException` is thrown. In an **unchecked** context, the most significant bits of the result are discarded and execution continues.
- The switch expression must be an integer type (including `char`) or a `string`. The case labels have to be constants. Unlike Java, you no longer fall through from case to case if you omit the `break` and there's code in the case. You will get a compiler error instead, and have to use a `goto` to jump to the next (or previous) case. If you have adjacent case labels, (i.e. No code in the case) then you can fall through.
- A **foreach** statement lets you iterate over the elements in arrays and collections.
- C# supports two types of multidimensional arrays – *rectangular* and *jagged*. In rectangular arrays, every row is the same length. A jagged array is simply an array of one-dimensional arrays, each of which can be of different length if desired.
- C# provides two ways of passing a value type into a method and modify it using the **ref** and **out** keywords. The **ref** keyword tells the C# compiler that the arguments being passed point to the same memory as the variables in the calling code. That way, if the called method modifies these values and then returns, the calling code's variables will have been modified. When you use the *ref* keyword, you must initialize the passed arguments before calling the method.
- The only difference between the **ref** keyword and the **out** keyword is that the *out* keyword doesn't require the calling code to initialize the passed arguments first.
- You can specify a variable number of method parameters by using the **params** keyword and by specifying an array in the method's argument list.
- In C#, what you throw has to be a `System.Exception` object, or something derived from `System.Exception`. Beta 1 of the .NET framework includes built-in exception handlers for common exception types such as divide-by-zero exception.
- A catch block which will catch any exception is called a general catch clause. These blocks don't specify an exception variable.
- If a `finally` block exists, it will be executed before the try block is completed, and after any possible exceptions are caught in the catch clause. A `finally` block can occur with or without catch blocks.
- The argument to catch is optional, but the entire catch clause itself is optional. Also, C# has no **throws** keyword.
- Namespace elements cannot be explicitly declared as private or protected. Only public members are allowed in a namespace (even internal and default are allowed).
- Even if you do not explicitly declare a namespace, a default namespace is created. This unnamed namespace, sometimes called the global namespace, is present in every file. Any identifier in the global namespace is available for use in a named namespace. Namespaces implicitly have public access and this is not modifiable.
- Java programmers should note that, we could use namespace first, followed by `using` or vice-versa.
- The **using** keyword has two uses - Create an alias for a namespace or permit the use of types in a namespace, such that, you do not have to qualify the use of a type in that namespace.

C# - CONSOLE APPLICATIONS

- We are not allowed to use the same **using** directive more than once in our program ie. we cannot say:

```
using System;  
using System;
```

- You can think of assemblies are something similar to jar files in Java.

3. Object Oriented Concepts

Object-oriented technologies provide many benefits to software developers and their products. Object-oriented concepts can be difficult to grasp and one's understanding of the concepts often slowly evolve over time.

If there's a downside, it is the expense of the learning curve. Thinking in objects is a dramatic departure from thinking procedurally, and the process of designing objects is much more challenging than procedural design, especially if you're trying to create reusable objects.

The significance of object-oriented technology is that it enables programmers to design software in much the same way that they perceive the real world.

Here's an example. You can walk into a computer store, and with a little background and often some help, assemble an entire PC computer system from various components: a motherboard, a CPU chip, a video card, a hard-disk, a keyboard, and so on. Ideally, when you finish assembling all the various self-contained units, you have a system in which all the units work together to create a larger system with which you can solve the problems you bought the computer in the first place.

Internally, each of those components may be vastly complicated and engineered by different companies with different methods of design. However, you don't need to know how the component works, what every chip on the board does, or how, when you press the A key, an "A" is sent to your computer. As the assembler of the overall system, each component you use is a self-contained unit, and all you are interested in is how the unit interacts with each other. Will this video card fit into the slots on the motherboard and will this monitor work with this video card? Will each particular component speak the right commands to the other components it interacts with so that each part of the computer is understood by every other part? Once you know what the interactions are between the components and can match the interactions, putting together the overall system is easy.

Object-Oriented Programming works in exactly the same way. Using object-oriented programming, your overall program is made up of lots of different self-contained components (objects), each of which has a specific role in the program and all of which can talk to each other in predefined ways.

3.1 What is an Object?

Objects are software bundles of data and related procedures that act on that data. The procedures are also known as methods (function in C). Software objects are often used to model real-world objects you find in everyday life.

As the name implies, objects are the key concept to understanding object-oriented technology. You can look around you now and see many examples of real-world objects: your dog, your desk, your television set, and your bicycle.

These real-world objects share two characteristics: they all have attributes and they all have behaviour. For example, Bicycles have attributes (current gear, current pedal cadence, two wheels, number of gears) and behaviour (braking, accelerating, slowing down, changing gears).

Attributes are the individual things that differentiate one object from another and determine the appearance, state or other qualities of that object. Attributes of an object can also include information about its state; for example, you could have features for engine condition (off or on). Attributes are defined by variables.

C# - CONSOLE APPLICATIONS

Software objects are modeled after real world objects in that, they too, have attributes and behaviour. A software object maintains its attributes in variables and implements its behaviour with methods.

Definition: An object is a software bundle of variables and related methods.

You can represent real-world objects in programs using software objects. You might want to represent a real-world bicycle as a software object within an electronic exercise bike. However, you can also use software objects to "objectify" abstract concepts. For example, "event" is a common object used in GUI window systems to represent the event when a user presses a mouse button or types a key on the keyboard.

Everything that the software object knows (attribute) and can do (behaviour) is expressed by the variables and methods within that object. A software object that modeled your real-world bicycle would have variables that indicated the bicycle's current state: its speed is 10 mph, its pedal cadence is 90 rpm, and its current gear is the 5th gear. These variables and methods are formally known as instance variables and instance methods to distinguish them from class variables and class methods. The software bicycle would also have methods to brake, change the pedal cadence and change gears. (The bike would not have a method for changing the speed of the bicycle as the bike's speed is really just a side-effect of what gear it's in, how fast the rider is pedaling and how steep the hill is).

Anything that an object does not know or cannot do is excluded from the object. For example, your bicycle (probably) doesn't have a name, and it can't run, bark or fetch. Thus, there are no variables or methods for those states and behaviours.

As you can visualise, the object's variables make up the center or nucleus of the object and the methods surround and hide the object's nucleus from other objects in the program. Packaging an object's variables within the protective custody of its methods is called encapsulation. Typically, encapsulation is used to hide unimportant implementation details from other objects. When you want to change gears on your bicycle, you don't need to know how the gear mechanism works; you just need to know which lever to move. Thus, the implementation can change at any time without changing other parts of the program.

3.2 The Benefit of Encapsulation

Encapsulating related variables and methods into a neat software bundle is a simple yet powerful idea that provides two primary benefits to software developers:

- Modularity - the source code for an object can be written and maintained independently of the source code for other objects. In addition, an object can be easily passed around in the system. You can give your bicycle to someone else and it will still work.
- Information hiding - an object has a public interface which other objects can use to communicate with it. However, the object can maintain private information and methods that can be changed at any time without affecting the other objects that depend on it. You don't need to understand the gear mechanism on your bike in order to use it.

3.3 What are Messages?

Software objects interact and communicate with each other via messages.

A single object alone is generally not very useful and usually appears as a single component of a larger program or application that contains many other objects. It is through the interaction of these objects that programmers achieve higher order functionality and more complex behaviour. Your bicycle hanging from a hook in the garage is just a bunch of titanium alloy and rubber; by itself, the bicycle is incapable of any activity. The bicycle is useful only when another object (you) interact with it (start pedaling).

Software objects interact and communicate with each other by sending messages to each other. When object A wants object B to perform one of its methods, object A sends a message to object B.

Sometimes the receiving object needs more information so that it knows exactly what to do - for example, when you want to change gears on your bicycle, you have to indicate which gear you want. This information is passed along with the message as parameters. The message parameters are actually the parameters to a method. The method's return type is the object's response to the message.

Three components comprise a message:

- the object to whom the message is addressed (bicycle)
- the name of the method to perform (change gears)
- any parameters needed by the method (to a higher gear)

These three components are enough information for the receiving object to perform the desired method. No other information or context is required.

The Benefit of Messages:

Everything an object can do is expressed through its methods, so message passing supports all possible interactions between objects.

Objects don't need to be in the same process or even on the same machine to send and receive messages back and forth to each other.

3.4 What are Classes?

A class is a blueprint, prototype or **description** that defines the variables and the methods common to all objects of a certain kind.

In the real world, you often have many objects of the same kind. For example, your bicycle is just one of many bicycles in the world. Using object-oriented terminology, we say that your bicycle object is an instance of the class of objects known as bicycles. All bicycles have some attributes (current gear, current cadence, two wheels) and behaviour (change gears, brake) in common. However, each bicycle's attribute is independent of and can be different from other bicycles.

When building bicycles, manufacturers take advantage of the fact that bicycles share characteristics and they build many bicycles from the same blueprint - it would be very inefficient to produce a new blueprint for every individual bicycle they manufactured.

In object-oriented software, it's also possible to have many objects of the same kind that share characteristics: rectangles, employee records, video clips and so on. Like the bicycle manufacturers, you can take advantage of the fact that objects of the same kind are similar and you can create a blueprint for those objects. Software "blueprints" for objects are called classes.

Hence, a class is a data structure that contains data members (constants, fields, and events), function members (methods, properties, indexers, operators, constructors, and destructors), and nested types. Class types support inheritance, a mechanism whereby derived classes can extend and specialize base classes.

Definition: A class is a blueprint or prototype that defines a group of data items called fields or variables and the associated functions or methods that perform operations on this data. Hence, classes are software blueprints for objects.

The Benefit of Classes:

C# - CONSOLE APPLICATIONS

Objects provide the benefit of modularity and information hiding. Classes provide the benefit of reusability. Bicycle manufacturers reuse the same blueprint repeatedly to build many bicycles. Software programmers use the same class repeatedly to create many objects.

When you write a C# program, you design and construct a set of classes. Then, when your program runs, instances of those classes are created and discarded as needed. Your task, as a C# programmer, is to create the right set of classes to accomplish what your program needs to accomplish.

The C# environment comes with a library of classes that implement a lot of the basic behaviour you need - not only for basic programming tasks (classes to provide basic math functions, arrays, strings, and so on), but also for graphics and networking behaviour. A class library is a set of classes.

Because each instance of a class can have different values for its variables, each variable is called an instance variable.

Class declarations are used to define new reference types. **C# supports single inheritance only, but a class may implement multiple interfaces.**

Class members can include constants, fields, methods, properties, indexers, events, operators, constructors, destructors, and nested type declaration.

The differentiation between classes and objects is often the source of some confusion. In the real world, it's obvious that classes are not themselves the objects that they describe - a blueprint of a bicycle is not a bicycle. However, it's a little more difficult to differentiate classes and objects in software. This is partially because software objects are electronic models of real-world objects or abstract concepts in the first place. People use the term "object" inconsistently and use it to refer to both classes and instances.

So far, a class's methods and variables don't exist yet. You must create an instance from the class before you can call the methods and before the variables can have any values. In comparison, an object's methods and variables actually exist and you can use it. You can send the object a message and it will respond by performing the method and perhaps modifying the values of the variables.

An instance of a class is another word for an actual object. If the class is the general representation of an object, an instance is its concrete representation.

3.5 What is Inheritance?

Classes inherit variables and methods from their superclass. Inheritance provides a powerful and natural mechanism for organising and structuring software programs.

Generally speaking, objects are defined in terms of classes. You know a lot about an object by knowing its class. Even if you don't know what a penny-farthing is, if I told you it was a bicycle, you would know that it had two wheels, handle bars and pedals.

Object-oriented systems take this a step further and allow classes to be defined in terms of other classes. For example, mountain bikes, racing bikes and tandems are all different kinds of bicycles. In object-oriented terminology, mountain bikes, racing bikes and tandems are all subclasses of the bicycle class. Similarly, the bicycle class is the superclass of mountain bikes, racing bikes and tandems.

Each subclass inherits attribute (in the form of variable declarations) from the superclass. Mountain bikes, racing bikes and tandems share some attributes: cadence, speed and the like. In addition, each subclass inherits methods from the superclass. Mountain bikes, racing bikes and tandems share some methods: braking and changing pedaling speed.

However, subclasses are not limited to the state and behaviours provided to them by their superclass. Subclasses can add variables and methods to the ones they inherited from the superclass. Tandem bicycles have two seats and two sets of handle bars; some mountain bikes have an extra set of gears with a lower gear ratio.

Subclasses can also override inherited methods and provide specialised implementations for those methods. For example, if you had a mountain bike with an extra set of gears, you would override the "change gears" method so that the rider could actually use those new gears.

You are not limited to just one layer of inheritance - the inheritance tree, or class hierarchy, can be as deep as needed. Methods and variables are inherited down through the levels. The further down in the hierarchy a class appears, the more specialised its behaviour.

At the top of the C# class hierarchy is the class Object; all classes inherit from this one superclass. Object is the most general class in the hierarchy; it defines methods inherited by all the classes in the C# class hierarchy.

You can think of a class hierarchy as defining very abstract concepts at the top of the hierarchy and those ideas becoming more concrete the farther down the chain of superclasses you go.

What if your class defines entirely new behaviour, and isn't really a subclass of another class? Your class can also inherit directly from Object, which still allows it to fit neatly into the C# class hierarchy. In fact, if you create a class definition that doesn't indicate its superclass in the first line, C# automatically assumes that you are inheriting from Object. The Motorcycle class you created, inherited from Object.

Each C# class can have only one superclass i.e. single inheritance.

The Benefit of Inheritance:

- Subclasses provide specialised behaviours from the basis of common elements provided by the superclass. With inheritance, programmers can reuse the code in the superclass many times.
- Programmers can implement superclasses that define "generic" behaviours (called abstract classes). The essence of the superclass is defined and may be partially implemented but much of the class is left undefined and non- implemented. Other programmers fill in the details with specialised subclasses.

4. Class and Object

4.1 Class Declaration

The use of a class tells the compiler that it's a reference type. All declarations of data members and methods take place between the opening and closing curly brackets. As in Java, the classes are defined and implemented in the same place. Class methods are invoked by using the dot notation. The data members in C# classes are set to certain **default values**, 0 for numeric types, false for Boolean, '\0' for chars and null for references.

A *class-declaration* is a *type-declaration* that declares a new class.

class-declaration:

```
attributesopt class-modifiersopt class identifier class-baseopt class-body ;opt
```

A *class-declaration* consists of an optional set of *attributes*, followed by an optional set of *class-modifiers*, followed by the keyword `class` and an *identifier* that names the class, followed by an optional *class-base* specification, followed by a *class-body*, optionally followed by a semicolon.

Some example classes:

```
// MotorCycle.cs
using System;
public class MotorCycle {
    string colour, make;
    bool engineState;
    public MotorCycle() {
        Console.WriteLine("Constructor called");
    }
    public void startEngine() {
        if (engineState)
            Console.WriteLine("Engine is Already ON");
        else {
            engineState = true;
            Console.WriteLine("Engine is now ON");
        }
    }
    public void showAttr() {
        Console.WriteLine("Make   is = " + make);
        Console.WriteLine("Colour is = " + colour);
        if (engineState)
            Console.WriteLine("Engine is Running");
        else
            Console.WriteLine("Engine is Idle");
    }
    public static void Main(String[] args) {
        MotorCycle m = new MotorCycle();
        m.make = "Yamaha";
        m.colour = "black";
        m.startEngine();
        m.showAttr();
        m.startEngine();
    }
}
```

```
// Account.cs
using System;
```



```

class Account {
    private double balance; // data member
    public Account(){
        balance = 0.0;
    }
    public Account(double amt){
        balance = amt;
    }
    public bool Deposit(double amt){
        //deposit cash
        if (amt <= 0.0)
            return false;
        else {
            balance += amt;
            return true;
        }
    }
    public bool Withdraw(double amt){
        //withdraw cash
        if ((balance-amt) < 0.0)
            return false;
        else
            balance -=amt;
        return true;
    }
    public double QueryBalance(){
        return balance;
    }
}
public class SMT {
    public static void Main(String[] args){
        Account a1 = new Account();
        Account a2 = new Account(3000.00);
    }
}

```

4.1.1 Class modifiers

A *class-declaration* may optionally include a sequence of class modifiers:

```

class-modifier:
    new
    public
    protected
    internal
    private
    abstract
    sealed

```

It is an error for the same modifier to appear multiple times in a class declaration.

The `new` modifier is only permitted on nested classes. It specifies that the class hides an inherited member by the same name.

The `public`, `protected`, `internal`, and `private` modifiers control the accessibility of the class. Depending on the context in which the class declaration occurs, some of these modifiers may not be permitted.

The `abstract` and `sealed` modifiers are discussed in the following sections.

C# - CONSOLE APPLICATIONS

4.1.1.1 Abstract classes

The abstract modifier is used to indicate that a class is incomplete and intended only to be a base class of other classes. An abstract class differs from a non-abstract class in the following ways:

- An abstract class cannot be instantiated, and it is an error to use the new operator on an abstract class. While it is possible to have variables and values whose compile-time types are abstract, such variables and values will necessarily either be null or contain references to instances of non-abstract classes derived from the abstract types.
- An abstract class is permitted (but not required) to contain abstract methods and accessors.
- An abstract class cannot be sealed.

When a non-abstract class is derived from an abstract class, the non-abstract class must include actual implementations of all inherited abstract methods and accessors. Such implementations are provided by overriding the abstract methods and accessors. In the example

```
abstract class A {
    public abstract void F();
}
abstract class B: A {
    public void G() {}
}
class C: B {
    public override void F() {
        // actual implementation of F
    }
}
```

the abstract class A introduces an abstract method F. Class B introduces an additional method G, but doesn't provide an implementation of F. B must therefore also be declared abstract. Class C overrides F and provides an actual implementation. Since there are no outstanding abstract methods or accessors in C, C is permitted (but not required) to be non-abstract. You should note that the presence of an abstract method in a class doesn't implicitly make the class abstract. You have to use the abstract modifier on the class as well. The following example illustrates this:

```
public class Account {
    public abstract bool withdraw(double amt);
}
```

When we compile this we get an error:

```
Test.cs(2,24): error CS0513: 'Account.withdraw(double)' is abstract but it is contained in nonabstract class 'Account'
```

The correct way to write is as follows:

```
public abstract class Account {
    public abstract bool withdraw(double amt);
}
```

Implementing classes could be SavingsAccount, CurrentAccount.

4.1.1.2 Sealed classes

The sealed modifier (similar to final in Java) is used to prevent derivation from a class. An error occurs if a sealed class is specified as the base class of another class.

A sealed class cannot also be an abstract class.

The sealed modifier is primarily used to prevent unintended derivation, but it also enables certain run-time optimizations.

The sealed modifier cannot be used on methods.

Example:

```
using System;
sealed class MyPoint {
    public MyPoint(int x,int y) {
        this.x =x;
        this.y =y;
    }
    private int X;
    public int x {
        get {
            return this.X;
        }
        set {
            this.X =value;
        }
    }
    private int Y;
    public int y {
        get {
            return this.Y;
        }
        set {
            this.Y = value;
        }
    }
}
class SealedApp {
    public static void Main() {
        MyPoint pt = new MyPoint(6,16);
        Console.WriteLine("x = {0}, y = {1}", pt.x, pt.y);
    }
}
```

Note that we used the *private* access modifier on the internal class members *X* and *Y*. Using the *protected* modifier would result in a warning from the compiler because of the fact that protected members are visible to derived classes and, as you now know, sealed classes don't have any derived classes.

4.1.1.3 Inner Classes

We can have inner classes as shown in the program **IC.cs**

```
using System;
public class A {
    public class B {
        public class C {
            public C() {
                Console.WriteLine("In C");
            }
        }
    }
}
static void Main() {
    A.B.C c = new A.B.C();
}
```

C# - CONSOLE APPLICATIONS

```
}  
}
```

4.1.1.4 Base classes

When a *class-type* is included in the *class-base*, it specifies the direct base class of the class being declared. If a class declaration has no *class-base*, or if the *class-base* lists only interface types, the direct base class is assumed to be `object`. A class inherits members from its direct base class.

In the example:

```
class A {}  
class B: A {}
```

class A is said to be the direct base class of B, and B is said to be derived from A. Since A does not explicitly specify a direct base class, its direct base class is implicitly `object`.

The direct base class of a class type must be at least as accessible as the class type itself. For example, it is an error for a `public` class to derive from a `private` or `internal` class (see example `Assembly2.cs` later on).

The base classes of a class are the direct base class and its base classes. In other words, the set of base classes is the transitive closure of the direct base class relationship. Referring to the example above, the base classes of B are A and `object`.

Except for class `object`, every class has exactly one direct base class. The `object` class has no direct base class and is the ultimate base class of all other classes.

When a class B derives from a class A, it is an error for A to depend on B. A class *directly depends on* its direct base class (if any) and *directly depends on* the class within which it is immediately nested (if any). Given this definition, the complete set of classes upon which a class depends is the transitive closure of the *directly depends on* relationship.

The example:

```
class A: B {}  
class B: C {}  
class C: A {}
```

is in error because the classes circularly depend on themselves. Likewise, the example

```
class A: B.C {}  
class B: A {  
    public class C {}  
}
```

is in error because A depends on B.C (its direct base class), which depends on B (its immediately enclosing class), which circularly depends on A.

Note that a class does not depend on the classes that are nested within it. In the example

```
class A {  
    class B: A {}  
}
```

B depends on A (because A is both its direct base class and its immediately enclosing class), but A does not depend on B (since B is neither a base class nor an enclosing class of A). Thus, the example is valid.

It is not possible to derive from a sealed class. In the example

```
sealed class A {}  
class B: A {} // Error, cannot derive from a sealed class  
class B is in error because it attempts to derive from the sealed class A.
```

4.1.1.5 Internal class

Internal members are accessible only within files in the same assembly. A common use of internal access is in component-based development because it enables a group of components to cooperate in a private manner without being exposed to the rest of the application code. For example, a framework for building graphical user interfaces could provide Control and Form classes that cooperate using members with internal access. Since these members are internal, they are not exposed to code that is using the framework.

It is an error to reference a member with internal access outside the assembly within which it was defined.

This example contains two files, Assembly1.cs and Assembly2.cs. The first file contains an internal base class, BaseClass. In the second file, an attempt to access the member of the base class will produce an error.

File **Assembly1.cs**:

```
// compile with /target:library
internal class BaseClass {
    public static int IntM = 0;
}
```

File **Assembly2.cs**:

```
// compile with /target:exe /reference:Assembly1.dll
public class TestAccess {
    public static void Main() {
        // error, BaseClass not visible outside assembly
        BaseClass myBase = new BaseClass();
    }
}
```

4.1.1.6 Interface implementations

A *class-base* specification may include a list of interface types, in which case the class is said to implement the given interface types.

4.1.2 Class body

The *class-body* of a class defines the members of the class.

```
class-body:
    { class-member-declarationsopt }
```

4.1.2.1 Class members

The members of a class consist of the members introduced by its *class-member-declarations* and the members inherited from the direct base class.

```
class-member-declarations:
    class-member-declaration
    class-member-declarations class-member-declaration
```

C# - CONSOLE APPLICATIONS

class-member-declaration:
constant-declaration
field-declaration
method-declaration
property-declaration
event-declaration
indexer-declaration
operator-declaration
constructor-declaration
destructor-declaration
static-constructor-declaration
type-declaration

The members of a class are divided into the following categories:

- Constants, which represent constant values associated with the class.
- Fields, which are the variables of the class.
- Methods, which implement the computations and actions that, can be performed by the class.
- Properties, which define named attributes and the actions associated with reading and writing those attributes.
- Events, which define notifications that, are generated by the class.
- Indexers, which permit instances of the class to be indexed in the same way as arrays.
- Operators, which define the expression operators that, can be applied to instances of the class.
- Instance constructors, which implement the actions, required to initialize instances of the class.
- Destructors, which implement the actions to perform before instances of the class, are permanently discarded.
- Static constructors, which implement the actions, required to initialize the class itself.
- Types, which represent the types that, are local to the class.

Members that contain executable code are collectively known as the *function members* of the class. The function members of a class are the methods, properties, indexers, operators, constructors, and destructors of the class.

A *class-declaration* creates a new declaration space, and the *class-member-declarations* immediately contained by the *class-declaration* introduce new members into this declaration space. The following rules apply to *class-member-declarations*:

- **Constructors and destructors must have the same name as the immediately enclosing class.** All other members must have names that differ from the name of the immediately enclosing class.
- The name of a constant, field, property, event, or type must differ from the names of all other members declared in the same class.
- The name of a method must differ from the names of all other non-methods declared in the same class. In addition, the *signature* of a method must differ from the signatures of all other methods declared in the same class.
- The signature of an indexer must differ from the signatures of all other indexers declared in the same class.

- The signature of an operator must differ from the signatures of all other operators declared in the same class.

The inherited members of a class are specifically not part of the declaration space of a class. Thus, a derived class is allowed to declare a member with the same name or signature as an inherited member (which in effect hides the inherited member).

4.1.2.2 Signature

Methods, constructors, indexers, and operators are characterized by their signatures:

The signature of a method consists of the name of the method and the number, modifiers, and types of its formal parameters. The signature of a method specifically does not include the return type.

The signature of a constructor consists of the number, modifiers, and types of its formal parameters.

The signature of an indexer consists of the number and types of its formal parameters. The signature of an indexer specifically does not include the element type.

The signature of an operator consists of the name of the operator and the number and types of its formal parameters. The signature of an operator specifically does not include the result type.

4.1.2.3 Constructors

A constructor is a method, which is called when an object of a class type is constructed, and is usually used for initialisation. A constructor method has several characteristics:

- It has the same name as the class name
- It has no return type
- It does not return any value.

Java Programmers should note that: If you attempt to prefix a constructor with a type, the compiler will emit an error stating that you cannot define members with the same names as the enclosing type.

In the example `VarTest.cs`:

```
class VarTest {
    public VarTest() {

    }
    static void Main() {
        VarTest t;
    }
}
```

If you compile the above program, the C# compiler will warn you that the variable `t` has been declared but is never used in the application.

Constructor Initializers:

All C# object constructors—with the exception of the *System.Object* constructors—include an invocation of the base class's constructor immediately before the execution of the first line of the constructor. These constructor initializers enable you to specify which class and which constructor you want called. This takes two forms:

- An initializer of the form `base(.)` enables the current class's base class constructor—that is, the specific constructor implied by the form of the constructor called—to be called.

C# - CONSOLE APPLICATIONS

- An initializer taking the form *this(.)* enables the current class to call another constructor defined within itself. This is useful when you have overloaded multiple constructors and want to make sure that a default constructor is always called.

```
using System;
class A {
    public A() {
        Console.WriteLine("A");
    }
}
class B : A {
    public B() : base() {
        Console.WriteLine("B");
    }
}
class BaseDefaultInitializerApp {
    public static void Main() {
        B b = new B();
    }
}
```

Another example, is when there are two classes: *A* and *B*. This time, class *A* has two constructors, one that takes no arguments and one that takes an *int*. Class *B* has one constructor that takes an *int*. The problem arises in the construction of class *B*. How do we ensure that the desired class *A* constructor will be called? By explicitly telling the compiler which constructor we want called in the initializer list, as below:

```
using System;
class A {
    public A() {
        Console.WriteLine("A");
    }
    public A(int foo) {
        Console.WriteLine("A = {0}", foo);
    }
}
class B : A {
    public B(int foo) : base(foo) {
        Console.WriteLine("B = {0}", foo);
    }
}
class DerivedInitializer2App {
    public static void Main() {
        B b = new B(42);
    }
}
```

An example of *this(.)* is now provided through the example [ThisEx.cs](#)

```
// ThisEx.cs
using System;
class Tmp {
    public Tmp() {
        Console.WriteLine("In Tmp()");
    }
    public Tmp(int i) : this() {
        Console.WriteLine("In Tmp with int");
    }
}
```



```

}
static void Main() {
    Tmp t = new Tmp(10);
}
}

```

You can use overloading to create several constructors for a class; which one will get called depends on the arguments you give to new.

It's to be noted that:

- Constructors are not inherited. Thus, a class has no other constructors than those that are actually declared in the class. If a class contains no constructor declarations, a default constructor is automatically provided. The default constructor simply invokes the parameterless constructor of the direct base class. If the direct base class does not have an accessible parameterless constructor, an error occurs.
- If you write a class with only one constructor with parameters and use it while creating an object, then a default constructor need not be given.
- If you write a class with only one constructor with parameters and try to create an object using a default constructor (not given by you) then the program does not compile. **As in Java, it's advisable to write a default constructor for every class you write.**
- **Constructors are usually public, but can also be private or protected.** When a class declares only private constructors, it is not possible for other classes to derive from the class or create instances of the class (an exception being classes nested within the class). **Private constructors are commonly used in classes that contain only static members.** For example:

```

public class Trig {
    private Trig() {} // Prevent instantiation
    public const double PI = 3.14159265358979323846;
    public static double Sin(double x) {...}
    public static double Cos(double x) {...}
    public static double Tan(double x) {...}
}

```

The Trig class provides a grouping of related methods and constants, but is not intended to be instantiated. It therefore declares a single private constructor. Note that at least one private constructor must be declared to suppress the automatic generation of a default constructor (which always has public access).

In the **Tree.cs** program below – **Java programmers should note that the name of the program can be anything you want (in any case too). All classes can be public or otherwise. Also note that in the program there can be only one and only one Main() method.**

```

using System;
public class GF {
    public GF() {
        Console.WriteLine("In GF");
    }
}
public class F : GF { // : is similar to extends in Java
    public F() {
        Console.WriteLine("In F");
    }
}
public class S : F {
    public S() {
        Console.WriteLine("In S");
    }
}

```

C# - CONSOLE APPLICATIONS

```
public static void Main(String[] args){
    S son = new S();
}
```

4.1.2.4 Calling Base Class Constructors

```
public class CheckAccount : Account {
    public CheckAccount(double amt) : base(amt) {
    }
}
```

Here, if a CheckAccount is created with a double being passed in to the constructor, that double is passed on to the base class constructor. The compiler sees base(amt) as meaning, Pass amt through to the base class constructor which takes one double as an argument. In this case, Account has a suitable constructor, so the compiler can find and use it.

4.1.2.5 Static Constructors

Static constructors implement the actions required to initialize a class i.e the constructor is called when the class is loaded. Static constructors are declared using *static-constructor-declarations*:

```
static-constructor-declaration:
    attributesopt static identifier ( ) block
```

A *static-constructor-declaration* may include set of *attributes*.

The *identifier* of a *static-constructor-declaration* must name the class in which the static constructor is declared. If any other name is specified, an error occurs.

The *block* of a static constructor declaration specifies the statements to execute in order to initialize the class. This corresponds exactly to the *block* of a static method with a void return type.

Static constructors are not inherited.

Static constructors are invoked automatically, and cannot be invoked explicitly. The exact timing and ordering of static constructor execution is not defined, though several guarantees are provided:

- The static constructor for a class is executed before any instance of the class is created.
- The static constructor for a class is executed before any static member of the class is referenced.
- The static constructor for a class is executed before the static constructor of any of its derived classes are executed.
- The static constructor for a class never executes more than once.
- The static constructor cannot have parameters.
- There's no such thing as a static destructor.

The example **SC1.sc**

```
using System;
class SC1 {
    static void Main() {
        A.F();
        B.F();
    }
}
class A {
    static A() {
```

```

        Console.WriteLine("Init A");
    }
    public static void F() {
        Console.WriteLine("A.F");
    }
}
class B {
    static B() {
        Console.WriteLine("Init B");
    }
    public static void F() {
        Console.WriteLine("B.F");
    }
}

```

could produce either the output:

```

Init A
A.F
Init B
B.F

```

or the output:

```

Init B
Init A
A.F
B.F

```

because the exact ordering of static constructor execution is not defined.

The example **SC2.cs**

```

using System;
class SC2 {
    static void Main() {
        Console.WriteLine("1");
        B.G();
        Console.WriteLine("2");
    }
}
class A {
    static A() {
        Console.WriteLine("Init A");
    }
}
class B: A {
    static B() {
        Console.WriteLine("Init B");
    }
    public static void G() {
        Console.WriteLine("B.G");
    }
}

```

is guaranteed to produce the output:

```

1
Init A
Init B
B.G
2

```

C# - CONSOLE APPLICATIONS

because the static constructor for the class A must execute before the static constructor of the class B, which derives from it.

In the example **SRO.cs** below, the screen resolution fields are static and read-only, and there's a static constructor.

using System;

```
class GraphicsPackage {
    public static readonly int ScreenWidth;
    public static readonly int ScreenHeight;
    static GraphicsPackage() {
        // Code would be here to
        // calculate resolution.
        ScreenWidth = 1024;
        ScreenHeight = 768;
    }
}
class ReadOnlyApp {
    public static void Main() {
        Console.WriteLine("Width = {0}, Height = {1}",
            GraphicsPackage.ScreenWidth,
            GraphicsPackage.ScreenHeight);
    }
}
```

4.1.2.6 Destructors

Destructors are also called a finalizer. C# destructors are very similar to Java's finalize() method, and have all the same disadvantages.

Destructors implement the actions required to destruct instances of a class. Destructors are declared using *destructor-declarations*:

destructor-declaration:
attributes_{opt} ~ identifier () block

A *destructor-declaration* may include set of *attributes*.

The *identifier* of a *destructor-declaration* must name the class in which the destructor is declared. If any other name is specified, an error occurs.

The *block* of a destructor declaration specifies the statements to execute in order to initialize a new instance of the class. This corresponds exactly to the *block* of an instance method with a void return type.

Destructors are not inherited. Thus, a class has no other destructors than those that are actually declared in the class.

Destructors are invoked automatically, and cannot be invoked explicitly. An instance becomes eligible for destruction when it is no longer possible for any code to use the instance. Execution of the destructor or destructors for the instance may occur at any time after the instance becomes eligible for destruction. When an instance is destructed, the destructors in an inheritance chain are called in order, from most derived to least derived.

The name of a class destructor is the class name preceded by a tilde (~). They are always public and have no return value. They do not take any arguments, so there can only ever be one for a class.

An example:

```
public class SMT {
```

```

private int xyz;
public SMT() {
    xyz = 25;
}
~SMT() {
    // tidy up
}
}

```

4.1.2.7 Inheritance - Single

A class *inherits* (use: instead of extends as in Java) the members of its direct **base** class. Inheritance means that a class implicitly contains all members of its direct base class, except for the constructors and destructors of the base class. Some important aspects of inheritance are:

- Inheritance is transitive. If C is derived from B, and B is derived from A, then C inherits the members declared in B as well as the members declared in A.
- A derived class *extends* its direct base class. A derived class can add new members to those it inherits, but it cannot remove the definition of an inherited member.
- Constructors and destructors are not inherited, but all other members are, regardless of their declared accessibility. However, depending on their declared accessibility, inherited members may not be accessible in a derived class.
- A derived class can *hide* inherited members by declaring new members with the same name or signature. Note however that hiding an inherited member does not remove the member—it merely makes the member inaccessible in the derived class.
- An instance of a class contains a copy of all instance fields declared in the class and its base classes, and an implicit conversion exists from a derived class type to any of its base class types. Thus, a reference to a derived class instance can be treated as a reference to a base class instance.
- A class can declare virtual methods, properties, and indexers, and derived classes can override the implementation of these function members. This enables classes to exhibit polymorphic behavior wherein the actions performed by a function member invocation vary depending on the run-time type of the instance through which the function member is invoked.

4.1.2.8 Accessing Base Class Members

You may want to call a method in a class' base class from time to time. You can do this using the **base** keyword. **base is in many ways the equivalent of Java's super keyword.**

4.1.2.9 The this Reference

A class method is always called in the context of some object. Suppose you wanted to know which object has called a method – you can get at this via the keyword **this**, which is a reference to the object that called the method.

4.1.2.10 The new modifier

A *class-member-declaration* is permitted to declare a member with the same name or signature as an inherited member. When this occurs, the derived class member is said to *hide* the base class member. Hiding an inherited member is not considered an error, but it does cause the compiler to issue a warning. To suppress the warning, the declaration of the derived class member can include a new modifier to indicate that the derived member is intended to hide the base member.

C# - CONSOLE APPLICATIONS

If a new modifier is included in a declaration that doesn't hide an inherited member, a warning is issued to that effect. This warning is suppressed by removing the new modifier.

It is an error to use the new and override modifiers in the same declaration.

Use the **new** modifier to explicitly hide a member inherited from a base class. To hide an inherited member, declare it in the derived class using the same name, and modify it with the **new** modifier.

Consider the following class:

```
public class MyBaseC {
    public int x;
    public void Invoke();
}
```

Declaring a member with the name M in a derived class, for example:

```
public class MyDerivedC : MyBaseC {
    new public void Invoke();
}
```

will hide the method Invoke() in the base class. However, the field x will not be affected because it is not hidden by a similar name.

In the example below (**MyDerivedC.cs**) a base class, MyBaseC, and a derived class, MyDerivedC, use the same field name x, thus hiding the value of the inherited field. The example demonstrates the use of the **new** modifier. It also demonstrates how to access the hidden members of the base class by using the fully qualified names.

```
// The new modifier
using System;
public class MyBaseC {
    public static int x = 55;
    public static int y = 22;
}
public class MyDerivedC : MyBaseC {
    new public static int x = 100;    // Name hiding
    public static void Main() {
        // Display the overlapping value of x:
        Console.WriteLine(x);
        // Access the hidden value of x:
        Console.WriteLine(MyBaseC.x);
        // Display the unhidden member y:
        Console.WriteLine(y);
    }
}
```

Output

```
100
55
22
```

If you remove the **new** modifier, the program will still compile and run, but you will get the warning:

SC0108: The keyword new is required on 'MyDerivedC.x' because it hides inherited member 'MyBaseC.x'.

4.1.2.11 Casting between Types

Assuming a base class named *Employee* and a derived class named *ContractEmployee*, the following code works because there's always an implied upcast from a derived class to its base class:

```
class Employee { }
class ContractEmployee : Employee { }
class CastExample1 {
    public static void Main () {
        Employee e = new ContractEmployee();
    }
}
```

However, the following is illegal, because the compiler cannot provide an implicit downcast:

```
class Employee { }
class ContractEmployee : Employee { }
class CastExample2 {
    public static void Main () {
        ContractEmployee ce = new Employee(); // Won't compile.
    }
}
```

Remember: **a derived class can be used in place of its base class.**

In the next example, the program compiles but throws a *System.InvalidCastException* at run-time.

```
class Employee { }
class ContractEmployee : Employee { }
class CastExample3 {
    public static void Main () {
        //Downcast will fail.
        ContractEmployee ce = (ContractEmployee)new Employee();
    }
}
```

There is one other way of casting objects: using the *as* keyword. The advantage to using this keyword instead of a cast is that if the cast is invalid, you don't have to worry about an exception being thrown. What will happen instead is that the result will be *null*. Here's an example:

```
using System;
class Employee { }
class ContractEmployee : Employee { }
class CastExample5 {
    public static void Main () {
        Employee e = new Employee();
        Console.WriteLine("e = {0}",
            e == null ? "null" : e.ToString());
        ContractEmployee c = e as ContractEmployee;
        Console.WriteLine("c = {0}",
            c == null ? "null" : c.ToString());
    }
}
```

If you run this example, you'll see the following result:

```
c: >CastExample5
e = Employee
c = null
```

C# - CONSOLE APPLICATIONS

4.1.2.12 Access modifiers

A *class-member-declaration* can have any one of the five possible types of declared accessibility: `public`, `protected internal`, `protected`, `internal`, or `private`. Except for the `protected internal` combination, it is an error to specify more than one access modifier. When a *class-member-declaration* does not include any access modifiers, the declaration defaults to `private` declared accessibility.

Each member of a class has a form of accessibility, as under:

- `public` members are available to all code;
- `protected` members are accessible only from derived classes;
- `internal` members are accessible only from within the same assembly;
- `protected internal` members are accessible only from derived classes within the same assembly;
- `private` members are accessible only from the class itself.

The point to remember is that the access modifiers are associated with members or types (classes etc.) and are not allowed on namespaces.

The examples below should illustrate the above:

```
// Am.cs
using System;
public class Dad {
    public bool diamond;
    protected bool gold;
    protected internal bool silver;
    internal bool car;
    bool house;
}
class Son : Dad {
    public static void Main(String[] args) {
        Son s = new Son();
        s.diamond = true;
        s.gold = true;
        s.silver = true;
        s.car = true;
        s.house = true; // Here private is inaccessible
        Console.WriteLine("diamond = {0}, gold = {1}", s.diamond, s.gold);
        Console.WriteLine("silver = {0}, car = {1}", s.silver, s.car);
        Console.WriteLine("house = {0}", s.house);
    }
}
```

```
// AM2.cs
using System;
public class Dad {
    public bool diamond;
    protected bool gold;
    protected internal bool silver;
    internal bool car;
    bool house;
}
class Friend {
    public static void Main(String[] args) {
```



```

Dad d = new Dad();
d.diamond = true;
d.gold    = true; // protected inaccessible
d.silver  = true;
d.car     = true;
d.house   = true; // private inaccessible
Console.WriteLine("diamond = {0}, gold = {1}", d.diamond, d.gold);
Console.WriteLine("silver  = {0}, car  = {1}", d.silver, d.car);
Console.WriteLine("house = {0}", d.house);
}
}

```

4.1.2.13 Restrictions on Using Accessibility Levels

When you declare a type, it is essential to see if that type has to be *at least as accessible as* another member or type. For example, **the direct base class must be at least as accessible as the derived class.**

The following declarations will result in a compiler error, because the base class BaseClass is less accessible than MyClass:

```

class BaseClass {...}
public class MyClass: BaseClass {...} // Error

```

4.1.2.14 Accessibility Domain

The example AM3.cs contains a top-level type, T1, and two nested classes, M1 and M2. The classes contain fields with different declared accessibilities. In the Main method, a comment follows each statement to indicate the accessibility domain of each member. Notice that the statements that attempt to reference the inaccessible members are commented out. If you want to see the compiler errors caused by referencing an inaccessible member, remove the comments one at a time.

```

using System;
namespace MyNameSpace {
    public class T1 {
        public static int myPublicInt;
        internal static int myInternalInt;
        private static int myPrivateInt = 0;
        public class M1 {
            public static int myPublicInt;
            internal static int myInternalInt;
            private static int myPrivateInt = 0;
        }
        private class M2 {
            public static int myPublicInt = 0;
            internal static int myInternalInt = 0;
            private static int myPrivateInt = 0;
        }
    }
}
public class MainClass {
    public static int Main() {
        // Access to T1 fields:
        T1.myPublicInt = 1; // Access is unlimited
        T1.myInternalInt = 2; // Accessible only in current project
        // T1.myPrivateInt = 3; // Error: inaccessible outside T1

        // Access to the M1 fields:
        T1.M1.myPublicInt = 1; // Access is unlimited
    }
}

```

C# - CONSOLE APPLICATIONS

```
T1.M1.myInternalInt = 2; // Accessible only in current project
// T1.M1.myPrivateInt = 3; // Error: inaccessible outside M1

// Access to the M2 fields:
// T1.M2.myPublicInt = 1; // Error: inaccessible outside T1
// T1.M2.myInternalInt = 2; // Error: inaccessible outside T1
// T1.M2.myPrivateInt = 3; // Error: inaccessible outside M2
return 0;
}
}
}
```

4.1.2.15 Virtual methods

One of the properties of inheritance is that we can use a derived class object through a base class reference, like this:

```
// Create a savings account
Account s1 = new CheckAccount(); //CheckAccount : Account
// Deposit and Withdraw
s1.Deposit(15000.00);
s1.Withdraw(2000.00);
```

As already mentioned, this works because a CheckAccount is an Account, so we can do everything to a CheckAccount that we can to the base class. In this case, we are simply calling the Deposit() and Withdraw() methods that CheckAccount inherits from Account.

Suppose that we want to provide CheckAccount with its own version of Withdraw(), because CheckAccounts can have an overdraft limit. We can code one up quite easily:

```
public class CheckAccount : Account {
    private double overdraftLimit = 500.00;
    public bool Withdraw(double amt) {
        if (balanceamt >= overdraftLimit) {
            base.Withdraw(amt);
            return true;
        }
        else
            return false;
    }
}
```

There's a problem with this, if we try to use our new version through an Account reference, as the compiler will insist on calling the one from Account, rather than from CheckAccount. This problem arises because the compiler has to decide which method to call, so it looks at the reference s1, sees that it is of type Account, and so calls the Account.Withdraw() method.

A **virtual method** is one where the decision on exactly which method to call is delayed until runtime, allowing the dynamic type of the reference to be used. You declare a method as virtual by using the virtual modifier in the **base** class:

```
public class Account {
    Virtual public bool Withdraw(double amt) {
    }
}
```

4.1.2.16 Override methods

When you override a virtual method in a derived class, you can use the **override** keyword to signal that you are overriding a virtual method.

```
public class CheckAccount : Account {
    private double overdraftLimit = 500.00;
    public override bool Withdraw(double amt) {
        if (balanceamt >= overdraftLimit) {
            base.Withdraw(amt);
            return true;
        }
        else
            return false;
    }
}
```

Let us wrap up this discussion with a consolidated example – **VO.cs**

```
// VO.cs
using System;
public class Account {
    public void Withdraw(double amt) {
        Console.WriteLine("Account.Withdraw method called...");
    }
}
public class CheckAccount : Account {
    public void Withdraw(double amt) {
        Console.WriteLine("CheckAccount.Withdraw method called...");
    }
    public static void Main(string[] args) {
        Account s1 = new CheckAccount();
        s1.Withdraw(5000.00);
    }
}
```

The output of the above is:

Account. Withdraw method called...

As mentioned earlier, the compiler has to decide which method to call, so it looks at the reference *s1*, sees that it is of type *Account*, and so calls the *Account. Withdraw()* method.

In the example **VO1.cs**, we use the **virtual** and **override** keywords to give a different output.

```
// VO1.cs
using System;
public class Account {
    virtual public void Withdraw(double amt) {
        Console.WriteLine("Account.Withdraw method called...");
    }
}
public class CheckAccount : Account {
    public override void Withdraw(double amt) {
        Console.WriteLine("CheckAccount.Withdraw method called...");
    }
    public static void Main(string[] args) {
        Account s1 = new CheckAccount();
        s1.Withdraw(5000.00);
    }
}
```

The output is:

CheckAccount. Withdraw method called...

C# - CONSOLE APPLICATIONS

Remember that the *virtual* keyword must be used on the base class's method, and the *override* keyword is used on the derived class's implementation of the method.

This example `VO2.cs` has the same method overridden multiple times.

```
using System;
class A {
    public virtual void MtdA() {
        Console.WriteLine("In A");
    }
}
class B : A {
    public override void MtdA() {
        Console.WriteLine("In B");
    }
}
class C : B {
    public override void MtdA() {
        Console.WriteLine("In C");
    }
}
class Tmp {
    static void Main() {
        A c = new C();
        c.MtdA();
    }
}
```

4.2 Interfaces

The **interface** keyword declares a reference type **that has abstract members**.

Interfaces are used to define a contract; a class or struct that implements the interface must adhere to this contract.

Interfaces can contain methods, properties, indexers, and events as members. They can't contain constants, fields (private data members), constructors and destructors or any type of static member.

All the members of an interface are public by definition, and the compiler will give you an error if you try to specify any other modifiers on interface members. The `static` and `public` modifiers are not permitted on interface methods.

C# interfaces are very much similar to Java interfaces. In C# we say `:` instead of implements, as in Java.

The example

```
interface Iexample {
    string this[int index] { get; set; }
    event EventHandler E;
    void F(int value);
    string P { get; set; }
}
public delegate void EventHandler(object sender, Event e);
shows an interface that contains an indexer, an event E, a method F, and a property P.
```

Interfaces may employ multiple inheritance. In the example below, **the interface `IComboBox` inherits from both `ITextBox` and `IListBox`.**

```

interface Icontrol {
    void Paint();
}
interface ITextBox: Icontrol {
    void SetText(string text);
}
interface IListbox: Icontrol {
    void SetItems(string[] items);
}
interface IComboBox: ITextBox, IListbox {}

```

Classes and structs can implement multiple interfaces. In the example below, the class `EditBox` derives from the class `Control` and implements both `IControl` and `IDataBound`.

```

interface IDataBound {
    void Bind(Binder b);
}
public class EditBox: Control, IControl, IDataBound {
    public void Paint();
    public void Bind(Binder b) {...}
}

```

In the example above, the `Paint` method from the `IControl` interface and the `Bind` method from `IDataBound` interface are implemented using public members on the `EditBox` class. C# provides an alternative way of implementing these methods that allows the implementing class to avoid having these members be public. Interface members can be implemented by using a qualified name. For example, the `EditBox` class could instead be implemented by providing `IControl.Paint` and `IDataBound.Bind` methods.

```

public class EditBox: IControl, IDataBound {
    void IControl.Paint();
    void IDataBound.Bind(Binder b) {...}
}

```

Interface members implemented in this way are called “explicit interface member implementations” because each method explicitly designates the interface method being implemented.

Explicit interface methods can only be called via the interface. For example, the `EditBox`’s implementation of the `Paint` method can be called only by casting to the `IControl` interface.

```

class SMT {
    static void Main() {
        EditBox editbox = new EditBox();
        editbox.Paint(); // error: EditBox does not have a Paint method
        IControl control = editbox;
        control.Paint(); // calls EditBox's implementation of Paint
    }
}

```

4.3 Structs

A struct in C# is simply a composite data type, consisting of a number of elements (or members) of other types. The variables which make up a struct are called its members (fields in C#), and can be accessed using a simple dot notation. It’s quite possible to nest references to structs, and you can use the dot notation to access all levels within the nested structure. You can also declare structs nested inside other structs. The list of similarities between classes and structs is long – structs can implement interfaces, and can have the same kinds of members as classes. **Structs differ from classes in several important ways, however: structs are value types rather than reference types, and inheritance is not supported for structs.** Struct values either are stored

C# - CONSOLE APPLICATIONS

“on the stack” or “in-line”. Careful programmers can enhance performance through judicious use of structs.

For example, the use of a struct rather than a class for a Point can make a large difference in the number of allocations. The program below creates and initializes an array of 100 points. With Point implemented as a class, the program instantiates 101 separate objects – one for the array and one each for the 100 elements.

```
class Point {
    public int x, y;
    public Point() {
        x = 0;
        y = 0;
    }
    public Point(int x, int y) {
        this.x = x;
        this.y = y;
    }
}
class SMT {
    static void Main() {
        Point[] points = new Point[100];
        for (int i = 0; i < 100; i++)
            points[i] = new Point(i, i*i);
    }
}
```

If Point is instead implemented as a struct, as in

```
struct Point {
    public int x, y;
    public Point(int x, int y) {
        this.x = x;
        this.y = y;
    }
}
```

then the test program instantiates just one object, for the array. The Point instances are allocated in-line within the array. Of course, this optimization can be mis-used. Using structs instead of classes can also make your programs fatter and slower, as the overhead of passing a struct instance by value is slower than passing an object instance by reference. There is no substitute for careful data structure and algorithm design.

If you pass a struct to a function, by default, the entire structure is copied onto the stack.

4.4 Enums

An enum type declaration defines a type name for a related group of symbolic constants (named integer constants). Enums are typically used when for “multiple choice” scenarios, in which a runtime decision is made from a number of options that are known at compile-time. Each of the named constants has a value, which by default starts at zero and increases by one for each succeeding member. You can give explicit values to any or all of the constants; any that you don’t specify get a value one more than the preceding constant. The default type of the constants is int; you can declare enum which use other integral types like – byte, sbyte, ushort, short, uint, long, ulong.

```
enum Weekday : short (Mon, Tue, Wed);
```

The other example

```

enum Color {
    Red,
    Blue,
    Green
}
class Shape {
    public void Fill(Color color) {
        switch(color) {
            case Color.Red:
                ...
                break;
            case Color.Blue:
                ...
                break;
            case Color.Green:
                ...
                break;
            default:
                break;
        }
    }
}

```

shows a Color enum and a method that uses this enum. The signature of the Fill method makes it clear that the shape can be filled with one of the given colors.

The use of enums is superior to the use of integer constants – as is common in languages without enums – because the use of enums makes the code more readable and self-documenting. The self-documenting nature of the code also makes it possible for the development tool to assist with code writing and other “designer” activities. For example, the use of Color rather than int for a parameter type enables smart code editors to suggest Color values.

4.5 Properties

In OO languages, the data members are normally private and access to them is through get and set (or accessor) methods. The drawback here is that one has to code the accessor methods for each data member and users have to remember to use them to access these data members.

C# has this idea of accessing data members through get and set code built into the language, in the form of **properties**. The difference between using get/set methods and properties is that to a user, using a property looks like they are getting direct access to the data, whereas in fact the compiler is mapping the call onto the get/set methods.

The success of rapid application development tools like Visual Basic can, to some extent, be attributed to the inclusion of properties as a first-class element. VB developers can think of a property as being field-like, and this allows them to focus on their own application logic rather than on the details of a component they happen to be using. On the face of it, this difference might not seem like a big deal, but modern component-oriented programs tend to be chockfull of property reads and writes. Languages with method-like usage of properties (e.g., o.SetValue(o.GetValue() + 1);) are clearly at a disadvantage compared to languages that feature field-like usage of properties (e.g., o.Value++;).

Properties are defined in C# using property declaration syntax. The first part of the syntax looks quite similar to a field declaration. The second part includes a get accessor and/or a set accessor. In the example below, the Button class defines a Caption property.

```

public class Button: Control {
    private string caption;

```

C# - CONSOLE APPLICATIONS

```
public string Caption {
    get {
        return caption;
    }
    set {
        caption = value;
        Repaint();
    }
}
```

Properties that can be both read and written, like the `Caption` property, include both `get` and `set` accessors. The `get` accessor is called when the property's value is read; the `set` accessor is called when the property's value is written. In a `set` accessor, the new value for the property is given in an implicit `value` parameter (the value represents the value passed in from the user).

Declaration of properties is relatively straightforward, but the true value of properties shows itself in their usage rather than in their declaration. The `Caption` property can be read and written in the same way that fields can be read and written:

```
Button b = new Button();
b.Caption = "ABC";      // set
string s = b.Caption;  // get
b.Caption += "DEF";    // get & set
```

You can omit either the `set` or `get` clause. You don't have to return the value of a variable in a `get` clause, but can use any code you like to calculate or obtain the value of the property. This means that properties don't have to be tied to a data member but can represent dynamic data. Properties can be inherited and you can use the `abstract` and `virtual` modifiers with them, so that derived classes can be required to implement their own versions of property methods. In addition, the `static` modifier can be used to create properties that belong to classes as opposed to individual objects.

4.6 Delegates

Let's go over this definition of a delegate very slowly.

4.6.1 Delegate

- is a reference type (abstract class extending `Object`)
- declaration consists of a name and a method signature
- instance encapsulates static or an instance method
- instances can hold and invoke a method or list of methods that match its signature
- method signature includes its return type
- method signature also allows the use of a `params` modifier in its parameter list
- are roughly similar to function pointers in C++; however, delegates are object-oriented, type-safe and secure
- There are basically two types of delegates. `Single Cast delegate` and `Multi Cast delegate`. A `single cast delegate` can call only one function. A `multi cast delegate` can call more than one function

The delegate object can call the referenced method, without having to know at compile time which method will be invoked.

Let us look at a declaration:

```
delegate int MyDelegate();
```

This declaration lets you create delegate instances that can hold and invoke methods that return int and have no parameters.

Let us follow this up with an example, where one delegate is mapped to both static and instance methods and returns specific information from each.

```
// Calling both static and instance methods from delegates
using System;
// delegate declaration
delegate int MyDelegate();
public class MyClass {
    public int InstanceMethod() {
        Console.WriteLine("A message from the instance method.");
        return 0;
    }
    static public int StaticMethod() {
        Console.WriteLine("A message from the static method.");
        return 0;
    }
}
public class MainClass {
    static public void Main() {
        MyClass p = new MyClass();
        // Map the delegate to the instance method:
        MyDelegate d = new MyDelegate(p.InstanceMethod);
        // Call the instance method:
        d();
        // Map to the static method:
        d = new MyDelegate(MyClass.StaticMethod);
        // Call the static method:
        d();
    }
}
```

Output from the program:

A message from the instance method.

A message from the static method.

4.6.2 Multicast Delegates:

If a delegate has a void return type, it is a multicast delegate that can hold and invoke multiple methods.

In the example below, we declare a simple delegate called SimpleDelegate, which can hold and then invoke MtdA and MtdB methods sequentially. The += method creates a new delegate by adding the right delegate operand to the left delegate operand.

```
using System;
delegate void SimpleDelegate();
class Test {
    static void Main() {
        new Test(); // prints "MtdA", "MtdB"
```

C# - CONSOLE APPLICATIONS

```
}
Test() {
    SimpleDelegate sd = null;
    sd += new SimpleDelegate(MtdA);
    sd += new SimpleDelegate(MtdB);
    sd();
}
void MtdA() {
    Console.WriteLine("MtdA");
}
void MtdB() {
    Console.WriteLine("MtdB");
}
}
```

A delegate can also be removed from another delegate using the -= operator:

```
Test() {
    SimpleDelegate sd = null;
    sd += new SimpleDelegate(MtdA);
    sd -= new SimpleDelegate(MtdA);
    // sd is now null
}
```

Delegates are invoked in the order they are added.

Please note that in the .NET runtime, C# compiles += and -= operations made on a delegate to the static Combine and Remove methods of the System.Delegate class. Delegates with a void return type alias System.MulticastDelegate.

Delegates are ideally suited for use as events - notifications from one component to "listeners" about changes in that component.

4.7 Events

- An event is a message sent by an object to signal the occurrence of an "action". The action could be caused by user interaction, such as a mouse click, or it could be triggered by some other program logic. The object that raises (triggers) the event is called the event sender. The object that captures the event and responds to it is called the event receiver.
- The problem in event communication is that the sender class does not know which object/method will receive (handle) the events it raises. What is needed is an intermediary (or pointer-like mechanism) between the source and the receiver. The communication channel between an event source and an event receiver is the delegate. Just think about delegates in the real world. Who are delegates? Delegates are people who represent a particular country in another country. In C#, delegates act as an intermediary between an event source and an event destination. Hence, a delegate acts as an event dispatcher for the class that raises the event by maintaining a list of registered event handlers for the event.
- Event handling is a process by which one object can notify other objects that an event has occurred. A delegate class used as an intermediary between an event source and event receiver is called an event handler.
- In the .NET Framework, a delegate is a class that can hold a reference to a method. Unlike other classes, a delegate class has a signature, and it can hold references only to methods that match its signature. A delegate is thus equivalent to a type-safe function pointer or a callback. A delegate declaration is sufficient to define a delegate class. The declaration

provides the signature of the delegate, and the implementation is provided by the Common Language Runtime.

- Events in C# follow the publish-subscribe design pattern in which a class publishes an event that it can "raise" and any number of classes can then subscribe to that event. Once the event is raised, the runtime takes care of notifying each subscriber that the event has occurred. The method called as a result of an event being raised is defined by a delegate.
- All event delegates are multicast, which means that they can hold references to more than one event handling method.

The following steps must be taken in order to create and use C# events:

1. Create or identify a delegate. If you are defining your own event, you must also ensure that there is a delegate to use with the event keyword. If the event is predefined, in the .NET Framework, for example, then consumers of the event need only know the name of the delegate.
2. Create a class that contains: An event created from the delegate. An event is declared like a field of delegate type, except that the keyword event precedes the event declaration, following the modifiers. Events usually are declared public, but any accessibility modifier is allowed.
3. Invoking an event: Once a class has declared an event, it can treat that event just like a field of the indicated delegate type. The field will either be null, if no client has hooked up a delegate to the event, or else it refers to a delegate that should be called when the event is invoked. Thus, invoking an event is generally done by first checking for null and then calling the event. Invoking an event can only be done from within the class that declared the event. The event keyword promotes encapsulation by ensuring that only the += and -= operations can be performed on the delegate. Note that in the example below, only the Event class can invoke the delegate (fire the event) or clear the delegate's invocation list.
4. Hooking up to an event / Use the event: From outside the class that declared it, an event looks like a field, but access to that field is very restricted. The only things that can be done are:
 - Compose a new delegate onto that field.
 - Remove a delegate from a (possibly composite) field.

This is done with the += and -= operators. To begin receiving event invocations, client code first creates a delegate of the event type that refers to the method that should be invoked from the event. Then, it composes that delegate onto any other delegates that the event might be connected to, using +=. When the client code is done receiving event invocations, it removes its delegate from the event by using operator -=.

The following problem should clarify this further -

Problem discussion:

Data: Amit is appearing for the C# Certification exam

Event: Amit gets a grade (A-C) - A is > 69%, B is 61-69%, C < 60%

Who are affected by this?: Teacher, Friend.

How are they affected?: Teacher is happy when the grade is good (A or B) and upset otherwise.

Amit's friend did not clear the certification examination and he has an opposite reaction to their teacher's.

C# - CONSOLE APPLICATIONS

Below is a simple program which illustrates Amit's teacher/friend reaction to his grades. Class Test is listening to all events of type grade. Every time a new grade is received, class Test triggers an event. Class Event sends a message to a class that is subscribed to the event. If no class is subscribed, the event is not handled by the program.

```
using System;
// Step 1
// The Delegate declaration which defines the signature of methods which can be
invoked
public delegate void GradeEvent(string s);

// class which makes the event
class Event {
    // Step 2
    // Note the use of the event keyword
    public event GradeEvent grade; //delegate grade is a member of Event

    // Step 3
    // Invoking the event
    public void TriggerEvent(string s) {
        if (grade != null) // if invocation list is not empty
            grade(s); // fire event
        else
            Console.WriteLine("Event is not registered");
    }
}

class Test {
    public static void CatchEvent(string s) {
        Console.WriteLine("Grade event " + s + " is caught");
        if(s.Equals("A") || s.Equals("B")) {
            Console.WriteLine("The Teacher is happy with " + s);
            Console.WriteLine("The Friend is upset with " + s);
        }
        else
            if( s.Equals("C")) {
                Console.WriteLine("The Teacher is upset with " + s);
                Console.WriteLine("The Friend is happy with " + s);
            }
            else
                Console.WriteLine("Some problem with the result...");
    }

    public static void Main() {
        // Use the event
        Event myEvent = new Event();
        myEvent.grade += new GradeEvent(CatchEvent); //register grade with CatchEvent
        myEvent.TriggerEvent("A");
        myEvent.TriggerEvent("B");
        myEvent.TriggerEvent("D");
        myEvent.grade -= new GradeEvent(CatchEvent); //quit registration
    }
}
```

.NET Framework Guidelines

Although the C# language allows events to use any delegate type, the .NET Frameworks has some stricter guidelines on the delegate types that should be used for events. If you intend for your component to be used with the .NET Frameworks, you probably will want to follow these guidelines.

The .NET Frameworks guidelines indicate that the delegate type used for an event should take two parameters, an "object source" parameter indicating the source of the event, and an "e" parameter that encapsulates any additional information (data) about the event. The type of the "e" parameter should derive from the EventArgs class. For events that do not use any additional information, the .NET Frameworks has already defined an appropriate delegate type: EventHandler. EventHandler which is a subclass of MulticastDelegate has a constructor and an Invoke method. When you create an EventHandler delegate, you identify the method that will response to the specified event. To associate the event with your event-handling method, add an instance of the delegate to the event. The event-handling method is called whenever the event occurs, unless you remove the delegate priorly.

4.8 Reflection

One very powerful feature of .NET is that it allows you to write code to access an application's metadata through a process known as reflection. Thus, reflection is the ability to discover type information at run time.

The System.Reflection namespace contains about 36 classes. Some of the important ones are: Assembly, Module, MethodInfo, FieldInfo, PropertyInfo, EventInfo.

In our first example, we will use the System.Type abstract class. This class provides methods for obtaining information about a type declaration, such as the constructors, methods, fields, properties, and events of a class, as well as the module and the assembly in which the class is deployed.

The program when executed, displays Int32 - the object Type. We use the GetType() method which returns a Type object that represents the type of an instance. The Name property gets the name of this member.

```
using System;
class Example1 {
    static void Main() {
        int i = 6;
        Type t = i.GetType();
        Console.WriteLine(t.Name); // output is Int32
    }
}
```

The System.Type class is the primary means by which to access metadata, and it acts as a gateway to the Reflection API.

In the next example, we create a Type object from a type name. The GetType(string) method gets the Type with the specified name, performing a case-sensitive search. This method searches in the calling object's assembly, then in the System assembly.

```
using System;
class Example2 {
    static void Main() {
        Type t = Type.GetType("System.Int32");
        Console.WriteLine(t.Name); // Output is Int32
    }
}
```

C# - CONSOLE APPLICATIONS

```
}
```

The System.Type class has about 47 properties, which help us in querying a Type regarding almost any of its attributes. The example below, uses some of these properties.

```
using System;
public class SomeClass {
}
class Query {
    public static void QueryType(string typeName) {
        try {
            Type type = Type.GetType(typeName);
            Console.WriteLine("Type name: {0}", type.FullName);
            Console.WriteLine("\tHasElementType = {0}", type.HasElementType);
            Console.WriteLine("\tIsAbstract = {0}", type.IsAbstract);
            Console.WriteLine("\tIsArray = {0}", type.IsArray);
            Console.WriteLine("\tIsByRef = {0}", type.IsByRef);
            Console.WriteLine("\tIsClass = {0}", type.IsClass);
            Console.WriteLine("\tIsCOMObject = {0}", type.IsCOMObject);
            Console.WriteLine("\tIsEnum = {0}", type.IsEnum);
            Console.WriteLine("\tIsImport = {0}", type.IsImport);
            Console.WriteLine("\tIsInterface = {0}", type.IsInterface);
            Console.WriteLine("\tIsLayoutSequential = {0}", type.IsLayoutSequential);
            Console.WriteLine("\tIsMarshalByRef = {0}", type.IsMarshalByRef);
            Console.WriteLine("\tIsNestedAssembly = {0}", type.IsNestedAssembly);
            Console.WriteLine("\tIsNestedFamANDAssem = {0}", type.IsNestedFamANDAssem);
            Console.WriteLine("\tIsNestedFamily = {0}", type.IsNestedFamily);
            Console.WriteLine("\tIsNestedFamORAssem = {0}", type.IsNestedFamORAssem);
            Console.WriteLine("\tIsNestedPrivate = {0}", type.IsNestedPrivate);
            Console.WriteLine("\tIsNestedPublic = {0}", type.IsNestedPublic);
            Console.WriteLine("\tIsNotPublic = {0}", type.IsNotPublic);
            Console.WriteLine("\tIsPointer = {0}", type.IsPointer);
            Console.WriteLine("\tIsPrimitive = {0}", type.IsPrimitive);
            Console.WriteLine("\tIsPublic = {0}", type.IsPublic);
            Console.WriteLine("\tIsSealed = {0}", type.IsSealed);
            Console.WriteLine("\tIsSerializable = {0}", type.IsSerializable);
            Console.WriteLine("\tIsServicedComponent = {0}", type.IsServicedComponent);
            Console.WriteLine("\tIsUnicodeClass = {0}", type.IsUnicodeClass);
            Console.WriteLine("\tIsValueType = {0}", type.IsValueType);
        } catch (System.NullReferenceException) {
            Console.WriteLine("{0} is not a valid type", typeName);
        }
    }
    static void Main() {
        QueryType("SomeClass");
    }
}
```

4.9 Assertions

Assertions often catch bugs introduced by faulty design/logic, incorrect assumptions, integration, and code maintenance.

Assertions are not supported in Java.

The System.Diagnostics namespace (assembly system.dll) provides classes that allow you to debug your application and to trace the execution of your code.

System.Diagnostics also provides classes that allow you to start system processes, read and write to event logs, and monitor system performance using performance counters.

The Debug class (subclass of Object) provides a set of methods and properties that help you debug your code.

To enable debugging in C#, add the /d:DEBUG flag to the compiler command line when you compile your code.

By using methods in the Debug class to print debugging information and check your logic with assertions, you can make your code more robust without impacting your shipping product's performance and code size.

The Assert() method checks for a condition, and displays a message if the condition is false.

The Debug.Assert Method (Boolean, String1, String2)

checks for a condition, and displays both the specified messages if the condition is false; where Boolean is a condition which, if false, causes the messages to be displayed, String1 is a message to display and String2 is a detailed message to display.

Typically, Assert is used to identify logic errors during program development.

The default behavior is to display a message box when the application is running in a user interface mode, and to output the message to the default trace output.

The Debug.Assert Method (Boolean)

checks for a condition, and outputs the callstack if the condition is false, where a condition which, if false, causes a message to be displayed.

Assert outputs the callstack with file and line numbers for each line in the callstack.

Program **ConfigFile.cs**

```
// csc /r:System.dll /d:DEBUG ConfigFile.cs
using System.Diagnostics;
class ConfigFile {
    bool isFileOpen;
    public void Open(string strFile) {
        // Pre-conditions
        Debug.Assert(!isFileOpen, "Config file already open.",
            "You can only call Open() once.");
        Debug.Assert(strFile.Length > 0);
        isFileOpen = true;
        // ...
    }
    public static void Main(string[] args) {
        ConfigFile file = new ConfigFile();
        file.Open("PuneCsharp.xml");
        file.Open("PuneCsharp.xml"); // Cause an assertion!
    }
}
```

4.10 MultiThreading – An Introduction

(An extract from the book 'Inside C#' by Tom Archer)

Multithreading allows an application to divide tasks such that they work independently of each other to make the most efficient use of the processor and the user's time.

A thread is a unit of processing, and multitasking is the simultaneous execution of multiple threads. Multitasking comes in two flavors: cooperative and preemptive. However, Microsoft

C# - CONSOLE APPLICATIONS

Windows NT and, later, Windows 95, Windows 98, and Windows 2000 support preemptive multitasking. With preemptive multitasking, the processor is responsible for giving each thread a certain amount of time in which to execute - a timeslice. The processor then switches among the different threads, giving each its timeslice, and the programmer doesn't have to worry about how and when to relinquish control so that other threads can run. .NET will only work on preemptive multitasking operating systems.

By the way, even with preemptive multitasking, if you're running on a single processor machine, you don't really have multiple threads executing at the same time. Because the processor is switching between processes at intervals that number in the milliseconds, it just "feels" that way. If you want to run true multiple threads concurrently, you'll need to develop and run your code on a machine with multiple processors.

Context Switching:

Context switching is integral to threading. The processor uses a hardware timer to determine when a timeslice has ended for a given thread. When the hardware timer signals the interrupt, the processor saves all registers for the current thread onto the stack. Then the processor moves those same registers from the stack into a data structure called a CONTEXT structure. When the processor wants to switch back to a previously executing thread, it reverses this procedure and restores the registers from the CONTEXT structure associated with the thread. This entire procedure is called context switching.

A Multithreaded Application in C#:

```
// SimpleThreadApp.cs
using System;
using System.Threading;
class SimpleThreadApp {
    public static void WorkerThreadMethod() {
        Console.WriteLine("Worker thread started");
    }
    public static void Main() {
        ThreadStart worker = new ThreadStart(WorkerThreadMethod);
        Console.WriteLine("Main - Creating worker thread");
        Thread t = new Thread(worker);
        t.Start();
        Console.WriteLine("Main - Have requested the start of worker thread");
    }
}
```

The output of the program is:

Main - Creating worker thread

Main - Have requested the start of worker thread

Worker thread started

If you compile and execute this application, you'll see that the message from the Main method prints before the message from the worker thread, proving that the worker thread is indeed working asynchronously. Let's dissect what's going on here.

The System.Threading namespace contains the different classes necessary for threading in the .NET environment.

Now take a look at the first line of the Main method:

```
ThreadStart WorkerThreadMethod = new ThreadStart(WorkerThreadMethod);
```

Any time you see the following form, you can be sure that x is a delegate or a definition of a method signature:

```
x varName = new x (methodName);
```

Delegates, basically serve the same purpose as function pointers in C++. However, delegates are type-safe, secure managed objects. This means that the runtime guarantees that a delegate points to a valid method, which further means that you get all the benefits of function pointers without any of the associated dangers, such as an invalid address or a delegate corrupting the memory of other objects.

So, we know that ThreadStart is a delegate. But it's not just any delegate. Specifically, it's the delegate that must be used when creating a new thread, and it's used to specify the method that you want called as your thread method. From there, I instantiate a Thread object where the constructor takes as its only argument a ThreadStart delegate, like:

```
Thread t = new Thread(worker);
```

After that, I call my Thread object's Start method, which results in a call to the WorkerThreadMethod. That's it!

4.11 Assignment

Use a generic, higher level **IAccount** interface and an abstract class **BankAccount** to collect all features common to all bank accounts. The BankAccount class has account number and balance as instance variables. It has the methods for deposit and withdrawal. The **SavingsAccount** and **BonusSaverAccount** are both savings accounts through which you can make deposits and withdrawals. However, the BonusSaverAccount is designed with incentives to encourage faster savings accumulation. Both types of accounts earn interest, but the BonusSaverAccount earns more. Furthermore, there is a financial penalty every time a withdrawal is made from a BonusSaverAccount.

The SavingsAccount and CurrentAccount classes are derived from BankAccount and BonusSaverAccount is derived from SavingsAccount.

The CurrentAccount has an overridden withdrawal method that makes use of overdraft protection.

```
// Assignment.cs
namespace BankSystem {
using System;
public interface IAccount {
    // Two abstract methods:
    void deposit(double amount);
    bool withdrawal(double amount);
}
public abstract class BankAccount : IAccount {
    // Fields:
    private int account;
    private double balance;
    // Constructor:
    public BankAccount(int accountNum, double initialBal) {
        account = accountNum;
        balance = initialBal;
    }
    // Property implementation:
    public int Account {
```

C# - CONSOLE APPLICATIONS

```
        get {
            return account;
        }
        set {
            account = value;
        }
    }
    public double Balance {
        get {
            return balance;
        }
        set {
            balance = value;
        }
    }
    public void deposit(double amount) {
        balance += amount;
        Console.WriteLine("Deposit into account " + account);
        Console.WriteLine("Amount: " + amount);
        Console.WriteLine("New Balance: " + balance);
    }
    public virtual bool withdrawal(double amount) {
        bool result = false;
        Console.WriteLine("Withdrawal from Account " + account);
        Console.WriteLine("Amount: " + amount);
        if (amount > balance)
            Console.WriteLine("Insufficient funds");
        else {
            balance -= amount;
            Console.WriteLine("New Balance: " + balance);
            result = true;
        }
        return result;
    }
}
class SavingsAccount : BankAccount {
    protected double rate;
    public SavingsAccount (int accountNum, double initialBal,
                           double interestRate) : base(accountNum, initialBal) {
        rate = interestRate;
    }
    public virtual void addInterest() {
        // using the Property names: Account and Balance
        Balance += Balance * rate;
        Console.WriteLine("Interest added to account: " + Account);
        Console.WriteLine("New balance: " + Balance);
    }
}
class BonusSaverAccount : SavingsAccount {
    private const int PENALTY = 25;
    private const double BONUSRATE = 0.02;
    public BonusSaverAccount (int accountNum, double initialBal,
                              double interestRate)
        : base(accountNum, initialBal, interestRate){
    }
    public override bool withdrawal(double amount) {
        Console.WriteLine("Penalty incurred: " + PENALTY);
    }
}
```

```

        return base.withdrawal(amount+PENALTY);
    }
    public override void addInterest() {
        Balance += Balance * (rate + BONUSRATE);
        Console.WriteLine("Interest added to account: " + Account);
        Console.WriteLine("New balance: " + Balance);
    }
}
class CurrentAccount : BankAccount {
    private SavingsAccount overdraft;
    public CurrentAccount(int accountNum, double initialBal,
        SavingsAccount protection) : base(accountNum, initialBal){
        overdraft = protection;
    }
    public override bool withdrawal(double amount) {
        bool result = false;
        if (!base.withdrawal(amount)) {
            Console.WriteLine("Using overdraft...");
            if (!overdraft.withdrawal(amount - Balance))
                Console.WriteLine("Overdraft source insufficient...");
            else {
                Balance = 0;
                Console.WriteLine("New Balance on account " + Account + ": " + Balance);
                result = true;
            }
        }
        return result;
    }
}
class Assignment {
    public static void Main(String[] args) {
        SavingsAccount savings =
            new SavingsAccount(101, 10000.00, 0.04);
        BonusSaverAccount bigSavings =
            new BonusSaverAccount(201, 10000.00, 0.02);
        CurrentAccount checking =
            new CurrentAccount(301, 500.00, savings);

        savings.deposit(1000.00);
        bigSavings.deposit(1000.00);
        savings.withdrawal(500.00);
        bigSavings.withdrawal(500.00);
        checking.withdrawal(501.00);
    }
}
}

```

4.12 Summary of Key Concepts

- An abstract class indicates that the class is incomplete and intended only to be a base class of other classes. An abstract class cannot be instantiated and cannot be sealed.
- The sealed modifier (similar to final in Java) is used to prevent derivation from a class. The sealed modifier cannot be used on methods.
- The direct base class of a class type must be at least as accessible as the class type itself.
- Internal members are accessible only within files in the same assembly.

C# - CONSOLE APPLICATIONS

- Constructors and destructors must have the same name as the immediately enclosing class. All other members must have names that differ from the name of the immediately enclosing class.
- If you attempt to prefix a constructor with a type, the compiler will emit an error stating that you cannot define members with the same names as the enclosing type.
- A constructor initializer of the form *base(.)* enables the current class's base class constructor—that is, the specific constructor implied by the form of the constructor called—to be called.
- An initializer taking the form *this(.)* enables the current class to call another constructor defined within itself. This is useful when you have overloaded multiple constructors and want to make sure that a default constructor is always called.
- Constructors are not inherited.
- It's advisable to write a default constructor for every class you write.
- Constructors are usually public, but can also be private or protected.
- Static constructors implement the actions required to initialize a class i.e. the constructor is called when the class is loaded.
- Static constructors are not inherited.
- Static constructors are invoked automatically, and cannot be invoked explicitly. The exact timing and ordering of static constructor execution is not defined, though several guarantees are provided:
 1. The static constructor for a class is executed before any instance of the class is created.
 2. The static constructor for a class is executed before any static member of the class is referenced.
 3. The static constructor for a class is executed before the static constructor of any of its derived classes are executed.
 4. The static constructor for a class never executes more than once.
 5. The static constructor cannot have parameters.
 6. There's no such thing as a static destructor.
- Destructors are invoked automatically, and cannot be invoked explicitly. The name of a class destructor is the class name preceded by a tilde (~). They are always public and have no return value. They do not take any arguments, so there can only ever be one for a class.
- A derived class can *hide* inherited members by declaring new members with the same name or signature. Note however that hiding an inherited member does not remove the member—it merely makes the member inaccessible in the derived class.
- The **base** keyword is in many ways the equivalent of Java's `super` keyword.
- Use the **new** modifier to explicitly hide a member inherited from a base class.
- A derived class can be used in place of its base class.
- The **as** keyword can be used instead of a cast. The advantage over a cast is that if the cast is invalid, you don't have to worry about an exception being thrown. What will happen instead is that the result will be *null*.
- When a *class-member-declaration* does not include any access modifiers, the declaration defaults to private declared accessibility.

- The access modifiers are associated with members or types (classes etc.) and are not allowed on namespaces.
- A **virtual method** is one where the decision on exactly which method to call is delayed until run-time, allowing the dynamic type of the reference to be used. You declare a method as virtual by using the `virtual` modifier in the base class.
- When you override a virtual method in a derived class, you can use the **override** keyword to signal that you are overriding a virtual method.
- Remember that the `virtual` keyword must be used on the base class's method, and the `override` keyword is used on the derived class's implementation of the method.
- The **interface** keyword declares a reference type that has abstract members. Interfaces can contain methods, properties, indexers, and events as members. They can't contain constants, fields (private data members), constructors and destructors or any type of static member. **All the members of an interface are public by definition**, and the compiler will give you an error if you try to specify any other modifiers on interface members. The `static` and `public` modifiers are not permitted on interface methods.
- Structs are value types rather than reference types, and inheritance is not supported for structs.
- An enum type declaration defines a type name for a related group of symbolic constants (named integer constants). Each of the named constants has a value, which by default starts at zero and increases by one for each succeeding member. You can give explicit values to any or all of the constants; any that you don't specify get a value one more than the preceding constant. The default type of the constants is `int`.
- The difference between using get/set methods and properties is that to a user, using a property looks like they are getting direct access to the data, whereas in fact the compiler is mapping the call onto the get/set methods.
- In a property set accessor, the new value for the property is given in an implicit value parameter (the value represents the value passed in from the user).
- You can omit either the set or get clause in case of a property.

5. Using .NET Base Classes

Microsoft has supplied a large number of base classes as part of the .NET framework. The base classes are accessible from C#, VB, C++ or any other .NET compliant language.

5.1 The WinCV Tool

WinCV is a class viewer tool, which can be used to examine the classes available in shared assemblies – including all the base classes. For each class, it lists the methods, properties, events and fields using a C# like syntax.

At the command prompt type **wincv**. You then type in a search string that is contained in the class you are looking for in the **Searching For** box. WinCv will then display a list of classes that contain the string in question in their names. Scan through the names to find the one that looks most suitable. The definition of the selected class is then displayed in the right hand pane. The left hand pane also indicates the namespace the class is contained in – you'll need this in order to be able to use that class in your C# code. The right hand pane of WinCV tells us which assembly the class is defined in. This information is useful to indicate if we need to link in any assemblies when we compile, in order to have access to that class.

5.2 StringBuilder class

This class is used to represent *mutable* strings. It is convenient for situations in which it is desirable to modify a string, perhaps by removing, replacing, or inserting characters, without creating a new string subsequent to each modification. It is used in conjunction with the [String](#) class to carry out modifications upon strings. The methods contained within this class do not return a new StringBuilder object unless specified otherwise. This class is defined in the namespace System.Text. It starts at a predefined size (16 characters by default) and grows dynamically as more string data is added.

```
using System;
using System.Text;
public class SBTest {
    public string SqrtIntFaster(int i) {
        StringBuilder buf = new StringBuilder(50);
        buf.Append("sqrt(").Append(i).Append(')');
        buf.Append(" = ").Append(Math.Sqrt(i));
        return buf.ToString();
    }
    static void Main() {
        SBTest sb = new SBTest();
        Console.WriteLine(sb.SqrtIntFaster(25));
    }
}
```

In the above program **SBTest.cs**, the StringBuilder constructor has the suggested starting size of 50. This size can increase as more characters are added. The Append() method appends a typed object to the end of the current StringBuilder. The ToString() method is overloaded and it converts a StringBuilder to a [String](#). We have also used Sqrt() method of the Math class.

5.3 File and Folder operations

The .NET base classes include a number of classes that provide a rich set of functionality to access the file system, to read and write to files, to move or copy files around, or to explore folders to check what files are there. These classes are contained in the System. IO namespace.

5.3.1 Finding out information about a File

The program `IBF.cs` will demonstrate how to get information about a file, using some of the properties of the `File` class.

```
using System;
using System.IO;
public class IBF {
    public static void Main(String[] args) {
        File f = new File(@"C:\WINDOWS\BOOTLOG.TXT");
        Console.WriteLine("Connected to file..." + f.Name);
        Console.WriteLine("In Folder....." + f.Directory);
        Console.WriteLine("Full Path....." + f.FullName);
        Console.WriteLine("Is Directory....." + f.IsDirectory.ToString());
        Console.WriteLine("Is File....." + f.IsFile.ToString());
        Console.WriteLine("Last Write Time...." + f.LastWriteTime.ToString());
        Console.WriteLine("Size in bytes....." + f.Length);
    }
}
```

In general you can use a `File` object to connect to either a file or a folder, although if you connect to a folder then attempting to access those properties that don't make sense for a folder (such as `Length` or `LastWriteTime`) will raise an exception.

5.3.2 Listing Files in a Folder

To explore the contents of a folder, we need another base class – the `Directory` class, also in the System. IO namespace. Note that the .NET base classes generally refer to folders as *directories* in class and method names.

The example `FIF.cs` connects to the folder `H:\pune-csharp` and separately lists the files and folders in it.

```
using System;
using System.IO;
public class FIF {
    public static void Main(String[] args) {
        Directory dl = new Directory(@"H:\pune-csharp");
        Console.WriteLine("Connected to folder..." + dl.Name);
        Console.WriteLine("Full Path....." + dl.FullName);
        Console.WriteLine("Is Directory....." + dl.IsDirectory.ToString());
        Console.WriteLine("Is File....." + dl.IsFile.ToString());
        Console.WriteLine("Files contained in this folder:");
        File[] childfiles = dl.GetFiles();
        foreach (File childfile in childfiles)
            Console.WriteLine(childfile.Name);
        Console.WriteLine("Subfolders contained in this folder:");
        Directory[] childfolders = dl.GetDirectories();
        foreach (Directory childfolder in childfolders)
            Console.WriteLine(childfolder.Name);
    }
}
```

C# - CONSOLE APPLICATIONS

5.3.3 Copying and Deleting Files

We start off by binding to the H:\pune-csharp folder, and we create both a new empty file and a new empty subfolder there, as in example **CFF.cs**:

```
using System;
using System.IO;
public class CFF {
    public static void Main(String[] args) {
        Directory dl = new Directory(@"H:\pune-csharp");
        dl.CreateSubdirectory("Talim");
        dl.CreateFile("Satish");
    }
}
```

Next, we bind to one of the files in the H:\pune-csharp folder, rename it and copy it, as in example **RC.cs**:

```
using System;
using System.IO;
public class RC {
    public static void Main(String[] args) {
        File fl = new File(@"H:\pune-csharp\Satish");
        fl.CopyTo(@"H:\pune-csharp\Talim\NewSatish");
    }
}
```

Next we delete the file NewSatish and the folder Talim, as in the example **DFD.cs**:

```
using System;
using System.IO;
public class DFF {
    public static void Main(String[] args) {
        File fl = new File(@"H:\pune-csharp\Satish");
        fl.Delete();
        Directory dl = new Directory(@"H:\pune-csharp\Talim");
        dl.Delete(true);
    }
}
```

Here Delete(true) is used to remove directories, subdirectories, and contents; otherwise **false**.

5.3.4 Reading Text Files

The available classes are all derived from the class System.IO.Stream, which can represent any stream. To read text files we use the class StreamReader. The example **RTF.cs** demonstrates this.

```
using System;
using System.IO;
public class RTF {
    public static void Main(String[] args) {
        File fl = new File(@"H:\CSHARPTEMP\Hello.cs");
        StreamReader sr = fl.OpenText();
        // continue reading until end of file
        string sLine;
        while ((sLine = sr.ReadLine()) != null)
            Console.WriteLine(sLine);
        sr.Close();
    }
}
```



```
}
```

5.3.5 Writing Text Files

For writing text files we use the StreamWriter class. The example `WTF.cs` explains this:

```
using System;
using System.IO;
public class WTF {
    public static void Main(String[] args) {
        StreamWriter sw = new StreamWriter(@"H:\CSHARPTEMP\TEMP.cs", false);
        sw.WriteLine("How do you find the C# Workshop?");
        sw.WriteLine("We now write some numbers and bool...");
        sw.WriteLine(6);
        sw.WriteLine(65.34);
        sw.WriteLine(true);
        sw.Close();
    }
}
```

The StreamWriter constructor takes two parameters: the full name of the file and a boolean that indicates whether data should be appended to the file. If this is false then the contents of the file will be overwritten by the StreamWriter. In either case, the file will be opened if it already exists or created if it does not.

5.3.6 Reading Binary Files

Here we use either the Stream or FileStream class. The program `RBFS.cs` demonstrates how to use the Stream class to read data. It opens a file and reads it, a byte at a time, each time displaying the numeric value of the byte read.

```
using System;
using System.IO;
public class RBFS {
    public static void Main(String[] args) {
        File f1 = new File(@"H:\CSHARPTEMP\Hello.cs");
        Stream s = f1.OpenRead();
        int iNext;
        while ((iNext = s.ReadByte()) != -1)
            Console.WriteLine(iNext.ToString());
        s.Close();
    }
}
```

5.3.7 Writing Binary Files

The program `WBFFS.cs` writes out a short text file that contains the letters FGHIJK followed by a carriage return-line feed combination.

```
using System;
using System.IO;
public class WBFFS {
    public static void Main(String[] args) {
        byte[] bytes = {70, 71, 72, 73, 74, 75, 13, 10};
        FileStream fs = new FileStream(@"H:\CSHARPTEMP\WBFFS.txt",
                                     FileMode.OpenOrCreate, FileAccess.Write);
        foreach (byte bNext in bytes)
            fs.WriteByte(bNext);
        fs.Close();
    }
}
```

C# - CONSOLE APPLICATIONS

The constructor we use takes three parameters: the full pathname of the file, the mode we are using to open it and the access required. The mode and access are enumerated values respectively taken from two further classes in the System.IO namespace: FileMode and FileAccess. The possible values for mode is Append, Create, CreateNew, Open, OpenOrCreate and Truncate. For the access, they are Read, ReadWrite and Write.

5.3.8 Reading/Writing to log files

The abstract base class Stream supports reading and writing bytes. All classes that represent streams inherit from the Stream class. The Stream class and its derived classes provide a generic view of data sources and repositories, isolating the programmer from the specific details of the operating system and underlying devices.

Streams involve these fundamental operations:

- Streams can be read from. Reading is the transfer of data from a stream into a data structure, such as an array of bytes.
- Streams can be written to. Writing is the transfer of data from a data structure into a stream.
- Streams can support seeking. Seeking is the querying and modifying of the current position within a stream.

Depending on the underlying data source or repository, streams might support only some of these capabilities.

I/O Classes Derived from System.Object - File provides static methods for the creation, copying, deletion, moving, and opening of files, and aids in the creation of FileStream objects. File are sealed classes. You can create new instances of these classes, but they can have no derived classes.

System.IO.TextReader and Its Derived Classes - TextReader is the abstract base class for StreamReader objects. While the implementations of the abstract Stream class are designed for byte input and output, the implementations of TextReader are designed for Unicode character output. StreamReader reads characters from Streams, using Encoding to convert characters to and from bytes. StreamReader has a constructor that attempts to ascertain what the correct Encoding for a given Stream is, based on the presence of an Encoding-specific preamble, such as a byte order mark.

System.IO.TextWriter and Its Derived Classes - TextWriter is the abstract base class for StreamWriter objects. While the implementations of the abstract Stream class are designed for byte input and output, the implementations of TextWriter are designed for Unicode character input. StreamWriter writes characters to Streams, using Encoding to convert characters to bytes.

Namespace: System.IO and Assembly: Mscorlib (in Mscorlib.dll)

The following code example opens the log.txt file for input, or creates a file if it does not already exist, and appends information to the end of the file. The contents of the file are then written to standard output for display.

The static AppendText() method of File class creates a StreamWriter that appends text to a file on the specified path, or creates the file if it does not already exist. The Write() method of StreamWriter is overloaded, overridden and here writes a string to the stream. The WriteLine() method inherited from TextWriter is overloaded and writes some data as specified by the overloaded parameters, followed by a line terminator. The Flush() method is overridden and clears all buffers for the current writer and causes any buffered data to be written to the underlying stream. The Close() method is overridden and closes the current StreamWriter and the underlying stream.

The static `OpenText()` method of `File` class creates a `StreamReader` that reads from an existing text file having the specified path. The `ReadLine()` method reads a line of characters from the current stream and returns the data as a string. The return value is the next line from the input stream, or a null reference if the end of the input stream is reached. The `Close()` method of `StreamReader` class closes the `StreamReader` and releases any system resources associated with the reader.

The `DateTime` structure represents an instant in time, typically expressed as a date and time of day. The `DateTime` value type represents dates and times with values ranging from 12:00:00 AM, 1/1/0001 CE (Common Era) to 11:59:59 PM, 12/31/9999 CE. Time values are measured in 100-nanosecond units called "ticks", and a particular date is the number of ticks since 12:00 AM January 1, 1 CE in the `GregorianCalendar` calendar. For example, a ticks value of 3124137600000000L represents the date, Friday, January 01, 0100 12:00:00 AM. A `DateTime` value is always expressed in the context of an explicit or default calendar. The `DateTime` and `TimeSpan` value types differ in that a `DateTime` represents an instant in time whereas a `TimeSpan` represents a time interval. This means, for example, that you can subtract one instance of `DateTime` from another to obtain the time interval between them. Or you could add a positive `TimeSpan` to the current `DateTime` to calculate a future date. Time values can be added to, or subtracted from, an instance of `DateTime`. Time values can be negative or positive, and expressed in units such as ticks, seconds, or instances of `TimeSpan`. Methods and properties in this value type take into account details such as leap years and the number of days in a month.

Descriptions of time values in this type are often expressed using the coordinated universal time (UTC) standard, which was previously known as Greenwich Mean Time (GMT). Calculations and comparisons of `DateTime` instances are only meaningful when the instances are created in the same time zone. For that reason, it is assumed that the developer has some external mechanism, such as an explicit variable or policy, to know in which time zone a `DateTime` instance was created. Methods and properties in this class always use the local time zone when making calculations or comparisons. A calculation on an instance of `DateTime`, such as `Add` or `Subtract`, does not modify the value of the instance. Instead, the calculation returns a new instance of `DateTime` whose value is the result of the calculation. The `DateTime.Now` property gets a `DateTime` that is the current local time on this computer. The `DateTime.ToLongTimeString()` method converts the time denoted by this instance to its equivalent long time `String` representation. The return value is a `String` containing the name of the day of the week, the name of the month, the numeric day of the hours, minutes, and seconds equivalent to the time value of this instance.

```
using System;
using System.IO;
class LogFileCreate {
    public static void Main(String[] args) {
        StreamWriter w = File.AppendText("log.txt");
        Log ("Test1", w);
        Log ("Test2", w);
        // Close the writer and underlying file.
        w.Close();
        // Open and read the file.
        StreamReader r = File.OpenText("log.txt");
        DumpLog (r);
    }

    public static void Log (String logMessage, TextWriter w) {
        w.Write("\r\nLog Entry : ");
        w.WriteLine("{0} {1}", DateTime.Now.ToLongTimeString(),
```

C# - CONSOLE APPLICATIONS

```
DateTime.Now.ToLongDateString());
w.WriteLine("  :");
w.WriteLine("  :{0}", logMessage);
w.WriteLine("-----");
// Update the underlying file.
w.Flush();
}

public static void DumpLog (StreamReader r) {
    // While not at the end of the file, read and write lines.
    String line;
    while ((line=r.ReadLine())!=null) {
        Console.WriteLine(line);
    }
    r.Close();
}
}
```

5.4 Networking

High level access is performed using a set of types that implement a generic request/response architecture that is extensible to support new protocols. The implementation of this architecture in the BCL also includes HTTP-specific extensions to make interacting with web servers easy.

Should the application require lower-level access to the network, types exist to support TCP and UDP. Finally, in situations where direct transport-level access is required, there are types that provide raw socket access.

5.4.1 HTTP

The HTTP protocol accounts for a large share of all traffic on the Internet; and the .NET frameworks provide robust support for the HTTP protocol with the **HttpWebRequest** and **HttpWebResponse** classes. These classes are the **WebRequest** and **WebResponse** derived classes returned whenever a URI beginning with "http" or "https" is presented to the **Create** method on the **WebRequestFactory**. In most cases, the **WebRequest** and **WebResponse** classes will provide all that is necessary to make the request, but when access to HTTP-specific features is required, the request or response can be typecast to **HttpWebRequest** or **HttpWebResponse**.

The **HttpWebRequest** and **HttpWebResponse** classes encapsulate a standard HTTP request and response transaction, and provide access to common HTTP headers through properties. These classes also support most of the HTTP 1.1 protocol features, including pipelining, chunking, authentication, pre-authentication, encryption, proxy support, server certificate validation, connection management, and HTTP extensions. Custom headers and headers not provided through properties can be accessed by storing them in the **Headers** property.

The following sample shows how to access HTTP specific properties, in this case turning off the HTTP Keep-alive behavior and getting the protocol version number from the Web server:

```
HttpWebRequest HttpWReq =
(HttpWebRequest)WebRequestFactory.Create("http://www.pune-csharp.com");
// Turn off connection keep-alives
HttpWReq.KeepAlive = false;

HttpWebResponse HttpWResp = (HttpWebResponse)HttpWReq.GetResponse();

// Look at the HTTP protocol version number returned by the server
String ver = HttpWResp.Version.ToString();
```

HttpWebRequest is the default class used by **WebRequestFactory** and does not need to be registered before passing an HTTP Uniform Resource Identifier (URI) to the **WebRequestFactory.Create** method.

Your application can automatically follow HTTP redirects by setting the **AllowAutoRedirect** property **true**. When the request is redirected, the **ResponseURI** property of the **HttpWebResponse** will contain the actual Web resource that responded to the request. When **AllowAutoRedirect** is **false**, your application must be prepared to handle redirects as an HTTP protocol error.

Applications receive HTTP protocol errors by catching a **WebException** with the **Status** set to **WebStatus.ProtocolError**. The **Response** property contains the **WebResponse** sent by the server and it can be examined to find the actual HTTP error encountered.

5.4.2 Generic Request/Response Architecture

This is based on Uniform Resource Indicator (URI) and stream I/O, follows the factory design pattern, and makes good use of abstract types and interfaces.

A uniform resource locator is a compact representation of a resource available to your application via the Internet. The **URI** class defines the properties and methods for handling URIs, including parsing, comparing, and combining.

The **URI** class stores only absolute URIs, relative URIs must be expanded with respect to a base URI so that they are absolute.

The **URI** is stored as a canonical URI in "escaped" format, with all characters with an ASCII value greater than 127 replaced with a hexadecimal representation. To put the URI in canonical form, the URI constructor:

- Converts the URI scheme to lower case.
- Converts the host name to lower case.
- Removes default and empty port numbers.
- Simplifies the URI by removing superfluous segments such as "/" and "/test" segments.

The **URI** class can be transformed from an escaped URI reference to a readable **URI** reference with the **ToStri ng** method.

The following example creates an instance of the **URI** class (derived from **Obj ect**), which can further be used to create a **WebRequest**:

```
URI siteURI = new URI("http://www.pune-csharp.com/");
```

The **WebRequestFactory** class (derived from **Obj ect**) is a static class that returns an instance of an object derived from **WebRequest**. The specific class of object returned is based on the URI scheme passed to the **Create** method.

The following example creates a **WebRequest** instance for an HTTP request. Since the URI indicates an HTTP request, the actual instance returned is an instance of **HttpWebRequest**

```
WebRequest wr = WebRequestFactory.Create(siteURI);
```

The **WebRequest** is an abstract class derived from **Obj ect**. Applications should never create **WebRequest** objects directly. The **GetResponse** method in this class, when overridden in a derived class, returns the response to an Internet request.

C# - CONSOLE APPLICATIONS

The **WebResponse** class is an abstract base class (derived from **Object**) from which protocol-specific classes are derived. The **WebResponse** class can be used to access any resource on the network that is addressable with a URI. Client applications should never create **WebResponse** objects directly. The **GetResponseStream** method in this class, when overridden in a derived class, returns the **Stream** object used for reading data from the resource referenced in the **WebRequest** object.

The **Stream** class provides a way to write and read bytes to and from a backing store. This class is abstract. The **StreamReader** class implements a **TextReader** (represents a reader that can read a sequential stream of characters. This class is abstract) that reads characters from a byte stream in a particular encoding. The character encoding is set by **Encoding** class and the default buffer size is used. The **ReadToEnd** method of the **StreamReader** class reads the stream from the current position to the end of the stream. The **Close** method closes the **StreamReader** and releases any system resources associated with the reader.

The example **Snarf.cs** below uses the **WebRequest** and **WebResponse** classes to retrieve the contents of a URI and display them to the console.

```
// Snarf.cs
// Compile with /r:System.Net.dll
// Run Snarf.exe <http-url> to retrieve a web page
using System;
using System.IO;
using System.Net;
using System.Text;
class Snarf {
    public static void Main(string[] args) {
        URI siteURI = new URI(args[0]);
        WebRequest req = WebRequestFactory.Create(siteURI);
        WebResponse res = req.GetResponse();
        Stream s = res.GetResponseStream();
        StreamReader sr = new StreamReader(s, Encoding.ASCII);
        string doc = sr.ReadToEnd();
        Console.WriteLine(doc);
        sr.Close();
    }
}
```


6. Miscellaneous

6.1 Comparison of C# and Java

6.1.1 Common features are:

- Automatic garbage collection
- Reflection for type information discovery
- Source code is compiled to an intermediate bytecode
- Just-in-Time (JIT) compilation compiles bytecode into native code
- Everything must be in a class – no global functions or data
- No multiple inheritance, although you can implement multiple interfaces
- All classes derive from Object
- Security for restricting access to resources
- Exceptions for error handling. There is no throws clause in C#, so effectively, all exceptions are unchecked. You are not forced to handle any exceptions. This is an unfortunate decision because the throws clause makes it obvious which exceptions can be thrown by a method and are part of the method's contract. Otherwise, you are forced to read the called method's source code to know which exceptions can be thrown
- Packages / namespaces for preventing type collision
- Code comments as documentation
- Arrays are bound checked
- GUI, networking and threading support
- No uninitialised variables
- No pointers
- No header files
- Most of the keywords in Java have their C# counterpart. Some keywords are identical, for example, new, bool, this... Many keywords in Java such as super, import, package have different names in C# (base, using, namespace)
- The System.Object class in C# has exactly the same methods as the java.lang.Object class in Java except they are spelled differently. The clone method in Java is called MemberwiseClone in C#, Java equals is Equals in C#, finalize is Finalize, getClass is GetType, hashCode is GetHashCode and toString is ToString
- C# specifies access modifiers inline as part of the member definition just like Java does. The modifiers public and private have the exact same meanings as in Java. However, protected access in Java is called protected internal in C#, and package access in Java is called internal in C#. C#'s protected modifier gives access to any subclass, even if it's not in the same program. Another difference is that package access is the default for Java while private is the default for C#

6.1.2 Differences**6.1.3 C# improvements over Java**

- C# has a simplified syntax for things such as iteration, events, and treating primitive types like objects, which reduces the amount of code you need to write.
- Reflection, Metadata and Custom Attributes Java and C# compilers both emit metadata with the class bytecodes to support reflection. Reflection provides the ability to obtain type information dynamically and makes it possible for the run-time system to automatically provide implementations for run-time type identification, dynamic method invocation, serialization, marshaling, and scripting support. Microsoft has extended the notion of metadata with Custom Attributes, which let you markup a class, method, method parameter, and just about anything else, with extra information that can be accessed at run-time. When compiled, the attributes are combined with the EXE/DLL itself, so it is not possible for them to be out of sync with the code. Attributes eliminate the need to maintain separate IDL files and type libraries.
- Versioning – This feature is much needed and Java developers are familiar with the problems of deprecated APIs and incompatible versions of serialized objects. .NET promises to fix these problems by letting you specify version dependencies between components and by supporting side-by-side execution of multiple versions of a component.
- Assertions – These are not supported in Java and are used to catch bugs introduced by faulty design / logic, incorrect assumptions, integration and code maintenance.
- ref and out parameters –

6.2 Web Service**6.2.1 What is a Web Service?**

Today, users are confined to doing what a particular page has been structured to do, and viewing data with whatever user interface was written on the server for that page. If say, a web page was designed to show a list of students ordered by name, but you from your browser wanted to see them ordered by marks then you were stuck - unless you had access to the web server to rewrite the pages served up.

Web Services are a way of overcoming that limitation and allowing software to be written and run on the client machine, which can use the data provided by the server in whatever way it wishes - provided of course that appropriate permissions have been set up. The idea is this: instead of supplying information via HTML, the page makes available a series of function calls. These function calls might look up information in a database or they might be used to supply information to the server. The point is that these functions work exactly the same as method calls in any .NET component - they take parameters and may return a value, except that they are callable over the internet. The data concerning which function is to be called, the values of any parameters, and any return value of the function are transmitted across the net via standard HTTP-based protocols.

6.2.2 Programming Web Services using ASP.NET and C#

You do not need to know anything about the underlying protocols in a web service, in order to write the web services themselves or the software on the client machine that calls them. ASP.NET takes care of converting data to and from the protocols for you on both the client and server side.

C# - CONSOLE APPLICATIONS

.NET Web Services expand on the concept of distributed processing to build components whose methods can be invoked across the internet. These components can be built in any .NET language, and they communicate using open protocols that are platform-independent. The application developer can concentrate on adding value to the existing web services, rather than duplicating the same service for hi/her own application. A single application might draw on and stitch together the services of hundreds of small web services distributed all over the world.

The plumbing necessary to discover and invoke web services is integrated into the .NET Framework and provided by classes within the System.Web.Services.WebService namespace. Creating a web service requires no special programming on your part; you need only write the implementing code, add the [WebMethod] attribute and let the server do the rest. The WebMethod attribute informs the compiler that this method is intended to be callable over the web, not just internally within the program.

Since ASP.NET provides the infrastructure for the inner workings of a Web Service, developers can focus on implementing the functionality of their specific Web Service. Developing an ASP.NET Web Service starts with these two steps:

1. Declare the Web Service.
2. Define the Web Service methods that compose the functionality of the Web Service.

6.2.2.1 Declare the Web Service:

When you declare a Web Service in ASP.NET, you place the required WebService directive at the top of a text file with an .asmx file name extension. Optionally, you can apply a WebService attribute and/or derive from the WebService class. The class implementing the Web Service, which does not have to reside in the same file, can optionally derive from the WebService class. The .asmx is noticed by the ASP.NET runtime, which tell it that this is a web service. It will therefore compile the file into a .NET class that can respond as a web service, and then call up this class. As with ASP.NET pages, it will cache the compiled executable so it does not need to be recompiled for future requests.

a. To declare a Web Service whose implementation resides in the same file:

Add a WebService directive to the top of a file with an .asmx extension, specifying the class implementing the Web Service and the programming language used in the implementation.

The Class attribute can be set to a class residing in the same file as the WebService directive or within a separate file. If the class resides in a separate file, it must be placed in the \Bin directory underneath the Web application where the Web Service resides. The Language attribute can be set to C#, VB, and JS, which refer to C#, Visual Basic.NET, and JScript.NET, respectively.

The following code example (MyMath.asmx) sets the Language attribute of the WebService directive to C# and the Class attribute to MyMath, which resides in the same file. Copy the file MyMath.asmx to the PuneCSServices directory under the home directory of the default web site - for the default IIS settings, ie. C:\inetpub\wwwroot\PuneCSServices

The <%WebService... %> tag at the top of the file is needed to inform the ASP.NET runtime that this page is to be processed as a web service.

```
<%@ WebService Language="C#" Class="MyMath" %>
using System.Web.Services;
public class MyMath {
    [ WebMethod ]
    public int Add(int num1, int num2) {
        return num1+num2;
    }
}
```

Invoke this webservice by typing in IE 5.5, <http://127.0.0.1/PuneCSServices/MyMath.asmx>

b. To declare a Web Service whose implementation resides in an assembly:

Add a `WebService` directive to the top of a file with an `.asmx` extension, specifying the class implementing the Web Service, the assembly containing the implementation, and the programming language used in the implementation.

The following `WebService` directive is the only line in a file with an `.asmx` extension (example `SubtractService.asmx`), specifying that the `SubtractService` class resides in the `SubtractService` assembly within the `\bin` directory of the Web application hosting the Web Service.

```
<%@ WebService Language="C#" Class="SubtractService,SubtractService" %>
```

Note: If you do not specify an assembly within the `WebService` directive, then ASP.NET searches through the list of assemblies in the `\bin` directory of the Web application hosting the Web Service the first time the Web Service is accessed. Therefore, you will get better performance on the first access by providing the assembly name.

Copy the file `SubtractService.asmx` to the directory `C:\Inetpub\wwwroot\PuneCSServices`

Copy the file `SubtractService.cs` to the directory `C:\Inetpub\wwwroot\Bin` compile by typing at the DOS prompt `csc /t:library SubtractService.cs` to create the file `SubtractService.dll`

Invoke this webservice by typing in IE 5.5:

<http://127.0.0.1/PuneCSServices/SubtractService.asmx>

c. Deriving from the WebService Class:

Classes implementing a Web Service can optionally derive from the `WebService` Class to gain access to the common ASP.NET objects such as `Application`, `Session`, `User`, and `Context`. The `Application` and `Session` properties provide access to storing and receiving state across the lifetime of the Web application or a particular session. The `User` property contains the identity of the caller, if authentication is turned on for the Web Service. With the identity, a Web Service can determine whether the user is authorized to call the Web Service. The `Context` property provides access to all HTTP-specific information about the Web Service client's request.

The following code example (`MyUtil.asmx`) looks up the authenticated user name and returns that name.

```
<%@ WebService Language="C#" Class="MyUtil" %>
using System.Web.Services;
public class MyUtil: WebService {
    [ WebMethod(Description="Obtains the User Name") ]
    public string GetUserName() {
        return User.Identity.Name;
    }
}
```

Copy this file in the directory `C:\Inetpub\wwwroot\PuneCSServices`

Invoke this webservice by typing in IE 5.5, <http://127.0.0.1/PuneCSServices/MyUtil.asmx>

Applying the WebService Attribute:

Applying the optional `WebService` attribute to a class implementing a Web Service allows the Web Service developer to set the XML namespace the Web Service is a member of, along with setting a string to describe the Web Service.

A Web Service uses an XML document in the Web Services Description Language (WSDL), to describe Web-callable endpoints. Within the WSDL an XML namespace is used to uniquely identify these endpoints. The default value of this namespace is `<http://tempuri.org/>`.

C# - CONSOLE APPLICATIONS

It is highly recommended that this default namespace be modified before the Web Service is made publicly consumable. This is important because the Web Service needs to be distinguished from other Web Services that might be using `<http://tempuri.org/>` (the default namespace). You can change this as shown in the example `MyUtil.asmx` below. The line to be added is:

```
[WebService(Namespace="http://127.0.0.1/PuneCSServices/")]
```

6.2.2.2 Define the Web Service methods:

Methods of a class implementing a Web Service do not automatically have the ability to be invoked over the Web, but with ASP.NET it is very simple to add that capability. To add this capability, apply a `WebMethod` attribute to public methods of a class implementing a Web Service. Methods of a Web Service that can be invoked over the Web are called Web Service methods.

To declare a Web Service method:

- Declare a Web Service, adding the `WebService` directive. See 1. above.
- Add public methods to the class implementing the Web Service.
- Apply the `WebMethod` attribute to the public methods you want to be callable across the Internet.

The following code example has two public methods, both of which are Web Service methods.

```
<%@ WebService Language="C#" Class="MyUtil" %>
using System;
using System.Web.Services;
[WebService(Namespace="http://127.0.0.1/PuneCSServices/")]
public class MyUtil: WebService {
    public string GetUserName() {
        [ WebMethod(Description="Obtains the User Name") ]
        return User.Identity.Name;
    }
    [ WebMethod(Description="return the name of the Web Server hosting the Web
Service")]
    public string GetMachineName() {
        return Server.MachineName;
    }
}
```

6.2.3 Building ASP.NET Web Services:

Building a simple ASP.NET Web Service is relatively easy and is covered above. However, the true power of ASP.NET Web Services is realized when you look at the Web Services infrastructure for ASP.NET Web Services. ASP.NET Web Services are built on top of ASP.NET, which is built on top of the .NET Framework and the common language runtime, which an ASP.NET Web Service can take advantage of. For instance, the performance, state management, and authentication supported by ASP.NET can all be taken advantage of by building Web Services using ASP.NET.

The infrastructure for ASP.NET Web Services is built using industry standards such as SOAP, XML, and WSDL, and allows clients from other platforms to interoperate with ASP.NET Web Services. As long as a client can format the SOAP in a format that ASP.NET can handle and send across the Internet, that client can call an ASP.NET Web Service, regardless of the platform on which the client resides.

When you build an ASP.NET Web Service, it automatically supports clients using the SOAP, HTTP-GET, and HTTP-POST protocols to invoke Web Service methods. Since HTTP-GET and HTTP-POST support passing parameters in named value pairs, the data type support for these two protocols

are not as rich as that supported for SOAP. In SOAP, which passes data to and from the Web Service using XML, you can define complex data types using XSD schemas, supporting a richer set of data types. Developers building an ASP.NET Web Service do not have to explicitly define complex data types they expect as parameters or return types as an XSD schema, but rather they can just build a managed class. ASP.NET Web Services handles converting the class into an XSD schema to pass it back and forth across the Internet.

6.2.4 Deploying a Web Service:

Deploying a Web Service involves copying the .asmx file and any assemblies used by the Web Service not a part of the Microsoft .NET Framework to the Web server on which it will reside.

For example, suppose you have a Web Service named PuneCSServices, to deploy the Web Service you would create a virtual directory on your Web Server and then place the Web Service .asmx in that directory. The virtual directory should also be an Internet Information Services (IIS) application, although it is not required. A typical deployment would have the following directory structure:

```

\inetpub
  \wwwroot
    \PuneCSServices
      PuneCSServices.disco (optional)
      PuneCSServices.asmx
    \Bin
      Assemblies utilized by your Web Service
      that are not in the Microsoft .NET Framework.
```

/*

Microsoft SMTP Service uses the Internet-standard Simple Mail Transfer Protocol (SMTP) to transport and deliver messages based on specifications in Request for Comments (RFC) 821 and RFC 822. It also includes enhancements that build upon the basic delivery functions of the protocol. There are options available that give you control over the routing and delivery of messages, and that provide secure communications.

/*

```
// Assembly: System.Web (in System.Web.dll)
```

```
using System;
```

```
using System.Web.Mail;
```

```
public class MailClient {
```

```
    public static void Main() {
```

```
        // Provides properties and methods to construct an email message.
```

```
        // The default constructor initializes all fields to their default values.
```

```
        MailMessage mail = new MailMessage();
```

```
        // From property gets or sets the email address of the sender.
```

```
        mail.From = "medunet@vsnl.com";
```

C# - CONSOLE APPLICATIONS

```
// From property gets or sets the email address of the recipient
mail.To = "mitalit@vsnl.net";

// Subject property gets or sets the subject line of the email message.
mail.Subject = "Test Message";

// Body property gets or sets the body of the email message.
mail.Body = "This is the actual message";

// BodyFormat property gets or sets the content type of the email body.
// This is one of the MailFormat enumerated values - Html or Text
mail.BodyFormat = MailFormat.Text;

// Smtplib class provides properties and methods to send an email
// attachment using the SMTP mail service built into Microsoft Windows 2000.
// Mail is by default queued on a Windows 2000 system, ensuring that
// the calling program does not block network traffic.
// Static method Send(MailMessage) sends a mail message using arguments supplied
// in the MailMessage properties.
SmtpMail.Send(mail);
}
}
```

/*

The MessageBox class displays a message box that can contain text, buttons, and symbols that inform and instruct the user. The example below shows how you can pop-up a MessageBox. The overloaded static Show() method is used below. The MessageBoxButtons Enumeration specifies constants defining which buttons to display on a MessageBox. The MessageBoxIcon Enumeration specifies constants defining which information to display. This enumeration is used by the MessageBox class. The description of each member of this enumeration contains a typical representation of the symbol. The actual graphic displayed is a function of the operating system constants. In current implementations there are four unique symbols with multiple values assigned to them.

Assembly: System.Windows.Forms (in System.Windows.Forms.dll)

*/

using System;

```
using System.Windows.Forms;
public class ShowMsgBox {
    static void Main() {
        MessageBox.Show("You must enter a name.", "Name Entry Error",
            MessageBoxButtons.OK, MessageBoxIcon.Exclamation);
    }
}
```
